



# HAND BOOK OF AUTOMOBILES

1920

NATIONAL AUTOMOBILE  
CHAMBER OF COMMERCE  
INCORPORATED









SEVENTEENTH, ANNUAL  
**HAND BOOK OF**  
**AUTOMOBILES**



# HAND BOOK OF AUTOMOBILES

1920

**NATIONAL AUTOMOBILE CHAMBER  
OF COMMERCE INCORPORATED**

*7 East 42d Street, New York, U.S.A.*

Copyright, 1920 by the  
NATIONAL AUTOMOBILE CHAMBER OF COMMERCE, Inc.  
New York City

Engraved and Printed by  
Redfield-Kendrick-Odell Co., Inc.  
New York

## SEVENTEENTH ANNUAL ANNOUNCEMENT

**A**LTHOUGH Armistice Day found the automobile industry still absorbed in the production of material which had done much towards the successful prosecution of the war, the manufacturers, with typical energy, attacked the problem of resuming normal production of automobiles and trucks. Opportunity for new design has resulted in making the Seventeenth Annual Handbook of Automobiles of special interest, containing the most attractive and extensive line of motor cars ever shown.

The book, as heretofore, is confined to brief and uniform specifications of the principal models produced by the leading manufacturers in the United States who are members of the National Automobile Chamber of Commerce, and is prepared as a book of reference and for comparison of the principal points of construction used by the different manufacturers.

Prices where given, were determined by the makers before January 1st, and the publishers do not guarantee prices, equipment or specifications, all of which are necessarily subject to change without notice. Write the company in whose product you are interested for the latest prices, and catalogue of complete details, using the forms in the last pages of this book, or see your local dealers.

NATIONAL AUTOMOBILE  
CHAMBER OF COMMERCE, INC.

*January, 1920*





# ORGANIZATION OF NATIONAL AUTOMOBILE CHAMBER OF COMMERCE

(INCORPORATED)

7 EAST 42d STREET, NEW YORK, U. S. A.

**Detroit, Michigan**  
**Ford Building**

**Washington, D. C.**  
**Riggs Building**

## OFFICERS

CHARLES CLIFTON, <i>President</i> . . . . .	Pierce-Arrow Motor Car Company
HUGH CHALMERS, <i>Vice-President</i> . . . . .	Chalmers Motor Company
R. D. CHAPIN, <i>Second Vice-President</i> . . . . .	Hudson Motor Car Company
Passenger Car Division	
WINDSOR T. WHITE, <i>Second Vice-President</i> . . . . .	The White Motor Company
Motor Truck Division	
C. C. HANCH, <i>Secretary</i> . . . . .	Maxwell Motor Company, Inc.
H. H. RICE, <i>Treasurer</i> . . . . .	Chevrolet Motor Company

ALFRED REEVES, <i>General Manager</i>	National Automobile Chamber of Commerce
J. S. MARVIN, <i>Assistant General Manager</i>	National Automobile Chamber of Commerce
S. A. MILES, <i>Show Manager</i>	National Automobile Chamber of Commerce

## BOARD OF DIRECTORS

A. J. BROUSSEAU . . . . .	Mack Bros. Motor Car Company
HUGH CHALMERS . . . . .	Chalmers Motor Company
R. D. CHAPIN . . . . .	Hudson Motor Car Company
C. W. CHURCHILL . . . . .	The Winton Company
CHARLES CLIFTON . . . . .	Pierce-Arrow Motor Car Company
R. H. COLLINS . . . . .	Cadillac Motor Car Company
JOHN F. DODGE . . . . .	Dodge Brothers
J. WALTER DRAKE . . . . .	Hupp Motor Car Corporation
C. C. HANCH . . . . .	Maxwell Motor Company, Inc.
ALVAN MACAULEY . . . . .	Packard Motor Car Company
WM. E. METZGER . . . . .	Columbia Motors Company
R. E. OLDS . . . . .	Reo Motor Car Company
H. H. RICE . . . . .	Chevrolet Motor Company
WINDSOR T. WHITE . . . . .	The White Motor Company
JOHN N. WILLYS . . . . .	Willys-Overland, Incorporated

## FOREIGN TRADE COMMITTEE

J. WALTER DRAKE, <i>Chairman</i> . . . . .	Hupp Motor Car Corporation
P. S. STEENSTRUP . . . . .	General Motors Truck Company
H. M. ROBINS . . . . .	Dodge Brothers
JAY RATHBUN . . . . .	The White Motor Company
E. C. MORSE . . . . .	Willys-Overland, Incorporated
J. P. ROBERTS . . . . .	The Studebaker Corporation of America
H. B. PHIPPS . . . . .	Hudson Motor Car Company
H. R. COBLEIGH, <i>Secretary</i> . . . . .	National Automobile Chamber of Commerce

## HIGHWAYS COMMITTEE

R. D. CHAPIN, *Chairman* . . . . . Hudson Motor Car Company  
 WM. E. METZGER . . . . . Columbia Motors Company  
 ROYAL R. SCOTT . . . . . Willys-Overland, Incorporated  
 S. M. WILLIAMS . . . . . Garford Motor Truck Company  
 GEORGE M. GRAHAM . . . . . Pierce-Arrow Motor Car Company  
 PYKE JOHNSON, *Secretary* . . . . . National Automobile Chamber of Commerce

## PATENTS COMMITTEE

C. C. HANCH, *Chairman* . . . . . Maxwell Motor Company, Inc.  
 WINDSOR T. WHITE . . . . . The White Motor Company  
 C. W. CHURCHILL . . . . . The Winton Company  
 WILFRED C. LELAND . . . . . Lincoln Motor Company  
 WM. MACGLASHAN . . . . . The Studebaker Corporation of America  
 R. A. BRANNIGAN, *Manager* . . . . . National Automobile Chamber of Commerce

## LEGISLATIVE COMMITTEE

H. H. RICE, *Chairman* . . . . . Chevrolet Motor Company  
 D. C. FENNER . . . . . Mack Bros. Motor Car Company  
 J. I. FARLEY . . . . . Auburn Automobile Company  
 DAVID LUDLUM . . . . . The Autocar Company  
 J. I. BARROWS . . . . . Lexington Motor Company  
 HARRY MEIKELL, JR., *Secretary* . . . . . National Automobile Chamber of Commerce

## MOTOR FUEL COMMITTEE

JOHN N. WILLYS, *Chairman* . . . . . Willys-Overland, Incorporated  
 ALVAN MACAULEY . . . . . Packard Motor Car Company  
 C. W. NASH . . . . . Nash Motors Company  
 JOHN F. DODGE . . . . . Dodge Brothers  
 E. A. WILLIAMS, JR. . . . . Garford Motor Truck Company

## REPRESENTING AUTOMOTIVE INDUSTRY IN CONFERENCE WITH REPRESENTATIVES OF OIL INDUSTRY

JOHN N. WILLYS, *Chairman* . . . . . Willys-Overland, Incorporated  
 ALVAN MACAULEY . . . . . Packard Motor Car Company  
 C. W. NASH . . . . . Nash Motors Company  
 H. L. HORNING . . . . . Representing Motor and Accessory Manufacturers' Association  
 C. F. KETTERING . . . . . Representing Society of Automotive Engineers

## TRAFFIC COMMITTEE

WM. E. METZGER, *Chairman* . . . . . Columbia Motors Company  
 A. I. PHILP . . . . . Dodge Brothers  
 F. C. CHANDLER . . . . . Chandler Motor Car Company  
 WILLIAM L. DAY . . . . . General Motors Truck Company  
 GEO. M. DICKSON . . . . . National Motor Car and Vehicle Corporation  
 J. S. MARVIN, *Manager* . . . . . National Automobile Chamber of Commerce

## INSURANCE COMMITTEE

WM. E. METZGER, *Chairman* . . . . . Columbia Motors Company  
 E. T. STRONG . . . . . Buick Motor Company  
 GEO. E. GODDARD . . . . . Dodge Brothers  
 MILTON TIBBETTS . . . . . Packard Motor Car Company  
 F. L. JEWETT . . . . . Paige-Detroit Motor Car Company  
 E. A. WILLIAMS, JR. . . . . Garford Motor Truck Company  
 M. L. PULCHER . . . . . Federal Motor Truck Company

## SERVICE COMMITTEE

E. T. HERBIG, *Chairman* . . . . . Service Motor Truck Company  
 H. W. DREW . . . . . Packard Motor Car Company  
 W. M. LADD . . . . . Pierce-Arrow Motor Car Company  
 A. B. CUMNER . . . . . The Autocar Company  
 W. M. BRITTON . . . . . Republic Motor Truck Company  
 O. T. HILLSHAFTER . . . . . Chandler Motor Car Company  
 W. B. RILEY . . . . . Jordan Motor Car Company  
 H. R. COBLEIGH, *Secretary* . . . . . National Automobile Chamber of Commerce

## PASSENGER CAR STANDARDS COMMITTEE

HOWARD E. MARMON, <i>Chairman</i>	Nordyke & Marmon Company
N. E. WAHLBERG	Nash Motors Company
RALPH DAVIS	Mitchell Motors Company, Inc.
GEO. B. ALLEN	Liberty Motor Car Company
L. C. FREEMAN	Maxwell Motor Company, Inc.

## HAND BOOK COMMITTEE

E. T. STRONG, <i>Chairman</i>	Buick Motor Company
F. H. AKERS	Reo Motor Car Company
GEO. A. KISSEL	Kissel Motor Car Company
GARVIN DENBY	Denby Motor Truck Company
A. L. CURTIS, <i>Secretary</i>	National Automobile Chamber of Commerce

## CONSERVATION COMMITTEE

W. C. SILLS, <i>Chairman</i>	Chevrolet Motor Company
T. R. LIPPARD	Stewart Motor Corporation
M. COOK	Service Motor Truck Company
F. E. BRADFIELD	Velle Motors Corporation
C. A. BAIRD	Jas. Cunningham Son & Company

## PASSENGER CAR SHOW COMMITTEE

JOHN N. WILLEYS, <i>Chairman</i>	Willys-Overland, Incorporated
H. G. ROOT	Westcott Motor Car Company
HARRY M. JEWETT	Paige-Detroit Motor Car Company
S. A. MILES, <i>Manager</i>	National Automobile Chamber of Commerce

## MOTOR TRUCK COMMITTEE

WINDSOR T. WHITE, <i>Chairman</i>	The White Motor Company
RAY C. CHAMBERLIN	Packard Motor Car Company
GEORGE M. GRAHAM	Pierce-Arrow Motor Car Company
VICTOR L. BROWN	Sterling Motor Truck Company
M. L. PULCHER	Federal Motor Truck Company
R. H. SALMONS	Selden Truck Corporation
D. C. FENNER	Mack Bros. Motor Car Company
F. W. FENN, <i>Secretary</i>	National Automobile Chamber of Commerce

## RURAL MOTOR EXPRESS

JAMES L. GEDDES, <i>Chairman</i>	Kelly-Springfield Motor Truck Company
E. A. WILLIAMS, JR.	Garford Motor Truck Company
O. H. BROWNING	International Harvester Company
A. T. MURRAY	Bethlehem Motors Corporation
GEO. D. WILCOX	Commerce Motor Car Company

## TRUCK STANDARDS COMMITTEE

D. C. FENNER, <i>Chairman</i>	Mack Bros. Motor Car Company
FRANCIS W. DAVIS	Pierce-Arrow Motor Car Company
F. A. WHITTEN	General Motors Truck Company
E. M. STERNBERG	Sterling Motor Truck Company
F. F. BEALL	Packard Motor Car Company

## MOTOR TRUCK SHOW COMMITTEE

M. L. PULCHER, <i>Chairman</i>	Federal Motor Truck Company
A. J. WHIPPLE	Diamond T Motor Car Company
DAVID S. LUDLUM	The Autocar Company
S. A. MILES, <i>Manager</i>	National Automobile Chamber of Commerce

## ELECTRIC VEHICLE COMMITTEE

W. C. ANDERSON, <i>Chairman</i>	Detroit Electric Car Company
FRED R. WHITE	Baker R & L Company
H. W. SUYDAM	Milburn Wagon Company

## REPRESENTATIVES ON NATIONAL INDUSTRIAL CONFERENCE BOARD

CHARLES CLIFTON	Pierce-Arrow Motor Car Company
A. J. BROSEAU	Mack Bros. Motor Car Company

## NATIONAL COUNCILLORS TO CHAMBER OF COMMERCE, U. S. A.

CHARLES CLIFTON	Pierce-Arrow Motor Car Company
R. H. JOHNSTON	The White Motor Company, Washington, D. C.

# ALPHABETICAL INDEX

## GASOLINE PASSENGER VEHICLES

	PAGES		PAGES
Allen Motor Company, The . . .	47	Liberty Motor Car Company	48-49
Anderson Motor Company . . .	70	Locomobile Company of America . . . . .	109
Apperson Brothers Automobile Company . . . . .	124-125	Lorraine Motors Corporation	142
Auburn Automobile Co. . . . .	72-73	McFarlan Motor Company . . .	56-57
Barley Motor Car Co. . . . .	162-163	Maxwell Motor Company, Inc.	115
Bartholomew Company, The . . .	122	Mercer Motors Company	106-108
Brewster & Company, Inc. . . .	71	Mitchell Motors Co., Inc.	101-103
Briscoe Motor Corporation . . .	120	Moline Plow Company— Stephens Motor Works . . .	100
Buick Motor Company . . . . .	80-85	Moon Motor Car Co., Inc.	26-27
Cadillac Motor Car Co. . . . .	155-157	Nash Motors Company . . . . .	121
J. I. Case T. M. Company . . . .	42-45	National Motor Car & Vehicle Corporation . . . . .	112-113
Chalmers Motor Company . . . .	69	Nordyke & Marmon Company	127
Chandler Motor Car Co. . . . .	134-135	Oakland Motor Car Co. . . . .	110-111
Chevrolet Motor Company . . . .	92-95	Olds Motor Works . . . . .	96-97
Cleveland Automobile Co. . . . .	58-59	Packard Motor Car Company	123
Cole Motor Car Company . . . . .	33-41	Paige-Detroit Motor Car Company . . . . .	148-149
Columbia Motors Company	16-19	W. A. Paterson Company . . . .	153
Crow-Elkhart Motor Corpora- tion . . . . .	146-147	Peerless Motor Car Company	64-68
Jas. Cunningham Son & Co. . . .	60-61	Pierce-Arrow Motor Car Co. . .	54-55
Daniels Motor Car Company . . .	158	Pilot Motor Car Company . . .	74
George W. Davis Motor Car Company . . . . .	28	Premier Motor Corpora- tion . . . . .	104-105
Dodge Brothers . . . . .	78	Reo Motor Car Company . . . .	126
Dorris Motor Car Company . . . .	151	Root & Van Dervoort Engin- eering Company . . . . .	132
Dort Motor Car Company	116-119	Saxon Motor Car Corporation	32
Elgin Motor Car Corporation . . .	46	Sayers & Scovill Company . . .	154
Elkhart Carriage & Motor Car Company . . . . .	98-99	Scripps-Booth Corporation	140-141
F.I.A.T. . . . .	159-161	Simplex Automobile Company	139
H. H. Franklin Manufacturing Company . . . . .	75	William Small Company . . . .	76
Grant Motor Car Corporation	79	Standard Steel Car Company . .	77
Haynes Automobile Company	24-25	F. B. Stearns Company . . . .	150
Hudson Motor Car Company	29	Studebaker Corporation of America, The . . . . .	22-23
Hupp Motor Car Corpora- tion . . . . .	128-131	Stutz Motor Car Company of America, Inc. . . . .	136-137
Jackson Motors Corporation . . .	152	Templar Motors Corpora- tion, The . . . . .	50-53
Jones Motor Car Company . . . .	133	Velie Motors Corporation . . . .	86-87
Jordan Motor Car Company . . . .	144	Westcott Motor Car Co. . . . .	20-21
King Motor Car Company . . . . .	143	Willys-Overland, Incor- porated . . . . .	88-91
Kissel Motor Car Company	30-31	The Winton Company . . . . .	62-63
Kline Car Corporation . . . . .	114		
Lewis Spring & Axle Co., The	138		
Lexington Motor Company . . . .	145		



## ALPHABETICAL INDEX—Continued

### ELECTRIC VEHICLES

PAGES	PAGES
Baker R & L Company . . . 168	Oneida Motor Truck Co. . . 172
Detroit Electric Car Company 167	Ward Motor Vehicle Co. . 170-171
Milburn Wagon Company . . 169	

### GASOLINE COMMERCIAL VEHICLES

PAGES	PAGES
Acme Motor Truck Company . 177	Mack Bros. Motor Car Co. . . 209
American La-France Fire Engine Company, Inc. . 180-181	Maxwell Motor Company, Inc. 187
Atterbury Motor Car Co. . . 224	Moreland Motor Truck Co. . 190
The Autocar Company . . . 186	Nash Motors Company . 178-179
Bethlehem Motors Corporation 244	Olds Motor Works . . . . 185
Brockway Motor Truck Co. . 184	Oneida Motor Truck Co. . 236-238
Clydesdale Motor Truck Company . . . . . 240-241	Packard Motor Car Company 246
Commerce Motor Car Co. . . 228	Paige-Detroit Motor Car Company . . . . . 230-231
Corbitt Motor Truck Co. . . 221	Pierce-Arrow Motor Car Company . . . . . 182-183
Denby Motor Truck Company 203	Reo Motor Car Company . . 193
Diamond T Motor Car Co. . . 176	Republic Motor Truck Co., Inc. 243
Dodge Brothers . . . . . 201	Rowe Motor Manufacturing Company . . . . . 226
Dorris Motor Car Company . 233	Sanford Motor Truck Co. . . 245
Duplex Truck Company 222-223	G. A. Schacht Motor Truck Company . . . . . 198-199
Federal Motor Truck Co. 234-235	Selden Truck Corporation 210-211
Garford Motor Truck Co. 216-219	Service Motor Truck Co. . 196-197
General Motors Truck Co. . . 200	Standard Motor Truck Co. . . 175
International Harvester Co. . 225	Sterling Motor Truck Co. . . 239
Jackson Motors Corporation . 232	Stewart Motor Corporation . 229
Jones Motor Car Company . . 202	United Motors Company . . 227
Kelly-Springfield Motor Truck Company . . . . . 194-195	Velie Motors Corporation . . 215
Kissel Motor Car Co. . . 212-214	Vim Motor Truck Company . 191
Kleiber & Company, Inc. . . 220	Walter Motor Truck Co. . . 242
Locomobile Company of America . . . . . 189	The White Motor Company 204-208
Maccar Truck Company . . . 192	J. C. Wilson Company . . . 188

# INDEX OF TRADE NAMES

## GASOLINE PASSENGER VEHICLES

	PAGES		PAGES
Allen . . . . .	47	Liberty . . . . .	48-49
Anderson . . . . .	70	Locomobile . . . . .	109
Apperson . . . . .	124-125	Lorraine . . . . .	142
Auburn . . . . .	72-73	McFarlan . . . . .	56-57
Brewster . . . . .	71	Marmon . . . . .	127
Briscoe . . . . .	120	Maxwell . . . . .	115
Buick . . . . .	80-85	Mercer . . . . .	106-108
Cadillac . . . . .	155-157	Mitchell . . . . .	101-103
Case . . . . .	42-45	Monroe . . . . .	76
Chalmers . . . . .	69	Moon . . . . .	26-27
Chandler . . . . .	134-135	Nash . . . . .	121
Chevrolet . . . . .	92-95	National . . . . .	112-113
Cleveland . . . . .	58-59	Oakland . . . . .	110-111
Cole . . . . .	33-41	Oldsmobile . . . . .	96-97
Columbia . . . . .	16-19	Overland . . . . .	88-89
Crow-Elkhart . . . . .	146-147	Packard . . . . .	123
Cunningham . . . . .	60-61	Paige . . . . .	148-149
Daniels . . . . .	158	Paterson . . . . .	153
Davis . . . . .	28	Peerless . . . . .	64-68
Dodge Brothers . . . . .	78	Pierce-Arrow . . . . .	54-55
Dorris . . . . .	151	Pilot . . . . .	74
Dort . . . . .	116-119	Premier . . . . .	104-105
Elgin . . . . .	46	Reo . . . . .	126
Elcar . . . . .	98-99	Roamer . . . . .	162-163
Fiat . . . . .	159-161	R & V Knight . . . . .	132
Franklin . . . . .	75	Saxon . . . . .	32
Glide . . . . .	122	Sayers-Six . . . . .	154
Grant . . . . .	79	Scripps-Booth . . . . .	140-141
Haynes . . . . .	24-25	Simplex . . . . .	139
Hollier . . . . .	138	Standard . . . . .	77
Hudson . . . . .	29	Stearns-Knight . . . . .	150
Hupmobile . . . . .	128-131	Stephens . . . . .	100
Jackson . . . . .	152	Studebaker . . . . .	22-23
Jones . . . . .	133	Stutz . . . . .	136-137
Jordan . . . . .	144	Templar . . . . .	50-53
King . . . . .	143	Velie . . . . .	86-87
Kissel Kar . . . . .	30-31	Westcott . . . . .	20-21
Kline Kar . . . . .	114	Willys-Knight . . . . .	90-91
Lexington . . . . .	145	Winton . . . . .	62-63

# INDEX OF TRADE NAMES—Continued

## ELECTRIC VEHICLES

	PAGES		PAGES
Detroit Electric . . . . .	167	Oneida Electric . . . . .	172
Milburn Electric . . . . .	169	Ward . . . . .	170-171
Raulang . . . . .	168		

## GASOLINE COMMERCIAL VEHICLES

Acme . . . . .	177	Maxwell . . . . .	187
American La-France . . . . .	180-181	Moreland . . . . .	190
Atterbury . . . . .	224	Nash . . . . .	178-179
Autocar . . . . .	186	Oldsmobile . . . . .	185
Bethlehem . . . . .	244	Oneida . . . . .	236-238
Brockway . . . . .	184	Packard . . . . .	246
Clydesdale . . . . .	240-241	Paige . . . . .	230-231
Commerce . . . . .	228	Pierce-Arrow . . . . .	182-183
Corbitt . . . . .	221	Reo . . . . .	193
Denby . . . . .	203	Republic . . . . .	243
Diamond T . . . . .	176	Riker . . . . .	189
Dodge Brothers . . . . .	201	Rowe . . . . .	226
Dorris . . . . .	233	Sanford . . . . .	245
Duplex . . . . .	222-223	Schacht . . . . .	198-199
Federal . . . . .	234-235	Selden . . . . .	210-211
Garford . . . . .	216-219	Service . . . . .	196-197
G M C . . . . .	200	Standard . . . . .	175
International . . . . .	225	Sterling . . . . .	239
Jackson . . . . .	232	Stewart . . . . .	229
Jones . . . . .	202	United . . . . .	227
Kelly-Springfield . . . . .	194-195	Velie . . . . .	215
Kissel . . . . .	212-214	Vim . . . . .	191
Kleiber . . . . .	220	Walter . . . . .	242
Maccar . . . . .	192	White . . . . .	204-208
Mack . . . . .	209	Wilson . . . . .	188

## N. A. C. C. HORSE-POWER RATING

The standard horse-power rating, formerly known as the A. L. A. M. Rating, has been officially adopted by the National Automobile Chamber of Commerce, Inc.

The formula adopted is  $\frac{D^2 \times N}{2.5}$ . D is the cylinder bore in inches, N the number of cylinders, and 2.5 a constant, based on the average view of eminent engineers as to a fair, conservative rating for a four-cycle motor at one thousand feet per minute piston speed.

**TABLE OF HORSE-POWER FOR USUAL SIZES OF MOTORS**

INS.	2 CYLS.	4 CYLS.	6 CYLS.	8 CYLS.	12 CYLS.
2½	5.00	10.00	15.00	20.00	30.00
2¾	5.50	11.03	16.54	22.05	33.08
3¼	6.00	12.10	18.15	24.20	36.30
2⅞	6.62	13.23	19.84	26.45	39.68
3	7.20	14.40	21.60	28.80	43.20
3⅛	7.81	15.63	23.44	31.25	46.88
3¼	8.50	16.90	25.35	33.80	50.70
3⅝	9.12	18.23	27.34	36.45	54.68
3½	9.80	19.60	29.40	39.20	58.80
3⅞	10.50	21.03	31.54	42.05	63.08
3¾	11.25	22.50	33.75	45.00	67.50
3⅞	12.00	24.03	36.04	48.05	72.08
4	12.80	25.60	38.40	51.20	76.80
4⅛	13.62	27.23	40.84	54.45	81.68
4¼	14.50	28.90	43.35	57.80	86.70
4⅝	15.31	30.63	45.94	61.25	91.88
4½	16.20	32.40	48.60	64.80	97.20
4⅞	17.12	34.23	51.34	68.45	102.68
4¾	18.00	36.10	54.15	72.20	108.30
4⅞	19.00	38.03	57.04	76.05	114.08
5	20.00	40.00	60.00	80.00	120.00
5⅛	21.00	42.03	63.04	84.05	126.08
5¼	22.00	44.10	66.15	88.20	132.30
5⅝	23.00	46.23	69.34	92.45	138.68
5½	24.20	48.40	72.60	96.80	145.20
5⅞	25.31	50.63	75.94	101.25	151.88
5¾	26.50	52.90	79.35	105.80	158.70
5⅞	27.62	55.23	82.84	110.45	165.68
6	28.80	57.60	86.40	115.20	172.80

**ILLUSTRATIONS AND  
SPECIFICATIONS  
GASOLINE  
PASSENGER  
VEHICLES**


---



**COLUMBIA  
MOTORS  
COMPANY**

**DETROIT  
MICHIGAN**

**Price, \$1695**




---

**COLUMBIA SIX TOURING—20-C**

---


COLOR . . . . .	Body, blue or maroon; running gear, black	BORE AND STROKE . . . . .	3¼ x 4¼ inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Force feed and splash
POSITION OF DRIVER. . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	115 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	32 x 4 inches	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4 inches	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheel drums	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheel drums	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry plate
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	25.35 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, electric horn and demountable rims.

# COLUMBIA MOTORS COMPANY

DETROIT  
MICHIGAN

Price, \$1845



## COLUMBIA SIX ROADSTER—20-E


<b>COLOR</b> . . . . .	Body, Petain gray; running gear, black	<b>LUBRICATION</b> . . . . .	Force feed and splash
<b>SEATING CAPACITY</b> . . . . .	Two	<b>RADIATOR</b> . . . . .	Cellular
<b>POSITION OF DRIVER.</b> . . . .	Left side	<b>COOLING</b> . . . . .	Water pump
<b>WHEELBASE</b> . . . . .	115 inches	<b>IGNITION</b> . . . . .	Storage battery
<b>GAUGE</b> . . . . .	56 inches	<b>STARTING SYSTEM</b> . . . . .	Two unit
<b>WHEELS</b> . . . . .	Disteel	<b>STARTER OPERATED</b> . . . . .	Gear to fly wheel
<b>FRONT TIRES</b> . . . . .	32 x 4 inches	<b>LIGHTING SYSTEM</b> . . . . .	Electric
<b>REAR TIRES</b> . . . . .	32 x 4 inches	<b>VOLTAGE</b> . . . . .	Six
<b>SERVICE BRAKE</b> . . . . .	Contracting on rear wheel drums	<b>WIRING SYSTEM</b> . . . . .	Single
<b>EMERGENCY BRAKE</b> . . . . .	Expanding on rear wheel drums	<b>GASOLINE SYSTEM</b> . . . . .	Vacuum
<b>CYLINDERS</b> . . . . .	Six	<b>CLUTCH</b> . . . . .	Dry multiple disc
<b>HOW ARRANGED</b> . . . . .	Vertically	<b>TRANSMISSION</b> . . . . .	Selective sliding
<b>CAST</b> . . . . .	En bloc	<b>GEAR CHANGES</b> . . . . .	Three forward, one reverse
<b>HORSEPOWER</b> . . . . .	25.35 (N.A.C.C. Rating)	<b>DRIVE</b> . . . . .	Spiral bevel
<b>BORE AND STROKE</b> . . . . .	3¼ x 4½ inches	<b>REAR AXLE</b> . . . . .	Semi-floating
		<b>STEERING GEAR</b> . . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, electric horn and demountable rims.

**COLUMBIA  
MOTORS  
COMPANY**

**DETROIT  
MICHIGAN**

**Price, \$1845**




---

**COLUMBIA SIX SPORT—20-D**

---

COLOR . . . . .	Body, Venetian blue; running gear, black	BORE AND STROKE . . . . .	3¼ x 4½ inches
SEATING CAPACITY . . . . .	Four	LUBRICATION . . . . .	Force feed and splash
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	115 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wire	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	32 x 4 inches	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4 inches	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheel drums	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheel drums	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry plate
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	25.35 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear


In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, electric horn and demountable rims.

---

**COLUMBIA  
MOTORS  
COMPANY.**

**DETROIT  
MICHIGAN**

Price . . . . . \$2850  
Four-Passenger Coupe—20-H . . 2850



**COLUMBIA SIX SEDAN—20-CS**


COLOR . . . . .	Body, blue or maroon; running gear, black	LUBRICATION . . . .	Force feed and splash
SEATING CAPACITY .	Five	RADIATOR . . . . .	Cellular
POSITION OF DRIVER.	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . .	115 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . . .	32 x 4 inches	LIGHTING SYSTEM .	Electric
REAR TIRES . . . .	32 x 4 inches	VOLTAGE . . . . .	Six
SERVICE BRAKE . . .	Contracting on rear wheel drums	WIRING SYSTEM . .	Single
EMERGENCY BRAKE .	Expanding on rear wheel drums	GASOLINE SYSTEM .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry plate
HOW ARRANGED . . .	Vertically	TRANSMISSION . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . .	Three forward, one reverse
HORSEPOWER . . . .	25.35 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE .	3 1/4 x 4 1/2 inches	REAR AXLE . . . .	Semi-floating
		STEERING GEAR . . .	Worm and gear

In addition to above specifications, price includes windshield, speedometer, ammeter, voltmeter, electric horn and demountable rims.

**WESTCOTT  
MOTOR CAR  
COMPANY**

**SPRINGFIELD  
O H I O**

<b>Price . . . . .</b>	<b>\$2390</b>
<b>Two-Passenger Roadster . . . . .</b>	<b>2390</b>
<b>Three-Passenger Coupe . . . . .</b>	<b>3190</b>
<b>Five-Passenger Sedan . . . . .</b>	<b>3490</b>




---

**WESTCOTT TOURING—TYPE C-38**

---

<b>COLOR . . . . .</b>	Optional	<b>LUBRICATION . . . . .</b>	Force feed and splash
<b>SEATING CAPACITY . . . . .</b>	Five	<b>RADIATOR . . . . .</b>	Cellular
<b>POSITION OF DRIVER . . . . .</b>	Left side	<b>COOLING . . . . .</b>	Water pump
<b>WHEELBASE . . . . .</b>	118 inches	<b>IGNITION . . . . .</b>	Storage battery
<b>GAUGE . . . . .</b>	56 inches	<b>STARTING SYSTEM . . . . .</b>	Three unit
<b>WHEELS . . . . .</b>	Wood	<b>STARTER OPERATED . . . . .</b>	Double reduced gear to fly wheel
<b>FRONT TIRES . . . . .</b>	33 x 4 inches, cord non-skid	<b>LIGHTING SYSTEM . . . . .</b>	Electric
<b>REAR TIRES . . . . .</b>	33 x 4 inches, cord non-skid	<b>VOLTAGE . . . . .</b>	Six
<b>SERVICE BRAKE . . . . .</b>	Contracting on rear wheels	<b>WIRING SYSTEM . . . . .</b>	Single
<b>EMERGENCY BRAKE . . . . .</b>	Expanding on rear wheels	<b>GASOLINE SYSTEM . . . . .</b>	Vacuum
<b>CYLINDERS . . . . .</b>	Six	<b>CLUTCH . . . . .</b>	Dry plate
<b>HOW ARRANGED . . . . .</b>	Vertically	<b>TRANSMISSION . . . . .</b>	Selective sliding
<b>CAST . . . . .</b>	En bloc	<b>GEAR CHANGES . . . . .</b>	Three forward, one reverse
<b>HORSEPOWER . . . . .</b>	25.35 (N.A.C.C. Rating)	<b>DRIVE . . . . .</b>	Spiral bevel
<b>BORE AND STROKE . . . . .</b>	3 1/4 x 4 1/2 inches	<b>REAR AXLE . . . . .</b>	Semi-floating
		<b>STEERING GEAR . . . . .</b>	Worm and wheel

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, radimeter, clock, tire pump, gasoline gauge on dash, electric horn and demountable rims.


---



# WESTCOTT MOTOR CAR COMPANY

SPRINGFIELD  
O H I O

Price . . . . .	\$2890
Five-Passenger Touring . . . . .	2890
Seven-Passenger Limousine Sedan . . . . .	4490



## WESTCOTT TOURING—TYPE C-48


COLOR . . . . .	Optional	BORE AND STROKE . . . . .	3½ x 5¼ inches
SEATING CAPACITY . . . . .	Seven	LUBRICATION . . . . .	Force feed and splash
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	125 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Three unit
FRONT TIRES . . . . .	32 x 4½ inches, cord, non-skid	STARTER OPERATED . . . . .	Double reduced gear to fly wheel
REAR TIRES . . . . .	32 x 4½ inches, cord, non-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry plate
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	29.4 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and wheel

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, radimeter, clock, tire pump, gasoline gauge on dash, electric horn and demountable rims.

**THE  
STUDEBAKER  
CORPORATION  
OF AMERICA**

**SOUTH BEND  
INDIANA**

Price . . . . .	\$1685
Four - Passenger Roadster . . . . .	1685
Coupe . . . . .	2485
Sedan . . . . .	2685



**STUDEBAKER SPECIAL SIX TOURING**


COLOR . . . . .	Body, dark blue; running gear, black	LUBRICATION . . . . .	Splash with circulating pump
SEATING CAPACITY . . . . .	Five	RADIATOR . . . . .	Tubular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	119 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Chain to crank shaft
FRONT TIRES . . . . .	32 x 4 inches, cord	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	32 x 4 inches, cord, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Cone
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	29.4 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3½ x 5 inches	REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, wind-  
shield, speedometer, ammeter, electric horn and demountable rims.

**THE  
STUDEBAKER  
CORPORATION  
OF AMERICA**

**SOUTH BEND  
INDIANA**

**Price, \$2135**




---

**STUDEBAKER BIG SIX TOURING**

---


<b>COLOR . . . . .</b>	Body, Brewster green; running gear, black	<b>BORE AND STROKE . . . . .</b>	3¼ x 5 inches
<b>SEATING CAPACITY . . . . .</b>	Seven	<b>LUBRICATION . . . . .</b>	Splash with circulating pump
<b>POSITION OF DRIVER . . . . .</b>	Left side	<b>RADIATOR . . . . .</b>	Tubular
<b>WHEELBASE . . . . .</b>	126 inches	<b>COOLING . . . . .</b>	Water pump
<b>GAUGE . . . . .</b>	56 inches	<b>IGNITION . . . . .</b>	Storage battery
<b>WHEELS . . . . .</b>	Wood	<b>STARTING SYSTEM . . . . .</b>	Two unit
<b>FRONT TIRES . . . . .</b>	33 x 4½ inches, cord	<b>STARTER OPERATED . . . . .</b>	Chain to crank shaft
<b>REAR TIRES . . . . .</b>	33 x 4½ inches, cord, anti-skid	<b>LIGHTING SYSTEM . . . . .</b>	Electric
<b>SERVICE BRAKE . . . . .</b>	Contracting on rear wheels	<b>VOLTAGE . . . . .</b>	Six
<b>EMERGENCY BRAKE . . . . .</b>	Expanding on rear wheels	<b>WIRING SYSTEM . . . . .</b>	Single
<b>CYLINDERS . . . . .</b>	Six	<b>GASOLINE SYSTEM . . . . .</b>	Vacuum
<b>HOW ARRANGED . . . . .</b>	Vertically	<b>CLUTCH . . . . .</b>	Cone
<b>CAST . . . . .</b>	En bloc	<b>TRANSMISSION . . . . .</b>	Selective sliding
<b>HORSEPOWER . . . . .</b>	36.04 (N.A.C.C. Rating)	<b>GEAR CHANGES . . . . .</b>	Three forward, one reverse
		<b>DRIVE . . . . .</b>	Spiral bevel
		<b>REAR AXLE . . . . .</b>	Semi-floating
		<b>STEERING GEAR . . . . .</b>	Worm and gear

In addition to above specifications price includes top, top hood, wind-shield, speedometer, ammeter, clock, electric horn and demountable rims.

---

**HAYNES  
AUTOMOBILE  
COMPANY**  
K O K O M O  
I N D I A N A

Price . . . . .	\$2685
Four-Passenger Roadster—45 . . .	2685
Coupe—45 . . . . .	3300
Sedan—45 . . . . .	3550
Limousine—45 . . . . .	4200



**HAYNES LIGHT SIX TOURING—45**


COLOR . . . . .	Body, Brewster green; running gear, black	BORE AND STROKE . . . . .	3½ x 5 inches
SEATING CAPACITY . . . . .	Seven	LUBRICATION . . . . .	Splash with circulating pump
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	127 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery and generator distributor
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	34 x 4½ inches, cord	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	34 x 4½ inches, cord, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Expanding on rear axle	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear axle	WIRING SYSTEM . . . . .	Double
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	29.4 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . . . .	Worm and nut

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, clock, tire pump, electric horn and demountable rims.

# HAYNES AUTOMOBILE COMPANY

K O K O M O  
I N D I A N A

Price . . . . .	\$4200
Four-Passenger Coupe—46 . . .	4000
Seven-Passenger Touring—46 . .	3450
Four-Passenger Roadster—46 . .	3450



## HAYNES LIGHT TWELVE SEDAN—46


COLOR . . . . .	Body, Classic Haynes blue; running gear, black	BORE AND STROKE . . .	2¼ x 5 inches
SEATING CAPACITY .	Seven	LUBRICATION . . . . .	Full force feed
POSITION OF DRIVER.	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	127 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery and distributor
WHEELS . . . . .	Wire	STARTING SYSTEM . .	Two unit
FRONT TIRES . . . .	34 x 4½ inches, cord	STARTER OPERATED .	Gear to fly wheel
REAR TIRES . . . . .	34 x 4½ inches, cord, anti-skid	LIGHTING SYSTEM . .	Electric
SERVICE BRAKE . . .	Expanding on rear axle	VOLTAGE . . . . .	Six
EMERGENCY BRAKE .	Expanding on rear axle	WIRING SYSTEM . . .	Double
CYLINDERS . . . . .	Twelve	GASOLINE SYSTEM . .	Vacuum
HOW ARRANGED . . .	V type, 60 degrees	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	In sixes	TRANSMISSION . . . .	Selective sliding
HORSEPOWER . . . .	36.3 (N.A.C.C. Rating)	GEAR CHANGES . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . .	Screw and nut

In addition to above specifications, price includes windshield, speedometer, ammeter, clock, tire pump, electric horn and demountable rims.

# MOON MOTOR CAR COMPANY

ST. LOUIS  
MISSOURI

Price . . . . \$1985  
Roadster . . . . 2085  
Sedan . . . . 2885  
Coupe . . . . 2885



## MOON 6-48 MODEL

COLOR . . . . .	Body, marine blue; running gear, black	LUBRICATION . . . .	Force feed and splash
SEATING CAPACITY .	Five	RADIATOR . . . . .	Cellular
POSITION OF DRIVER	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . .	122 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . . .	32 x 4 inches	LIGHTING SYSTEM . .	Electric
REAR TIRES . . . .	32 x 4 inches	VOLTAGE . . . . .	Six
SERVICE BRAKE . . .	Contracting on rear axle	WIRING SYSTEM . . .	Single
EMERGENCY BRAKE .	Expanding on rear axle	GASOLINE SYSTEM . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry plate
HOW ARRANGED . . .	Vertically	TRANSMISSION . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . .	Three forward, one reverse
HORSEPOWER . . . .	25.35 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE .	3 1/4 x 4 1/2 inches	REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . .	Worm and gear

In addition to above specifications, price includes top, top hood, wind-  
shield, speedometer, ammeter, electric horn and demountable rims.

# MOON MOTOR CAR COMPANY

ST. LOUIS  
MISSOURI

Price . . . . \$2750  
Roadster . . . 2750  
Coupe . . . . 3650  
Sedan . . . . 3750




## MOON TOURING—6-68

COLOR . . . . .	Body, green or maroon; running gear, black	LUBRICATION . . . .	Force feed and splash
SEATING CAPACITY .	Seven	RADIATOR . . . . .	Cellular
POSITION OF DRIVER	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . .	125 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . . .	33 x 5 inches	LIGHTING SYSTEM . .	Electric
REAR TIRES . . . .	33 x 5 inches	VOLTAGE . . . . .	Six
SERVICE BRAKE . . .	Contracting on rear axle	WIRING SYSTEM . . .	Single
EMERGENCY BRAKE .	Expanding on rear axle	GASOLINE SYSTEM . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry plate
HOW ARRANGED . . .	Vertically	TRANSMISSION . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . .	Three forward, one reverse
HORSEPOWER . . . .	29.4 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE .	3½ x 5¼ inches	REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, wind-shield, speedometer, ammeter, tire pump, electric horn and demountable rims.

**GEO. W. DAVIS  
MOTOR CAR  
COMPANY**  
RICHMOND  
INDIANA

Price . . . . .	\$1985
Four-Passenger Sport—52 . . .	2025
Four-Passenger Special Sport—53	2150
Five-Passenger Sedan—54 . . .	2985
Four-Passenger Coupe—55 . . .	2985




---

**DAVIS FIVE-PASSENGER TOURING—51**

---

COLOR . . . . .	Body, green or blue; running gear, black	LUBRICATION . . . .	Force feed
SEATING CAPACITY .	Five	RADIATOR . . . . .	Cellular
POSITION OF DRIVER.	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . .	120 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM .	Single unit
WHEELS . . . . .	Wood	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . . .	33 x 4 inches	LIGHTING SYSTEM .	Electric
REAR TIRES . . . .	33 x 4 inches, non-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . .	Contracting on rear axle	WIRING SYSTEM . .	Single
EMERGENCY BRAKE .	Expanding on rear axle	GASOLINE SYSTEM .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry single plate
HOW ARRANGED . .	Vertically	TRANSMISSION . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . .	Three forward, one reverse
HORSEPOWER . . . .	25.35 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE .	3¼ x 4½ inches	REAR AXLE . . . .	Full floating
		STEERING GEAR . .	Worm and gear


In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.



# HUDSON MOTORCAR COMPANY

DETROIT  
MICHIGAN

Seven-Passenger Phaeton . . .	} Prices Upon Appli- cation
Four-Passenger Phaeton . . .	
Sedan . . . . .	
Coupe . . . . .	
Touring Limousine . . . . .	
Limousine . . . . .	




## HUDSON SUPER-SIX PHAETON

COLOR . . . . .	Body, Valentine blue; running gear, blue enamel; fenders and splash guards, black enamel	HORSEPOWER . . . . .	29.4 (N.A.C.C. Rating)
SEATING CAPACITY . . . . .	Seven	BORE AND STROKE . . . . .	3½ x 5 inches
POSITION OF DRIVER . . . . .	Left side	LUBRICATION . . . . .	Splash with circulating pump
WHEELBASE . . . . .	125¼ inches	RADIATOR . . . . .	Cellular
GAUGE . . . . .	56 inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Wood	IGNITION . . . . .	Storage battery
FRONT TIRES . . . . .	34 x 4½ inches, anti-skid	STARTING SYSTEM . . . . .	Single unit
REAR TIRES . . . . .	34 x 4½ inches, anti-skid	STARTER OPERATED . . . . .	Gear to fly wheel
SERVICE BRAKE . . . . .	Contracting on rear wheels	LIGHTING SYSTEM . . . . .	Electric
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	VOLTAGE . . . . .	Six
CYLINDERS . . . . .	Six	WIRING SYSTEM . . . . .	Single
HOW ARRANGED . . . . .	Vertically	GASOLINE SYSTEM . . . . .	Vacuum
CAST . . . . .	En bloc	CLUTCH . . . . .	Multiple disc in oil
		TRANSMISSION . . . . .	Selective sliding
		GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.

**KISSEL MOTOR  
CAR COMPANY**  
HARTFORD  
WISCONSIN

Two-Passenger Speedster . . .	} Prices Upon Appli- cation
Seven-Passenger Touring . . .	
Four-Passenger Coupe . . . .	
Six-Passenger Sedan . . . . .	
Six-Passenger Urban-Sedan . .	



**KISSEL CUSTOM-BUILT FOUR-PASSENGER TOURSTER**


COLOR . . . . .	Blue with cream wheels	BORE AND STROKE . . .	3 1/4 x 5 1/2 inches
SEATING CAPACITY . .	Four	LUBRICATION . . . . .	Force feed and splash
POSITION OF DRIVER .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	124 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wire	STARTING SYSTEM . . .	Two unit
FRONT TIRES . . . . .	32 x 4 1/2 inches, cord	STARTER OPERATED . .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4 1/2 inches, cord, non-skid	LIGHTING SYSTEM . . .	Electric
SERVICE BRAKE . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . .	Contracting on rear wheels	WIRING SYSTEM . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . .	Vacuum
HOW ARRANGED . . . .	Vertically	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	26.3 (N.A.C.C. Rating)	GEAR CHANGES . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Screw and split nut

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, clock, electric horn and demountable rims.

# KISSEL MOTOR CAR COMPANY

HARTFORD  
WISCONSIN

Two-Passenger Speedster . . .	} Prices Upon Appli- cation
Four-Passenger Tourster . . .	
Seven-Passenger Touring . . .	
Six-Passenger Sedan . . .	
Six-Passenger Urban-Sedan . . .	



## KISSEL CUSTOM-BUILT FOUR-PASSENGER COUPE

COLOR . . . . .	Blue with cream wheels	BORE AND STROKE . .	3 $\frac{1}{8}$ x 5 $\frac{1}{2}$ inches
SEATING CAPACITY . .	Four	LUBRICATION . . . .	Force feed and splash
POSITION OF DRIVER .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	124 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wire	STARTING SYSTEM . .	Two unit
FRONT TIRES . . . . .	32 x 4 $\frac{1}{2}$ inches, cord	STARTER OPERATED .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4 $\frac{1}{2}$ inches, cord, non-skid	LIGHTING SYSTEM . .	Electric
SERVICE BRAKE . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . .	Contracting on rear wheels	WIRING SYSTEM . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . .	Vacuum
HOW ARRANGED . . .	Vertically	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	En bloc	TRANSMISSION . . .	Selective sliding
HORSEPOWER . . . . .	26.3 (N.A.C.C. Rating)	GEAR CHANGES . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Full floating
		STEERING GEAR . . .	Screw and split nut

In addition to above specifications, price includes windshield, speedometer, ammeter, voltmeter, clock, electric horn and demountable rims.

# SAXON MOTOR CAR CORPORATION

DETROIT  
MICHIGAN

Price Upon Application



## SAXON TOURING

COLOR . . . . .	Body, blue; running gear, black	BORE AND STROKE .	3¼ x 5 inches
SEATING CAPACITY .	Five	LUBRICATION . . . .	Force feed
POSITION OF DRIVER.	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	112 inches	COOLING . . . . .	Thermo-syphon
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM .	Two unit
FRONT TIRES . . . .	32 x 4 inches	STARTER OPERATED .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4 inches, anti-skid	LIGHTING SYSTEM .	Electric
SERVICE BRAKE . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE .	Expanding on rear wheels	WIRING SYSTEM . .	Single
CYLINDERS . . . . .	Four	GASOLINE SYSTEM .	Vacuum
HOW ARRANGED . . .	Vertically	CLUTCH . . . . .	Dry plate
CAST . . . . .	En bloc	TRANSMISSION . . .	Selective sliding
HORSEPOWER . . . .	15.6 (N.A.C.C. Rating)	GEAR CHANGES . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . .	Worm and gear


In addition to above specifications, price includes top, top hood, wind-shield, speedometer, ammeter, electric horn and demountable rims.

**C O L E  
MOTOR CAR  
COMPANY**  

---

**INDIANAPOLIS  
I N D I A N A**

Price . . . . .	\$2850
Roadster—871 . . . .	2850
Sportster—872 . . . .	2850
Sportsedan—878 . . . .	4150
Sportosine—879 . . . .	4250
Sportcoupe—883 . . . .	4050
Tourosine—884 . . . .	4250
Toursedan—885 . . . .	4250
Towncar—887 . . . .	4150




---

**COLE AERO-EIGHT TOURSTER—870**

---

COLOR . . . . .	Cole blue or gray and black	LUBRICATION . . . .	Force feed
SEATING CAPACITY .	Seven	RADIATOR . . . . .	Cellular
POSITION OF DRIVER.	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . .	127 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM .	Single unit
WHEELS . . . . .	Wood	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . . .	33 x 5 inches, cord	LIGHTING SYSTEM .	Electric
REAR TIRES . . . .	33 x 5 inches, cord, anti-skid	VOLTAGES . . . . .	Six to eight
SERVICE BRAKE . .	Contracting on rear wheels	WIRING SYSTEM . .	Single
EMERGENCY BRAKE .	Expanding on rear wheels	GASOLINE SYSTEM .	Vacuum
CYLINDERS . . . . .	Eight	CLUTCH . . . . .	Cone
HOW ARRANGED . .	V type, 90 degrees	TRANSMISSION . . .	Selective sliding
CAST . . . . .	In fours	GEAR CHANGES . .	Three forward, one reverse
HORSEPOWER . . . .	39.2 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE .	3½ x 4½ inches	REAR AXLE . . . .	Full floating
		STEERING GEAR . .	Worm and gear


In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, clock, tire pump, electric horn and demountable rims.

**C O L E  
MOTOR CAR  
COMPANY**  

---

**INDIANAPOLIS  
I N D I A N A**

Price . . . . .	\$4250
Tourster—870 . . . . .	2850
Roadster—871 . . . . .	2850
Sportster—872 . . . . .	2850
Sportsedan—878 . . . . .	4150
Sportosine—879 . . . . .	4250
Sportcoupe—883 . . . . .	4050
Tourosine—884 . . . . .	4250
Towncar—887 . . . . .	4150




---

**COLE AERO-EIGHT TOURSEDAN—885**

---

COLOR . . . . .	Cole blue and black	LUBRICATION . . . . .	Force feed
SEATING CAPACITY . . . . .	Seven	RADIATOR . . . . .	Cellular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	127 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Single unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	33 x 5 inches, cord	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	33 x 5 inches, cord, anti-skid	VOLTAGES . . . . .	Six to eight
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Eight	CLUTCH . . . . .	Cone
HOW ARRANGED . . . . .	V type, 90 degrees	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	In fours	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	39.2 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3½ x 4½ inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and gear


In addition to above specifications, price includes windshield, speedometer, ammeter, clock, tire pump, electric horn and demountable rims.

---

# COLE MOTOR CAR COMPANY

INDIANAPOLIS  
INDIANA


Price . . . . .	\$4250
Tourster—870 . . . . .	2850
Roadster—871 . . . . .	2850
Sportster—872 . . . . .	2850
Sportsedan—878 . . . . .	4150
Sportosine—879 . . . . .	4250
Sportcoupe—883 . . . . .	4050
Toursedan—885 . . . . .	4250
Towncar—887 . . . . .	4150



## COLE AERO-EIGHT TOUROSINE—884

COLOR . . . . .	Cole blue and black	BORE AND STROKE . . . . .	3½ x 4½ inches
SEATING CAPACITY . . . . .	Seven	LUBRICATION . . . . .	Force feed
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	127 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Single unit
FRONT TIRES . . . . .	33 x 5 inches, cord	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	33 x 5 inches, cord, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGES . . . . .	Six to eight
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Eight	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	V type, 90 degrees	CLUTCH . . . . .	Cone
CAST . . . . .	In fours	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	39.2 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes windshield, speedometer, ammeter, clock, tire pump, electric horn and demountable rims.




### CASE TOURING—V

COLOR . . . . .	Blue	LUBRICATION . . . .	Force feed and splash
SEATING CAPACITY .	Seven	RADIATOR . . . . .	Tubular
POSITION OF DRIVER.	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . .	126 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM .	Single unit
WHEELS . . . . .	Wood	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . .	34 x 4½ inches	LIGHTING SYSTEM .	Electric
REAR TIRES . . . .	34 x 4½ inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . .	Contracting on rear wheels	WIRING SYSTEM . .	Single
EMERGENCY BRAKE .	Expanding on rear wheels	GASOLINE SYSTEM .	Vacuum
CYLINDERS . . . .	Six	CLUTCH . . . . .	Dry plate
HOW ARRANGED . .	Vertically	TRANSMISSION . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . .	Three forward, one reverse
HORSEPOWER . . . .	29.4 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE .	3½ x 5½ inches	REAR AXLE . . . .	Three-quarters floating
		STEERING GEAR . .	Screw and nut

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, motometer, tire pump, electric horn, demountable rims and one extra rin, without tire.





### CASE SEDAN—V

COLOR . . . . .	Blue	LUBRICATION . . . . .	Force feed and splash
SEATING CAPACITY . . . . .	Seven	RADIATOR . . . . .	Tubular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	126 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Single unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	34 x 4½ inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	34 x 4½ inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry plate
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	29.4 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3½ x 5¼ inches	REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . . . .	Screw and nut


In addition to above specifications, price includes windshield, speedometer, ammeter, heater, motometer, tire pump, electric horn, demountable rims and one extra rim, without tire.



# ELGIN MOTOR CAR CORPORATION

ARGO, ILLINOIS

Price . . . . .	\$1485
Four-Passenger Scout . . . . .	1585
Five-Passenger Sedan . . . . .	2450



## ELGIN SIX TOURING—SERIES K


COLOR . . . . .	Body, dark blue; running gear, natural wood	BORE AND STROKE . . . . .	3½ x 4¼ inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Force feed and splash
POSITION OF DRIVER. . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	118 inches	COOLING . . . . .	Thermo-syphon
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	33 x 4 inches	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	33 x 4 inches, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear hub drum	VOLTAGES . . . . .	Six to eight
EMERGENCY BRAKE . . . . .	Expanding on rear hub drum	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Plate
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	23.44 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, electric horn, demountable rims, tire carrier and license support.

# THE ALLEN MOTOR COMPANY

COLUMBUS, OHIO

Price . . . . .	\$1395
Roadster . . . . .	1445
Sedan . . . . .	2145




## ALLEN TOURING—43

COLOR . . . . .	Body, dark blue; running gear, black; wheels, cream	BORE AND STROKE . . . . .	3 1/2 x 5 inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Force feed and splash
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	110 inches	COOLING . . . . .	Thermo-syphon
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	32 x 4 inches, anti-skid	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4 inches, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Four	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Plate
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	19.6 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, motometer, tire pump, electric horn and demountable rims.

**LIBERTY  
MOTORCAR  
COMPANY**  
**DETROIT  
MICHIGAN**

Price . . . . .	\$1695
Two-Passenger Roadster . . . . .	1695
Four-Passenger Speedster . . . . .	1785
Five-Passenger Sedan . . . . .	2595
Four-Passenger Coupe . . . . .	2495
Brougham . . . . .	3225
Landaulet . . . . .	3325




---

**LIBERTY SIX TOURING—10-C**

---

COLOR . . . . .	Liberty blue	LUBRICATION . . . . .	Force feed and splash
SEATING CAPACITY . . . . .	Five	RADIATOR . . . . .	Cellular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Thermo-syphon
WHEELBASE . . . . .	117 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	32 x 4 inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	32 x 4 inches, anti-skid	VOLTAGES . . . . .	Six to eight
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Contracting on transmission	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	23.4 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3½ x 5 inches	REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, clock, tire pump, electric horn and demountable rims.


---

**LIBERTY  
MOTORCAR  
COMPANY**  

---

**DETROIT  
MICHIGAN**

Price . . . . .	\$2595
Five-Passenger Touring . . . . .	1695
Two-Passenger Roadster . . . . .	1695
Four-Passenger Speedster . . . . .	1785
Four-Passenger Coupe . . . . .	2495
Brougham . . . . .	3225
Landaulet . . . . .	3325




---

**LIBERTY SIX SEDAN—10-C**


---

COLOR . . . . .	Gray	LUBRICATION . . . . .	Force feed and splash
SEATING CAPACITY . . . . .	Five	RADIATOR . . . . .	Cellular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Thermo-syphon
WHEELBASE . . . . .	117 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	32 x 4 inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	32 x 4 inches, anti-skid	VOLTAGES . . . . .	Six to eight
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Contracting on transmission	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	23.4 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3 $\frac{1}{8}$ x 5 inches	REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes speedometer, ammeter, voltmeter, clock, tire pump, electric horn and demountable rims.

**THE TEMPLAR  
MOTORS  
CORPORATION**  
CLEVELAND, OHIO

Price . . . . .	\$2685
Two-Passenger Touring Roadster	2685
Four-Passenger Sportette . . . .	2685
Three-Passenger Coupe . . . . .	3585
Five-Passenger Sedan . . . . .	3585



### TEMPLAR TOURING


COLOR . . . . .	Body, gray, wine or bronze; running gear, fenders and splasher, black	BORE AND STROKE . . . . .	3 3/4 x 5 1/2 inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Full force feed
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	118 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	High tension magneto
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	32 x 4 inches, ribbed cord	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4 inches, cord, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Expanding on rear wheel drums	VOLTAGES . . . . .	Six to eight
EMERGENCY BRAKE . . . . .	Expanding on rear wheel drums	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Four	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Plate
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	18.23	GEAR CHANGES . . . . .	Three forward, one reverse
	(N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and nut

In addition to above specifications, price includes top, top hood, windshield and cleaner, speedometer, ammeter, spotlight, motometer, clock, tire pump, electric horn and demountable rims.

# THE TEMPLAR MOTORS CORPORATION

CLEVELAND, OHIO

Price . . . . .	\$3585
Two-Passenger Touring Roadster . . . . .	2685
Four-Passenger Sportette . . . . .	2685
Five-Passenger Touring . . . . .	2685
Three-Passenger Coupe . . . . .	3585



## TEMPLAR SEDAN


COLOR . . . . .	Body, Brewster green or coach blue; running gear, black	BORE AND STROKE . . . . .	3½ x 5½ inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Full force feed
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	118 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	High tension magneto
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	32 x 4 inches, ribbed cord	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4 inches, cord, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Expanding on rear wheel drums	VOLTAGES . . . . .	Six to eight
EMERGENCY BRAKE . . . . .	Expanding on rear wheel drums	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Four	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Plate
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	18.23 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and nut

In addition to above specifications, price includes windshield and cleaner, speedometer, ammeter, spotlight, motometer, clock, tire pump, electric horn and demountable rims.

**PIERCE-ARROW  
MOTOR CAR  
COMPANY**

**B U F F A L O  
N E W Y O R K**

Price . . . . .	\$7750
Three-Passenger Runabout . . . . .	7650
Four-Passenger Touring . . . . .	7650
Four-Passenger Roadster . . . . .	7650
Five-Passenger Touring . . . . .	7650
Seven-Passenger Touring . . . . .	7750
Three-Passenger Coupe . . . . .	8750
Brougham—Flat Roof . . . . .	9050
French Brougham . . . . .	9050
Suburban . . . . .	9250
French Suburban . . . . .	9250
Vestibule Suburban—Flat Roof . . . . .	9450
Suburban Landau . . . . .	9250



**PIERCE-ARROW TOURING—48**

COLOR . . . . .	Optional	LUBRICATION . . . . .	Force feed
SEATING CAPACITY . . . . .	Six	RADIATOR . . . . .	Cellular
POSITION OF DRIVER . . . . .	Right side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	142 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	35 x 5 inches, cord	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	35 x 5 inches, cord, anti-skid	VOLTAGES . . . . .	Six-eight
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Pressure
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Cone
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	In pairs	GEAR CHANGES . . . . .	Four forward, one reverse
HORSEPOWER . . . . .	48.6 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	4½ x 5½ inches	REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Screw and nut


In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, clock, tire pump, electric horn and demountable rims.



# PIERCE-ARROW MOTOR CAR COMPANY

BUFFALO  
NEW YORK

Price	\$8550
Three-Passenger Runabout	7250
Four-Passenger Roadster	7250
Four-Passenger Touring	7250
Five-Passenger Touring	7250
Seven-Passenger Touring	7250
Three-Passenger Coupe	8250
Brougham—Flat Roof	8550
French Brougham	8550
Brougham Landaulet	8550
Town Brougham	8550
Vestibule Brougham	8750
Four-Passenger Sedan	8550
Seven-Passenger Sedan	8750




## PIERCE-ARROW BROUGHAM—38

COLOR . . . . .	Optional	BORE AND STROKE . . . . .	4 x 5½ inches
SEATING CAPACITY . . . . .	Seven	LUBRICATION . . . . .	Force feed
POSITION OF DRIVER . . . . .	Right side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	134 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	34 x 4½ inches, cord	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	34 x 4½ inches, cord, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGES . . . . .	Six-eight
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Pressure
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Cone
CAST . . . . .	In pairs	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	38.4 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Four forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Screw and nut

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, clock, tire pump, electric horn and demountable rims.

**McFARLAN  
MOTOR  
COMPANY**  
**CONNERSVILLE  
INDIANA**

<b>Price . . . . .</b>	<b>\$5000</b>
<b>Two-Passenger Roadster . . . .</b>	<b>4800</b>
<b>Four-Passenger Roadster . . . .</b>	<b>4800</b>
<b>Six-Passenger Touring . . . . .</b>	<b>4800</b>
<b>Seven-Passenger Touring . . . .</b>	<b>4800</b>




---

**McFARLAN SIX TOURING—TYPE 125**

---


<b>COLOR . . . . .</b>	<b>Optional</b>	<b>LUBRICATION . . . .</b>	<b>Force feed and splash</b>
<b>SEATING CAPACITY .</b>	<b>Four</b>	<b>RADIATOR . . . . .</b>	<b>Cellular</b>
<b>POSITION OF DRIVER</b>	<b>Left side</b>	<b>COOLING . . . . .</b>	<b>Water pump</b>
<b>WHEELBASE . . . .</b>	<b>136 inches</b>	<b>IGNITION . . . . .</b>	<b>High tension magneto and storage battery</b>
<b>GAUGE . . . . .</b>	<b>56 inches</b>	<b>STARTING SYSTEM . .</b>	<b>Two unit</b>
<b>WHEELS . . . . .</b>	<b>Wire or disteel</b>	<b>STARTER OPERATED</b>	<b>Gear to fly wheel</b>
<b>FRONT TIRES . . . .</b>	<b>33 x 5 inches, cord</b>	<b>LIGHTING SYSTEM . .</b>	<b>Electric</b>
<b>REAR TIRES . . . .</b>	<b>33 x 5 inches, cord</b>	<b>VOLTAGE . . . . .</b>	<b>Six</b>
<b>SERVICE BRAKE . .</b>	<b>Contracting on rear wheels</b>	<b>WIRING SYSTEM . . .</b>	<b>Single</b>
<b>EMERGENCY BRAKE .</b>	<b>Expanding on rear wheels</b>	<b>GASOLINE SYSTEM . .</b>	<b>Vacuum</b>
<b>CYLINDERS . . . . .</b>	<b>Six</b>	<b>CLUTCH . . . . .</b>	<b>Dry multiple disc</b>
<b>HOW ARRANGED . .</b>	<b>Vertically</b>	<b>TRANSMISSION . . .</b>	<b>Selective sliding</b>
<b>CAST . . . . .</b>	<b>En bloc</b>	<b>GEAR CHANGES . . .</b>	<b>Three forward, one reverse</b>
<b>HORSEPOWER . . . .</b>	<b>48.6</b>	<b>DRIVE . . . . .</b>	<b>Spiral bevel</b>
<b>(N.A.C.C. Rating)</b>		<b>REAR AXLE . . . . .</b>	<b>Full floating</b>
<b>BORE AND STROKE .</b>	<b>4½ x 6 inches</b>	<b>STEERING GEAR . . .</b>	<b>Worm and gear</b>

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, clock, tire pump, electric horn and demountable rims.

---

**McFARLAN  
MOTOR  
COMPANY**  
CONNERSVILLE  
INDIANA

Price . . . . .	\$5950
Town Car . . . . .	5900
Knickerbocker Cabriolet . . . . .	6500
Philadelphia Brougham . . . . .	6200
Touring Sedan . . . . .	5900
Sport Sedan . . . . .	6100




---

**McFARLAN SIX LIMOUSINE—TYPE 138**

---


COLOR . . . . .	Optional	LUBRICATION . . . . .	Force feed and splash
SEATING CAPACITY . . . . .	Seven	RADIATOR . . . . .	Cellular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	136 inches	IGNITION . . . . .	High tension magneto and storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	35 x 5 inches, cord	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	35 x 5 inches, cord	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	48.6 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	4½ x 6 inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and sector

In addition to above specifications, price includes windshield, speedometer, ammeter, voltmeter, clock, tire, pump electric horn and demountable rims.

---

**CLEVELAND  
AUTOMOBILE  
COMPANY**  
CLEVELAND, OHIO

**Price . . . . \$1385**  
**Roadster . . . 1385**  
**Sedan . . . . 2195**  
**Coupe . . . . 2195**




---

**CLEVELAND TOURING—40**

---


<b>COLOR . . . . .</b>	Body, Cleveland blue; running gear, black	<b>BORE AND STROKE .</b>	3 x 4½ inches
<b>SEATING CAPACITY .</b>	Five	<b>LUBRICATION . . . .</b>	Force feed and splash
<b>POSITION OF DRIVER.</b>	Left side	<b>RADIATOR . . . . .</b>	Cellular
<b>WHEELBASE . . . . .</b>	112 inches	<b>COOLING . . . . .</b>	Water pump
<b>GAUGE . . . . .</b>	56 inches	<b>IGNITION . . . . .</b>	Battery
<b>WHEELS . . . . .</b>	Wood	<b>STARTING SYSTEM .</b>	Two unit
<b>FRONT TIRES . . . .</b>	32 x 4 inches	<b>STARTER OPERATED .</b>	Gear to fly wheel
<b>REAR TIRES . . . . .</b>	32 x 4 inches, anti-skid	<b>LIGHTING SYSTEM .</b>	Electric
<b>SERVICE BRAKE . . .</b>	Contracting on rear axle	<b>VOLTAGE . . . . .</b>	Six
<b>EMERGENCY BRAKE .</b>	Contracting on transmission brake	<b>WIRING SYSTEM . .</b>	Single
<b>CYLINDERS . . . . .</b>	Six	<b>GASOLINE SYSTEM .</b>	Vacuum
<b>HOW ARRANGED . . .</b>	Vertically	<b>CLUTCH . . . . .</b>	Dry disc
<b>CAST . . . . .</b>	En bloc	<b>TRANSMISSION . . .</b>	Selective sliding
<b>HORSEPOWER . . . .</b>	21.6 (N.A.C.C. Rating)	<b>GEAR CHANGES . .</b>	Three forward, one reverse
		<b>DRIVE . . . . .</b>	Spiral bevel
		<b>REAR AXLE . . . . .</b>	Semi-floating
		<b>STEERING GEAR . . .</b>	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, electric horn and demountable rims.

# CLEVELAND AUTOMOBILE COMPANY

CLEVELAND, OHIO

Price . . . . .	\$2195
Coupe . . . . .	2195
Roadster . . . . .	1385
Touring . . . . .	1385




## CLEVELAND SEDAN—40

COLOR . . . . .	Body, Cleveland blue; running gear, black	BORE AND STROKE . . . . .	3 x 4½ inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Force feed and splash
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	112 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	32 x 4 inches	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4 inches, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear axle	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Contracting on transmission brake	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry disc
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	21.6 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes windshield, speedometer, ammeter, electric horn and demountable rims.

**J A M E S  
CUNNINGHAM  
SON & COMPANY**  
ROCHESTER  
NEW YORK

Price . . . . \$6200  
Roadster . . . 6200  
Sedan . . . . 7600




---

**CUNNINGHAM TOURING—37½-A—MODEL V**

---


COLOR . . . . .	Optional	BORE AND STROKE . .	3¾ x 5 inches
SEATING CAPACITY .	Four	LUBRICATION . . . .	Full force feed
POSITION OF DRIVER.	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . .	132 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wire or wood	STARTING SYSTEM .	Two unit
FRONT TIRES . . . .	35 x 5 inches	STARTER OPERATED .	Gear to transmission
REAR TIRES . . . .	35 x 5 inches, anti-skid	LIGHTING SYSTEM .	Electric
SERVICE BRAKE . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE .	Expanding on rear wheels	WIRING SYSTEM . .	Single
CYLINDERS . . . . .	Eight	GASOLINE SYSTEM .	Vacuum
HOW ARRANGED . .	V type, 90 degrees	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	Four en bloc	TRANSMISSION . . .	Selective sliding
HORSEPOWER . . . .	45 (N.A.C.C. Rating)	GEAR CHANGES . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . .	Full floating
		STEERING GEAR . .	Worm and sector

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, clock, tire pump, electric horn and demountable rims.

---

**J A M E S  
CUNNINGHAM  
SON & COMPANY**  
**ROCHESTER  
NEW YORK**

Price . . . . .	\$6700
Inside Drive Limousine . . . . .	8100
Town Limousine . . . . .	8100
Landaulet . . . . .	8100




---

**CUNNINGHAM TOURING—59A—MODEL V**

---


COLOR . . . . .	Optional	LUBRICATION . . . . .	Full force feed
SEATING CAPACITY . . . . .	Six	RADIATOR . . . . .	Cellular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	142 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wire or wood	STARTER OPERATED . . . . .	Gear to transmission
FRONT TIRES . . . . .	35 x 5 inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	35 x 5 inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Eight	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . . . . .	V type, 90 degrees	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	Four en bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	45 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3¾ x 5 inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and sector

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, clock, tire pump, electric horn and demountable rims.

---

**THE WINTON  
COMPANY**  
CLEVELAND, OHIO

Price	\$3950
Four-Passenger Sport Touring	3950
Five-Passenger Touring	3950
Six-Passenger Touring	3950
Two-Passenger Roadster	3950
Three-Passenger Roadster	3950
Four-Passenger Victoria	4850
Four-Passenger Sport Sedan	5050
Seven-Passenger Four-Door Sedan	5150
Seven-Passenger French Limousine Town Car	4900
Seven-Passenger Three-Quarter Limousine	4900
Seven-Passenger Four-Door Limousine	5150
Seven-Passenger Limousine Landaulet	5150



**WINTON SIX TOURING—25**

COLOR . . . . .	Optional	LUBRICATION . . . .	Force feed
SEATING CAPACITY .	Seven	RADIATOR . . . . .	Cellular
POSITION OF DRIVER	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . .	132 inches	IGNITION . . . . .	High tension magneto
GAUGE . . . . .	56 inches	STARTING SYSTEM . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED	Gear to fly wheel
FRONT TIRES . . . .	35 x 5 inches	LIGHTING SYSTEM . .	Electric
REAR TIRES . . . .	35 x 5 inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . .	Contracting on rear wheels	WIRING SYSTEM . . .	Single
EMERGENCY BRAKE .	Expanding on rear wheels	GASOLINE SYSTEM . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . .	Vertically	TRANSMISSION . . . .	Selective sliding
CAST . . . . .	In pairs	GEAR CHANGES . . .	Four forward, one reverse
HORSEPOWER . . . .	33.75 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE .	3 $\frac{3}{4}$ x 5 $\frac{1}{4}$ inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . .	Worm and gear


In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, clock, tire pump, electric horn and demountable rims.



# THE WINTON COMPANY

CLEVELAND, OHIO

Price . . . . .	\$4350
Four-Passenger Sport Touring . . . . .	4350
Five-Passenger Touring . . . . .	4350
Six-Passenger Touring . . . . .	4350
Two-Passenger Roadster . . . . .	4350
Three-Passenger Roadster . . . . .	4350
Seven-Passenger Four-Door Sedan . . . . .	5600
Seven-Passenger French Limousine Town Car . . . . .	5350
Seven-Passenger Three-Quarter Limousine . . . . .	5350
Seven-Passenger Four-Door Limousine . . . . .	5600




## WINTON SIX TOURING—24

COLOR . . . . .	Optional	LUBRICATION . . . . .	Force feed
SEATING CAPACITY . . . . .	Seven	RADIATOR . . . . .	Cellular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	138 inches	IGNITION . . . . .	High tension magneto
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	35 x 5 inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	35 x 5 inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	In pairs	GEAR CHANGES . . . . .	Four forward, one reverse
HORSEPOWER . . . . .	48.6 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	4 1/2 x 5 1/4 inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, clock, tire pump, electric horn and demountable rims.

**PEERLESS  
MOTOR CAR  
COMPANY**  
CLEVELAND, OHIO

Price . . . . .	\$2900
Roadster . . . . .	2900
Coupe . . . . .	3500
Sedan . . . . .	3700
Sedan Limousine . . . .	3900




---

**PEERLESS TOURING**

---


COLOR . . . . .	Body, Peerless green; running gear, black	BORE AND STROKE . . .	3¼ x 5 inches
SEATING CAPACITY . .	Seven	LUBRICATION . . . . .	Full force feed
POSITION OF DRIVER .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	125 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . .	Two unit
FRONT TIRES . . . . .	34 x 4½ inches	STARTER OPERATED . .	Gear to fly wheel
REAR TIRES . . . . .	34 x 4½ inches, anti-skid	LIGHTING SYSTEM . . .	Electric
SERVICE BRAKE . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . .	Expanding on rear wheels	WIRING SYSTEM . . . .	Single
CYLINDERS . . . . .	Eight	GASOLINE SYSTEM . . .	Vacuum
HOW ARRANGED . . . .	V type, 90 degrees	CLUTCH . . . . .	Dry disc
CAST . . . . .	Four en bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	33.8 (N.A.C.C. Rating)	GEAR CHANGES . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . . . .	Worm and sector

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, oil pressure gauge, tire pump, electric horn and demountable rims.

# PEERLESS MOTOR CAR COMPANY

CLEVELAND, OHIO

Price . . . . .	\$2900
Touring . . . . .	2900
Coupe . . . . .	3500
Sedan . . . . .	3700
Sedan Limousine . . . . .	3900



## PEERLESS ROADSTER

COLOR . . . . .	Body, Peerless green; running gear, black	BORE AND STROKE . . . . .	3 1/4 x 5 inches
SEATING CAPACITY . . . . .	Four	LUBRICATION . . . . .	Full force feed
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	125 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	34 x 4 1/2 inches	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	34 x 4 1/2 inches, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Eight	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	V type, 90 degrees	CLUTCH . . . . .	Dry disc
CAST . . . . .	Four en bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	33.8 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . . . .	Worm and sector


In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, oil pressure gauge, tire pump, electric horn and demountable rims.

**PEERLESS  
MOTOR CAR  
COMPANY**  

---

**CLEVELAND, OHIO**

<b>Price</b> . . . . .	<b>\$3700</b>
<b>Touring</b> . . . . .	<b>2900</b>
<b>Roadster</b> . . . . .	<b>2900</b>
<b>Coupe</b> . . . . .	<b>3500</b>
<b>Sedan Limousine</b> . . . .	<b>3900</b>




---

**PEERLESS SEDAN**


---

<b>COLOR</b> . . . . .	Black above belt, Peerless green be- low belt; running gear, black	<b>BORE AND STROKE</b> . .	3¼ x 5 inches
<b>SEATING CAPACITY</b> .	Seven	<b>LUBRICATION</b> . . . .	Full force feed
<b>POSITION OF DRIVER</b>	Left side	<b>RADIATOR</b> . . . . .	Cellular
<b>WHEELBASE</b> . . . .	125 inches	<b>COOLING</b> . . . . .	Water pump
<b>GAUGE</b> . . . . .	56 inches	<b>IGNITION</b> . . . . .	Storage battery
<b>WHEELS</b> . . . . .	Wood	<b>STARTING SYSTEM</b> . .	Two unit
<b>FRONT TIRES</b> . . . .	34 x 4½ inches	<b>STARTER OPERATED</b> .	Gear to fly wheel
<b>REAR TIRES</b> . . . .	34 x 4½ inches, anti-skid	<b>LIGHTING SYSTEM</b> . .	Electric
<b>SERVICE BRAKE</b> . . .	Contracting on rear wheels	<b>VOLTAGE</b> . . . . .	Six
<b>EMERGENCY BRAKE</b> .	Expanding on rear wheels	<b>WIRING SYSTEM</b> . . .	Single
<b>CYLINDERS</b> . . . . .	Eight	<b>GASOLINE SYSTEM</b> . .	Vacuum
<b>HOW ARRANGED</b> . . .	V type, 90 degrees	<b>CLUTCH</b> . . . . .	Dry disc
<b>CAST</b> . . . . .	Four en bloc	<b>TRANSMISSION</b> . . .	Selective sliding
<b>HORSEPOWER</b> . . . .	33.8 (N.A.C.C. Rating)	<b>GEAR CHANGES</b> . . .	Three forward, one reverse
		<b>DRIVE</b> . . . . .	Spiral bevel
		<b>REAR AXLE</b> . . . . .	Three-quarters floating
		<b>STEERING GEAR</b> . . .	Worm and sector

In addition to above specifications, price includes windshield, speedometer, ammeter, oil pressure gauge, tire pump, electric horn and demountable rims.

**PEERLESS  
MOTOR CAR  
COMPANY**  
CLEVELAND, OHIO

<b>Price</b> . . . . .	<b>\$3900</b>
<b>Touring</b> . . . . .	<b>2900</b>
<b>Roadster</b> . . . . .	<b>2900</b>
<b>Coupe</b> . . . . .	<b>3500</b>
<b>Sedan</b> . . . . .	<b>3700</b>




---

**PEERLESS SEDAN—LIMOUSINE**

---


<b>COLOR</b> . . . . .	Body, black above belt, Peerless green below belt; running gear, black	<b>BORE AND STROKE</b> . . .	3¼ x 5 inches
<b>SEATING CAPACITY</b> . .	Seven	<b>LUBRICATION</b> . . . . .	Full force feed
<b>POSITION OF DRIVER</b>	Left side	<b>RADIATOR</b> . . . . .	Cellular
<b>WHEELBASE</b> . . . . .	125 inches	<b>COOLING</b> . . . . .	Water pump
<b>GAUGE</b> . . . . .	56 inches	<b>IGNITION</b> . . . . .	Storage battery
<b>WHEELS</b> . . . . .	Wood	<b>STARTING SYSTEM</b> . . .	Two unit
<b>FRONT TIRES</b> . . . . .	34 x 4½ inches	<b>STARTER OPERATED</b> . .	Gear to fly wheel
<b>REAR TIRES</b> . . . . .	34 x 4½ inches, anti-skid	<b>LIGHTING SYSTEM</b> . . .	Electric
<b>SERVICE BRAKE</b> . . . .	Contracting on rear wheels	<b>VOLTAGE</b> . . . . .	Six
<b>EMERGENCY BRAKE</b> . .	Expanding on rear wheels	<b>WIRING SYSTEM</b> . . . .	Single
<b>CYLINDERS</b> . . . . .	Eight	<b>GASOLINE SYSTEM</b> . . .	Vacuum
<b>HOW ARRANGED</b> . . . .	V type, 90 degrees	<b>CLUTCH</b> . . . . .	Dry disc
<b>CAST</b> . . . . .	Four en bloc	<b>TRANSMISSION</b> . . . . .	Selective sliding
<b>HORSEPOWER</b> . . . . .	33.8 (N.A.C.C. Rating)	<b>GEAR CHANGES</b> . . . .	Three forward, one reverse
		<b>DRIVE</b> . . . . .	Spiral bevel
		<b>REAR AXLE</b> . . . . .	Three-quarters floating
		<b>STEERING GEAR</b> . . . . .	Worm and sector

In addition to above specifications, price includes windshield, speedometer, ammeter, oil pressure gauge, tire pump, electric horn and demountable rims.

**PEERLESS  
MOTOR CAR  
COMPANY**

**CLEVELAND, OHIO**

<b>Price . . . . .</b>	<b>\$3500</b>
<b>Touring . . . . .</b>	<b>2900</b>
<b>Roadster . . . . .</b>	<b>2900</b>
<b>Sedan . . . . .</b>	<b>3700</b>
<b>Sedan Limousine . . . . .</b>	<b>3900</b>



**PEERLESS COUPE**

<b>COLOR . . . . .</b>	Body, black above belt, Peerless green below; running gear, black	<b>BORE AND STROKE . . . . .</b>	3¼ x 5 inches
<b>SEATING CAPACITY</b>	Four	<b>LUBRICATION . . . . .</b>	Full force feed
<b>POSITION OF DRIVER</b>	Left side	<b>RADIATOR . . . . .</b>	Cellular
<b>WHEELBASE . . . . .</b>	125 inches	<b>COOLING . . . . .</b>	Water pump
<b>GAUGE . . . . .</b>	56 inches	<b>IGNITION . . . . .</b>	Storage battery
<b>WHEELS . . . . .</b>	Wood	<b>STARTING SYSTEM . . . . .</b>	Two unit
<b>FRONT TIRES . . . . .</b>	34 x 4½ inches	<b>STARTER OPERATED . . . . .</b>	Gear to fly wheel
<b>REAR TIRES . . . . .</b>	34 x 4½ inches, anti-skid	<b>LIGHTING SYSTEM . . . . .</b>	Electric
<b>SERVICE BRAKE . . . . .</b>	Contracting on rear wheels	<b>VOLTAGE . . . . .</b>	Six
<b>EMERGENCY BRAKE . . . . .</b>	Expanding on rear wheels	<b>WIRING SYSTEM . . . . .</b>	Single
<b>CYLINDERS . . . . .</b>	Eight	<b>GASOLINE SYSTEM . . . . .</b>	Vacuum
<b>HOW ARRANGED . . . . .</b>	V type, 90 degrees	<b>CLUTCH . . . . .</b>	Dry disc
<b>CAST . . . . .</b>	Four en bloc	<b>TRANSMISSION . . . . .</b>	Selective sliding
<b>HORSEPOWER . . . . .</b>	33.8 (N.A.C.C. Rating)	<b>GEAR CHANGES . . . . .</b>	Three forward, one reverse
		<b>DRIVE . . . . .</b>	Spiral bevel
		<b>REAR AXLE . . . . .</b>	Three-quarters floating
		<b>STEERING GEAR . . . . .</b>	Worm and sector

In addition to above specifications, price includes windshield, speedometer, ammeter, oil pressure gauge, tire pump, electric horn and demountable rims.

**CHALMERS  
MOTOR CAR  
COMPANY**  

---

**DETROIT  
MICHIGAN**

Price . . . . .	\$1685
Standard Roadster—Type 35-C . . . . .	1685
Five-Passenger Touring—Type 35-C . . . . .	1685
Three-Passenger Coupe—Type 35-C . . . . .	2105
Sedan—Type 35-C . . . . .	2370




---

**CHALMERS TOURING—TYPE 35-C**

---

COLOR . . . . .	Body, blue; running gear, black	BORE AND STROKE . . . . .	3¼ x 4½ inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Force feed and splash
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	117 inches	COOLING . . . . .	Thermo-syphon
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	32 x 4 inches	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4 inches, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear axle	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear axle	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	25.35 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear


In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.

**ANDERSON  
MOTOR  
COMPANY**  


---

**ROCK HILL,  
SOUTH CAROLINA**

Price . . . . .	\$1775
Five-Passenger Touring . . . .	1775
Seven-Passenger Touring . . . .	1850
Four-Passenger Sport Touring . .	1835
Five-Passenger Sedan . . . . .	2650
Coupe . . . . .	2550




---

**ANDERSON CONVERTIBLE ROADSTER—R**

---

COLOR . . . . .	Body, Pershing green running gear, black	BORE AND STROKE . . . . .	3¼ x 4½ inches
SEATING CAPACITY . . . . .	Two or five	LUBRICATION . . . . .	Force feed and splash
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	120 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Single unit
FRONT TIRES . . . . .	33 x 4 inches	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	33 x 4 inches, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	25.35 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and nut


In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, motometer, clock, tire pump, electric horn and demountable rims.

---



**BREWSTER &  
COMPANY,  
INCORPORATED**  
LONG ISLAND CITY  
NEW YORK

Price . . . . .	\$9400
Town Brougham . . . . .	9400
Town Landaulet . . . . .	9500
Round Corner Landaulet . . . . .	9500
Limousine . . . . .	9600
Enclosed Drive . . . . .	9400
Club Runabout . . . . .	7900




---

**BREWSTER COUNTRY BROUGHAM**

---

COLOR . . . . .	Optional	LUBRICATION . . . . .	Force feed
SEATING CAPACITY . . . . .	Six	RADIATOR . . . . .	Cellular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	125 inches	IGNITION . . . . .	High tension magneto
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Single unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Direct to fly wheel
FRONT TIRES . . . . .	34 x 4½ inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	34 x 4½ inches, anti-skid	VOLTAGE . . . . .	Twelve
SERVICE BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Four	CLUTCH . . . . .	Cone
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	25.6 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	4 x 5½ inches	REAR AXLE . . . . .	Live axle—full floating
		STEERING GEAR . . . . .	Worm and nut


In addition to above specifications, price includes windshield, speedometer, ammeter, voltmeter, clock, tire pump, electric horn and demountable rims.

---

**A U B U R N  
A U T O M O B I L E  
C O M P A N Y**  
A U B U R N  
I N D I A N A

Price . . . . .  
 Four-Passenger Tourster—6-39K  
 Two-Passenger Roadster—6-39R  
 Four-Passenger Coupe—6-39 . . .  
 Five-Passenger Sedan—6-39 . . .

Prices  
Upon  
Appli-  
cation



**AUBURN FIVE-PASSENGER TOURING—6-39 H**


COLOR . . . . .	Blue, gray or lake	LUBRICATION . . . . .	Force Feed and splash
SEATING CAPACITY . . . . .	Five	RADIATOR . . . . .	Cellular
POSITION OF DRIVER. . . . .	Left side	COOLING . . . . .	Centrifugal pump
WHEELBASE . . . . .	120 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	33 x 4 inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	33 x 4 inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	25.35 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3¼ x 4½ inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Screw and nut

In addition to above specifications, price includes top, windshield, speedometer, ammeter, tire pump, electric horn, demountable rims and rebound snubbers.

# AUBURN AUTOMOBILE COMPANY

AUBURN  
INDIANA

Price . . . . .		} Prices Upon Appli- cation
Five-Passenger Touring—6-39H		
Four-Passenger Tourster—6-39K		
Two-Passenger Roadster—6-39R		
Four-Passenger Coupe—6-39.		



## AUBURN FIVE-PASSENGER SEDAN—6-39


COLOR . . . . .	Blue, gray or lake	LUBRICATION . . . .	Force feed and splash
SEATING CAPACITY .	Five	RADIATOR . . . . .	Cellular
POSITION OF DRIVER.	Left side	COOLING . . . . .	Centrifugal pump
WHEELBASE . . . . .	120 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . . .	33 x 4 inches	LIGHTING SYSTEM .	Electric
REAR TIRES . . . . .	33 x 4 inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . .	Contracting on rear wheels	WIRING SYSTEM . .	Single
EMERGENCY BRAKE .	Expanding on rear wheels	GASOLINE SYSTEM .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry disc
HOW ARRANGED . . .	Vertically	TRANSMISSION . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . .	Three forward, one reverse
HORSEPOWER . . . .	25.35 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE .	3¼ x 4½ inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . .	Screw and nut

In addition to above specifications, price includes windshield, speedometer, ammeter, tire pump, electric horn, demountable rims and rebound snubbers.

# PILOT MOTOR CAR COMPANY

RICHMOND  
INDIANA

Price . . . . .	\$1650
Four-Passenger Roadster . . . . .	1700
Five-Passenger Sedan . . . . .	2500
Four-Passenger Coupe . . . . .	2450




## PILOT TOURING—6-45

COLOR . . . . .	Body, Brewster green; running gear, black	BORE AND STROKE . . . . .	3 3/8 x 5 inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Force feed and splash
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	120 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	32 x 4 inches, anti-skid	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4 inches, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Expanding on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	23.44 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, wind-shield, speedometer, ammeter, electric horn and demountable rims.

**H. H. FRANKLIN  
MANUFACTUR-  
ING COMPANY**  
SYRACUSE  
NEW YORK

Price . . . . .	\$2750
Runabout . . . . .	2700
Four-Passenger Roadster . . . . .	2750
Brougham . . . . .	3700
Sedan . . . . .	3750




---

**FRANKLIN TOURING—SERIES 9-B**

---

COLOR . . . . .	Body, Brewster green; running gear, axles and guards, black	BORE AND STROKE . . . . .	3¼ x 4 inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Force feed
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Air
WHEELBASE . . . . .	115 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Single unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Chain to crank shaft
FRONT TIRES . . . . .	32 x 4 inches, ribbed cord	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	32 x 4 inches, cord anti-skid	VOLTAGE . . . . .	Twelve
SERVICE BRAKE . . . . .	Contracting on transmission	WIRING SYSTEM . . . . .	Double
EMERGENCY BRAKE . . . . .	Contracting on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Single dry plate
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	Singly	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	25.35 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear


In addition to above specifications, price includes top, windshield, speedometer, current indicator, clock, tire pump, and electric horn.

---

**WILLIAM  
S M A L L  
C O M P A N Y**

**INDIANAPOLIS  
I N D I A N A**

**Price . . . . \$1295  
Roadster . . . 1295**




**MONROE TOURING—S-9**

<b>COLOR . . . . .</b>	Body, dark blue; running gear, black with ivory wheels	<b>BORE AND STROKE . .</b>	3¼ x 4½ inches
<b>SEATING CAPACITY .</b>	Five	<b>LUBRICATION . . . .</b>	Full force feed
<b>POSITION OF DRIVER</b>	Left side	<b>RADIATOR . . . . .</b>	Cellular
<b>WHEELBASE . . . .</b>	115 inches	<b>COOLING . . . . .</b>	Thermo-syphon
<b>GAUGE . . . . .</b>	56 inches	<b>IGNITION . . . . .</b>	Storage battery
<b>WHEELS . . . . .</b>	Wood	<b>STARTING SYSTEM . .</b>	Two unit
<b>FRONT TIRES . . . .</b>	32 x 3½ inches	<b>STARTER OPERATED</b>	Gear to fly wheel
<b>REAR TIRES . . . .</b>	32 x 3½ inches, anti-skid	<b>LIGHTING SYSTEM . .</b>	Electric
<b>SERVICE BRAKE . .</b>	Contracting on drums	<b>VOLTAGE . . . . .</b>	Six
<b>EMERGENCY BRAKE .</b>	Expanding on drums	<b>WIRING SYSTEM . .</b>	Single
<b>CYLINDERS . . . . .</b>	Four	<b>GASOLINE SYSTEM .</b>	Vacuum
<b>HOW ARRANGED . .</b>	Vertically	<b>CLUTCH . . . . .</b>	Dry plate multiple disc
<b>CAST . . . . .</b>	En bloc	<b>TRANSMISSION . . .</b>	Selective sliding
<b>HORSEPOWER . . . .</b>	16.9 (N.A.C.C. Rating)	<b>GEAR CHANGES . .</b>	Three forward, one reverse
		<b>DRIVE . . . . .</b>	Spiral bevel
		<b>REAR AXLE . . . .</b>	Semi-floating
		<b>STEERING GEAR . .</b>	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, tire pump, electric horn and demountable rims.

**STANDARD  
STEEL CAR  
COMPANY**  
**PITTSBURGH  
PENNSYLVANIA**

Price . . . . .	\$3000
Four-Passenger Touring . . . . .	3000
Three-Passenger Roadster . . . . .	3000
Seven-Passenger Sedan . . . . .	4300
Four-Passenger Coupe . . . . .	4200
Seven-Passenger Suburban Sedan . . . . .	5000




### STANDARD EIGHT TOURING—I

COLOR . . . . .	Body, blue or maroon; running gear, black	BORE AND STROKE . . . . .	3¼ x 5 inches
SEATING CAPACITY . . . . .	Seven	LUBRICATION . . . . .	Full force feed
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	127 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	High tension magneto and storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	34 x 4½ inches, cord	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	34 x 4½ inches, cord, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Eight	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	V type, 90 degrees	CLUTCH . . . . .	Dry plate
CAST . . . . .	Four en bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	33.8 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, clock, tire pump, electric horn and demountable rims.

**D O D G E  
B R O T H E R S  
D E T R O I T  
M I C H I G A N**

Price . . . . .	\$1085
Two-Passenger Roadster . . . . .	1085
Three-Passenger Coupe . . . . .	1750
Five-Passenger Sedan . . . . .	1900



### DODGE BROTHERS TOURING

COLOR . . . . .	Black	LUBRICATION . . . . .	Splash with circulating pump
SEATING CAPACITY . . . . .	Five	RADIATOR . . . . .	Tubular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Centrifugal pump
WHEELBASE . . . . .	114 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Single unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Chain to crank shaft
FRONT TIRES . . . . .	32 x 3½ inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	32 x 3½ inches, anti-skid	VOLTAGE . . . . .	Twelve
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Four	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	24.03 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3¼ x 4½ inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and worm wheel


In addition to above specifications, price includes top, top hood, wind-shield, speedometer, ammeter, tire pump, electric horn and demountable rims.



# GRANT MOTOR CAR CORPORATION

CLEVELAND, OHIO


Price . . . . .	} Prices Upon Appli- cation
Roadster . . . . .	
Sedan . . . . .	
Coupe . . . . .	



## GRANT SIX TOURING—H

COLOR . . . . .	Body, Grant blue; running gear, black	LUBRICATION . . . . .	Splash with circulating pump
SEATING CAPACITY . . . . .	Five	RADIATOR . . . . .	Tubular
POSITION OF DRIVER. . . . .	Left side	COOLING . . . . .	Thermo-syphon
WHEELBASE . . . . .	116 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	32 x 4 inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	32 x 4 inches, anti-skid	VOLTAGES . . . . .	Six to eight
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	22.5 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3 $\frac{1}{8}$ x 4 $\frac{1}{2}$ inches	REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . . . .	Screw and nut

In addition to above specifications, price includes top, top hood, wind-  
shield, speedometer, ammeter, tire pump, electric horn and demountable rims.




---

**BUICK ROADSTER—K-6-44**

---


COLOR . . . . .	Body, Buick blue; wheels, straw color	LUBRICATION . . . . .	Splash with circulating pump
SEATING CAPACITY .	Three	RADIATOR . . . . .	Cellular
POSITION OF DRIVER.	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	118 inches	IGNITION . . . . .	High tension generator and storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM .	Single unit
WHEELS . . . . .	Wood	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . . . .	33 x 4 inches	LIGHTING SYSTEM .	Electric
REAR TIRES . . . . .	33 x 4 inches, anti-skid	VOLTAGES . . . . .	Six to eight
SERVICE BRAKE . . .	Contracting on brake drum	WIRING SYSTEM . .	Single
EMERGENCY BRAKE .	Expanding inside brake drum	GASOLINE SYSTEM .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry plate multiple disc
HOW ARRANGED . . .	Vertically	TRANSMISSION . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . .	Three forward, one reverse
HORSEPOWER . . . .	27.34 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE .	3½ x 4½ inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . .	Screw and nut

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, tire pump, electric horn and demountable rim.

# BUICK MOTOR COMPANY

F L I N T  
M I C H I G A N


Price, \$1495



## BUICK TOURING—K-6-45

COLOR . . . . .	Body, dark green; wheels, straw color	LUBRICATION . . . .	Splash with circulating pump
SEATING CAPACITY .	Five	RADIATOR . . . . .	Cellular
POSITION OF DRIVER.	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . .	118 inches	IGNITION . . . . .	High tension generator and storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM .	Single unit
WHEELS . . . . .	Wood	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . . .	33 x 4 inches	LIGHTING SYSTEM .	Electric
REAR TIRES . . . .	33 x 4 inches, anti-skid	VOLTAGES . . . . .	Six to eight
SERVICE BRAKE . .	Contracting on brake drum	WIRING SYSTEM . .	Single
EMERGENCY BRAKE .	Expanding inside brake drum	GASOLINE SYSTEM .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry plate multiple disc
HOW ARRANGED . .	Vertically	TRANSMISSION . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . .	Three forward, one reverse
HORSEPOWER . . . .	27.34 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE .	3½ x 4¼ inches	REAR AXLE . . . .	Full floating
		STEERING GEAR . .	Screw and nut

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.





---

**BUICK COUPE—K-6-46**

---

COLOR . . . . .	Body, black; wheels, dark blue	LUBRICATION . . . .	Splash with circulating pump
SEATING CAPACITY .	Four	RADIATOR . . . . .	Cellular
POSITION OF DRIVER.	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . .	118 inches	IGNITION . . . . .	High tension generator and storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM .	Single unit
WHEELS . . . . .	Wood	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . . .	33 x 4 inches	LIGHTING SYSTEM .	Electric
REAR TIRES . . . .	33 x 4 inches, anti-skid	VOLTAGES . . . . .	Six to eight
SERVICE BRAKE . .	Contracting on brake drum	WIRING SYSTEM . .	Single
EMERGENCY BRAKE .	Expanding inside brake drum	GASOLINE SYSTEM .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry plate multiple disc
HOW ARRANGED . .	Vertically	TRANSMISSION . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . .	Three forward, one reverse
HORSEPOWER . . . .	27.34 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE .	3 $\frac{3}{4}$ x 4 $\frac{1}{2}$ inches	REAR AXLE . . . .	Full floating
		STEERING GEAR . .	Screw and nut


In addition to above specifications, price includes windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.



**BUICK SEDAN—K-6-47**

COLOR . . . . .	Body, black; wheels, dark blue	LUBRICATION . . . .	Splash with circulating pump
SEATING CAPACITY .	Five	RADIATOR . . . . .	Cellular
POSITION OF DRIVER.	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	118 inches	IGNITION . . . . .	High tension generator and storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM .	Single unit
WHEELS . . . . .	Wood	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . . .	34 x 4½ inches	LIGHTING SYSTEM .	Electric
REAR TIRES . . . .	34 x 4½ inches, anti-skid	VOLTAGES . . . . .	Six to eight
SERVICE BRAKE . .	Contracting on brake drum	WIRING SYSTEM . .	Single
EMERGENCY BRAKE .	Expanding inside brake drum	GASOLINE SYSTEM .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry plate multiple disc
HOW ARRANGED . .	Vertically	TRANSMISSION . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . .	Three forward, one reverse
HORSEPOWER . . . .	27.34 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE .	3¾ x 4½ inches	REAR AXLE . . . .	Full floating
		STEERING GEAR . .	Screw and nut

In addition to above specifications, price includes windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.





---

**BUICK TOURING—K-6-49**

---

COLOR . . . . .	Body and wheels, Buick deep blue	LUBRICATION . . . .	Splash with circulating pump
SEATING CAPACITY .	Seven	RADIATOR . . . . .	Cellular
POSITION OF DRIVER.	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	124 inches	IGNITION . . . . .	High tension generator and storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM .	Single unit
WHEELS . . . . .	Wood	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . . .	34 x 4½ inches	LIGHTING SYSTEM .	Electric
REAR TIRES . . . .	34 x 4½ inches, anti-skid	VOLTAGES . . . . .	Six to eight
SERVICE BRAKE . .	Contracting on brake drum	WIRING SYSTEM . .	Single
EMERGENCY BRAKE .	Expanding inside brake drum	GASOLINE SYSTEM .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry plate multiple disc
HOW ARRANGED . .	Vertically	TRANSMISSION . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . .	Three forward, one reverse
HORSEPOWER . . . .	27.34 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE .	3½ x 4½ inches	REAR AXLE . . . .	Full floating
		STEERING GEAR . .	Screw and nut

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, clock, tire pump, electric horn and demountable rims.




---

**BUICK SEDAN—K-6-50**

---

COLOR . . . . .	Body, dark blue and black; wheels, dark blue	LUBRICATION . . . .	Splash with circulating pump
SEATING CAPACITY .	Seven	RADIATOR . . . . .	Cellular
POSITION OF DRIVER.	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . .	124 inches	IGNITION . . . . .	High tension generator and storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM .	Single unit
WHEELS . . . . .	Wood	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . . .	34 x 4½ inches	LIGHTING SYSTEM .	Electric
REAR TIRES . . . .	34 x 4½ inches, anti-skid	VOLTAGE . . . . .	Six to eight
SERVICE BRAKE . .	Contracting on brake drum	WIRING SYSTEM . .	Single
EMERGENCY BRAKE .	Expanding inside brake drum	GASOLINE SYSTEM .	Vacuum
CYLINDERS . . . .	Six	CLUTCH . . . . .	Dry plate multiple disc
HOW ARRANGED . .	Vertically	TRANSMISSION . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . .	Three forward, one reverse
HORSEPOWER . . . .	27.34 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE .	3½ x 4½ inches	REAR AXLE . . . .	Full floating
		STEERING GEAR . .	Screw and nut


In addition to above specifications, price includes windshield, speedometer, ammeter, clock, tire pump, electric horn and demountable rims.

---

# VELIE MOTORS CORPORATION

M O L I N E  
I L L I N O I S

Price Upon Application



## VELIE TOURING—34


COLOR . . . . .	Blue	LUBRICATION . . . . .	Force feed and splash
SEATING CAPACITY . . . . .	Five	RADIATOR . . . . .	Cellular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Thermo-syphon
WHEELBASE . . . . .	112 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	32 x 3 1/4 inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	32 x 3 1/4 inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	23.44 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3 1/8 x 4 1/4 inches	REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, electric horn, and demountable rims.



**VELIE MOTORS  
CORPORATION**  
**MOLINE, ILLINOIS**

Price . . . . .	\$1785
Two-Passenger Roadster . . . . .	1785
Four-Passenger Speedster . . . . .	1950
Four-Passenger Coupe . . . . .	2485
Six-Passenger Sedan . . . . .	2485





---

**VELIE TOURING—48**

---

COLOR . . . . .	Blue or maroon	LUBRICATION . . . . .	Force feed and splash
SEATING CAPACITY . . . . .	Five	RADIATOR . . . . .	Cellular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	115 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	32 x 4 inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	32 x 4 inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	25.35 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3¼ x 4½ inches	REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, motometer, voltmeter, electric horn and demountable rims.





---

### OVERLAND FOUR TOURING

---

COLOR . . . . .	Black	LUBRICATION . . . .	Splash
SEATING CAPACITY .	Five	RADIATOR . . . . .	Cellular
POSITION OF DRIVER	Left side	COOLING . . . . .	Thermo-syphon
WHEELBASE . . . .	100 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . . .	30 x 3½ inches	LIGHTING SYSTEM . .	Electric
REAR TIRES . . . .	30 x 3½ inches, non-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . .	Contracting on rear wheels	WIRING SYSTEM . .	Single
EMERGENCY BRAKE .	Expanding on rear wheels	GASOLINE SYSTEM .	Gravity
CYLINDERS . . . .	Four	CLUTCH . . . . .	Plate in oil
HOW ARRANGED . .	Vertically	TRANSMISSION . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . .	Three forward, one reverse
HORSEPOWER . . . .	18.23 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE .	3½ x 4 inches	REAR AXLE . . . .	Three-quarters floating
		STEERING GEAR . .	Planetary

In addition to above specifications, price includes top, top hood, wind-shield, speedometer, ammeter, electric horn and five demountable rims.




---


**OVERLAND FOUR SEDAN**

---

COLOR . . . . .	Body, blue; top, hood and running gear, black	BORE AND STROKE . . . . .	3½ x 4 inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Splash
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	100 inches	COOLING . . . . .	Thermo-syphon
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wire	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	31 x 4 inches	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	31 x 4 inches, non-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Four	GASOLINE SYSTEM . . . . .	Gravity
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Plate in oil
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	18.23	GEAR CHANGES . . . . .	Three forward, one reverse
	(N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . . . .	Planetary

In addition to above specifications, price includes windshield, speedometer, ammeter, tire pump, electric horn and spare wheel.

---





---

### WILLYS-KNIGHT TOURING

---

COLOR . . . . .	Body and wheels, blue; running gear and hood, black	BORE AND STROKE . . .	3½ x 4½ inches
SEATING CAPACITY . .	Five	LUBRICATION . . . . .	Force feed
POSITION OF DRIVER .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	118 inches	COOLING . . . . .	Thermo-syphon
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . .	Two unit
FRONT TIRES . . . . .	33 x 4 inches, ribbed cord	STARTER OPERATED . .	Gear to fly wheel
REAR TIRES . . . . .	33 x 4 inches, cord, non-skid	LIGHTING SYSTEM . . .	Electric
SERVICE BRAKE . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . .	Expanding on rear wheels	WIRING SYSTEM . . . .	Single
CYLINDERS . . . . .	Four	GASOLINE SYSTEM . . .	Pressure
HOW ARRANGED . . . .	Vertically	CLUTCH . . . . .	Single dry plate
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	21.03 (N.A.C.C. Rating)	GEAR CHANGES . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, clock, tire pump, electric horn and five demountable rims.



### **WILLYS-KNIGHT SEDAN**


COLOR . . . . .	Body, blue; top, running gear and hood black	BORE AND STROKE . . . . .	3 3/4 x 4 1/2 inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Force feed
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	118 inches	COOLING . . . . .	Thermo-syphon
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	34 x 4 1/2 inches ribbed cord	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	34 x 4 1/2 inches, cord, non-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Four	GASOLINE SYSTEM . . . . .	Pressure
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Single dry plate
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	21.03 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes windshield, speedometer, ammeter, clock, tire pump, electric horn and five demountable rims.

# CHEVROLET MOTOR COMPANY

BROADWAY  
AT 57th STREET  
NEW YORK CITY

Price . . . . .	\$735
"Four-Ninety" Roadster . . . . .	715
"Four-Ninety" Coupe . . . . .	1110
"Four-Ninety" Sedan . . . . .	1185
"Four-Ninety" Light Delivery Wagon . . . . .	735
"Four-Ninety" Station Wagon . . . . .	770



## CHEVROLET "FOUR-NINETY" TOURING


COLOR . . . . .	Black	RADIATOR . . . . .	Cellular
SEATING CAPACITY . . . . .	Five	COOLING . . . . .	Water pump
POSITION OF DRIVER . . . . .	Left side	IGNITION . . . . .	High tension magneto and storage battery
WHEELBASE . . . . .	102 inches	STARTING SYSTEM . . . . .	Two unit
GAUGE . . . . .	56 inches	STARTER OPERATED . . . . .	Gear to fly wheel
WHEELS . . . . .	Wood	LIGHTING SYSTEM . . . . .	Electric
FRONT TIRES . . . . .	30 x 3½ inches, anti-skid	VOLTAGES . . . . .	Six to eight
REAR TIRES . . . . .	30 x 3½ inches, anti-skid	WIRING SYSTEM . . . . .	Single
SERVICE BRAKE . . . . .	Contracting on rear wheels	GASOLINE SYSTEM . . . . .	Gravity
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	CLUTCH . . . . .	Cone
CYLINDERS . . . . .	Four	TRANSMISSION . . . . .	Selective sliding
HOW ARRANGED . . . . .	Vertically	GEAR CHANGES . . . . .	Three forward, one reverse
CAST . . . . .	En bloc	DRIVE . . . . .	Spiral bevel
HORSEPOWER . . . . .	21.75 (N.A.C.C. Rating)	REAR AXLE . . . . .	Three-quarters floating
BORE AND STROKE . . . . .	3½ x 4 inches	STEERING GEAR . . . . .	Spur and gear
LUBRICATION . . . . .	Splash with circulating pump		

In addition to above specifications, price includes top, top hood, windshield, electric starter, speedometer, ammeter, tire pump and jack, electric horn, complete lamp equipment, including headlight dimmers, demountable rims, extra rim and carrier, and complete tools.

# CHEVROLET MOTOR COMPANY

BROADWAY  
AT 57th STREET  
NEW YORK CITY

Price	.....	\$1185
"Four-Ninety" Coupe	.....	1110
"Four-Ninety" Touring	.....	735
"Four-Ninety" Roadster	.....	715
"Four-Ninety" Light Delivery Wagon	.....	735
"Four-Ninety" Station Wagon	.....	770



## CHEVROLET "FOUR-NINETY" SEDAN

COLOR	.....	Black	LUBRICATION	.....	Splash with circulating pump
SEATING CAPACITY	.....	Five	RADIATOR	.....	Cellular
POSITION OF DRIVER	.....	Left side	COOLING	.....	Water pump
WHEELBASE	.....	102 inches	IGNITION	.....	High tension magneto and storage battery
GAUGE	.....	56 inches	STARTING SYSTEM	.....	Two unit
WHEELS	.....	Wood	STARTER OPERATED	.....	Gear to fly wheel
FRONT TIRES	.....	31 x 4 inches	LIGHTING SYSTEM	.....	Electric
REAR TIRES	.....	31 x 4 inches, anti-skid	VOLTAGES	.....	Six to eight
SERVICE BRAKE	.....	Contracting on rear wheels	WIRING SYSTEM	.....	Single
EMERGENCY BRAKE	.....	Expanding on rear wheels	GASOLINE SYSTEM	.....	Gravity
CYLINDERS	.....	Four	CLUTCH	.....	Cone
HOW ARRANGED	.....	Vertically	TRANSMISSION	.....	Selective sliding
CAST	.....	En bloc	GEAR CHANGES	.....	Three forward, one reverse
HORSEPOWER	.....	21.75 (N.A.C.C. Rating)	DRIVE	.....	Spiral bevel
BORE AND STROKE	.....	3½ x 4 inches	REAR AXLE	.....	Three-quarters floating
			STEERING GEAR	.....	Spur and gear


In addition to above specifications, price includes windshield, electric starter, speedometer, ammeter, tire pump, jack and complete tools, electric horn, complete lamp equipment including headlight dimmers, demountable rims, extra rim and carrier.

**OLDS MOTOR  
WORKS**  

---

**LANSING  
MICHIGAN**

Price . . . . .	\$1395
Two-Passenger Roadster . . . .	1395
Four-Passenger Coupe . . . . .	1995
Five-Passenger Sedan . . . . .	1995




---

**OLDSMOBILE TOURING—37-A**

---


COLOR . . . . .	Body, Periscope green; running gear, black; wheels, natural wood	BORE AND STROKE . . . . .	2 $\frac{1}{8}$ x 4 $\frac{3}{4}$ inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Force feed
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	112 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	32 x 4 inches	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4 inches, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Cone
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	19	GEAR CHANGES . . . . .	Three forward, one reverse
(N.A.C.C. Rating)		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Screw and nut

In addition to above specifications, price includes top, top hood, wind-shield, speedometer, ammeter, clock, electric horn and demountable rims.



**OLDS MOTOR  
WORKS  
LANSING  
MICHIGAN**

**Price . . . . . \$1895**  
**Four-Passenger "Pacemaker" . 1895**  
**Seven-Passenger Sedan . . . . 2950**




---

**OLDSMOBILE "THOROBRED" TOURING—45-B**

---

<b>COLOR . . . . .</b>	Body, Periscope green; running gear, black; wheels, natural wood	<b>BORE AND STROKE . . . . .</b>	2 $\frac{1}{4}$ x 4 $\frac{3}{4}$ inches
<b>SEATING CAPACITY</b>	Seven	<b>LUBRICATION . . . . .</b>	Force feed
<b>POSITION OF DRIVER</b>	Left side	<b>RADIATOR . . . . .</b>	Cellular
<b>WHEELBASE . . . . .</b>	122 inches	<b>COOLING . . . . .</b>	Water pump
<b>GAUGE . . . . .</b>	56 inches	<b>IGNITION . . . . .</b>	Storage battery
<b>WHEELS . . . . .</b>	Wood	<b>STARTING SYSTEM . . . . .</b>	Two unit
<b>FRONT TIRES . . . . .</b>	33 x 4 $\frac{1}{2}$ inches	<b>STARTER OPERATED . . . . .</b>	Gear to fly wheel
<b>REAR TIRES . . . . .</b>	33 x 4 $\frac{1}{2}$ inches, anti-skid	<b>LIGHTING SYSTEM . . . . .</b>	Electric
<b>SERVICE BRAKE . . . . .</b>	Contracting on rear wheels	<b>VOLTAGE . . . . .</b>	Six
<b>EMERGENCY BRAKE . . . . .</b>	Expanding on rear wheels	<b>WIRING SYSTEM . . . . .</b>	Single
<b>CYLINDERS . . . . .</b>	Eight	<b>GASOLINE SYSTEM . . . . .</b>	Vacuum
<b>HOW ARRANGED . . . . .</b>	V type, 90 degrees	<b>CLUTCH . . . . .</b>	Cone
<b>CAST . . . . .</b>	In fours	<b>TRANSMISSION . . . . .</b>	Selective sliding
<b>HORSEPOWER . . . . .</b>	26.45	<b>GEAR CHANGES . . . . .</b>	Three forward, one reverse
(N.A.C.C. Rating)		<b>DRIVE . . . . .</b>	Spiral bevel
		<b>REAR AXLE . . . . .</b>	Full floating
		<b>STEERING GEAR . . . . .</b>	Screw and nut


In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, clock, electric horn and demountable rims.

---

# ELKHART CARRIAGE AND MOTOR CAR COMPANY

ELKHART  
INDIANA

Price . . . . .	\$1595
Four-Passenger Sportster . . . . .	1595
Three-Passenger Coupe . . . . .	2195
Five-Passenger Sedan . . . . .	2295



## ELCAR TOURING—D-SIX


COLOR . . . . .	Body, coach blue or maroon; running gear, black	BORE AND STROKE . . . . .	3¼ x 4½ inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Full force feed
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	116 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Single unit
FRONT TIRES . . . . .	33 x 4 inches	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	33 x 4 inches, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry plate
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	25.35 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes top, windshield, speedometer, ammeter, motometer, electric horn and demountable rims.

# ELKHART CARRIAGE AND MOTOR CAR COMPANY

ELKHART  
INDIANA

Price . . . . .	\$2095
Five-Passenger Touring . . . .	1395
Four-Passenger Sportster . . . .	1395
Three-Passenger Coupe . . . .	1995



## ELCAR SEDAN—G-FOUR


COLOR . . . . .	Body, coach blue below belt, black above; running gear, black	BORE AND STROKE . . . .	3½ x 5 inches
SEATING CAPACITY . . . .	Five	LUBRICATION . . . . .	Pump over and splash
POSITION OF DRIVER . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	116 inches	COOLING . . . . .	Thermo-syphon
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . .	Single unit
FRONT TIRES . . . . .	33 x 4 inches	STARTER OPERATED . . .	Gear to fly wheel
REAR TIRES . . . . .	33 x 4 inches, anti-skid	LIGHTING SYSTEM . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Four	GASOLINE SYSTEM . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry plate
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	19.6 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes windshield, speedometer, ammeter, motometer, electric horn and demountable rims.

**MOLINE PLOW  
COMPANY**  
**STEPHENS  
MOTOR  
WORKS**

**MOLINE, ILLINOIS**

Price . . . . .	\$2050
Two-Passenger Roadster—82 . . .	2050
Six-Passenger Touring—86 . . .	2050
Four-Passenger Coupe—83 . . .	3050
Five-Passenger Sedan—85 . . .	3050




---

**STEPHENS SALIENT SIX—84**

---


COLOR . . . . .	Body, Saginaw red; running gear, black	BORE AND STROKE . . .	3¼ x 4½ inches
SEATING CAPACITY . .	Four	LUBRICATION . . . . .	Full force feed
POSITION OF DRIVER .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	122 inches	COOLING . . . . .	Thermo-syphon
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . .	Single unit
FRONT TIRES . . . . .	32 x 4 inches, cord, rib tread	STARTER OPERATED .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4 inches, cord, anti-skid	LIGHTING SYSTEM . .	Electric
SERVICE BRAKE . . .	Contracting on rear axle	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . .	Expanding on rear axle	WIRING SYSTEM . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . .	Vacuum
HOW ARRANGED . . .	Vertically	CLUTCH . . . . .	Dry disc
CAST . . . . .	En bloc	TRANSMISSION . . .	Selective sliding
HORSEPOWER . . . . .	25.35 (N.A.C.C. Rating)	GEAR CHANGES . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.

**MITCHELL  
MOTORS  
COMPANY  
INCORPORATED**

**R A C I N E  
W I S C O N S I N**

**Price . . . . . \$1690**  
**Three-Passenger Roadster . . . 1690**




---

**MITCHELL TOURING—E-40**

---


COLOR . . . . .	Body, cobalt blue; running gear, black; wheels, cream	BORE AND STROKE . .	3¼ x 5 inches
SEATING CAPACITY .	Five	LUBRICATION . . . .	Force feed and splash
POSITION OF DRIVER	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . .	120 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . .	Two unit
FRONT TIRES . . . .	33 x 4 inches	STARTER OPERATED .	Gear to fly wheel
REAR TIRES . . . .	33 x 4 inches, anti-skid	LIGHTING SYSTEM . .	Electric
SERVICE BRAKE . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE .	Expanding on rear wheels	WIRING SYSTEM . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . .	Vacuum
HOW ARRANGED . .	Vertically	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	En bloc	TRANSMISSION . . .	Selective sliding
HORSEPOWER . . . .	25.35 (N.A.C.C. Rating)	GEAR CHANGES . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Full floating
		STEERING GEAR . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, tire pump, electric horn, spare tire carrier and demountable rims.

---

**MITCHELL  
MOTORS  
COMPANY  
INCORPORATED**  
**RACINE  
WISCONSIN**

**Price, \$2500**





---

**MITCHELL COUPE—E-40**

---

<b>COLOR . . . . .</b>	Body, cobalt blue; running gear, black; wheels, cream	<b>BORE AND STROKE . . .</b>	3¼ x 5 inches
<b>SEATING CAPACITY . .</b>	Four	<b>LUBRICATION . . . . .</b>	Force feed and splash
<b>POSITION OF DRIVER</b>	Left side	<b>RADIATOR . . . . .</b>	Cellular
<b>WHEELBASE . . . . .</b>	120 inches	<b>COOLING . . . . .</b>	Water pump
<b>GAUGE . . . . .</b>	56 inches	<b>IGNITION . . . . .</b>	Storage battery
<b>WHEELS . . . . .</b>	Wood	<b>STARTING SYSTEM . . .</b>	Two unit
<b>FRONT TIRES . . . . .</b>	33 x 4 inches, cord, anti-skid	<b>STARTER OPERATED . .</b>	Gear to fly wheel
<b>REAR TIRES . . . . .</b>	33 x 4 inches, cord, anti-skid	<b>LIGHTING SYSTEM . . .</b>	Electric
<b>SERVICE BRAKE . . .</b>	Contracting on rear wheels	<b>VOLTAGE . . . . .</b>	Six
<b>EMERGENCY BRAKE . .</b>	Expanding on rear wheels	<b>WIRING SYSTEM . . . .</b>	Single
<b>CYLINDERS . . . . .</b>	Six	<b>GASOLINE SYSTEM . . .</b>	Vacuum
<b>HOW ARRANGED . . .</b>	Vertically	<b>CLUTCH . . . . .</b>	Dry multiple disc
<b>CAST . . . . .</b>	En bloc	<b>TRANSMISSION . . . .</b>	Selective sliding
<b>HORSEPOWER . . . . .</b>	25.35 (N.A.C.C. Rating)	<b>GEAR CHANGES . . . .</b>	Three forward, one reverse
		<b>DRIVE . . . . .</b>	Spiral bevel
		<b>REAR AXLE . . . . .</b>	Full floating
		<b>STEERING GEAR . . . .</b>	Worm and gear

In addition to above specifications, price includes windshield and cleaner, speedometer, ammeter, tire pump, electric horn, spare tire carrier and demountable rims.




---

**MITCHELL SEDAN—E-40**

---

<b>COLOR . . . . .</b>	Body, cobalt blue; running gear, black; wheels, cream	<b>BORE AND STROKE . . .</b>	3¼ x 5 inches
<b>SEATING CAPACITY . .</b>	Five	<b>LUBRICATION . . . . .</b>	Force feed and splash
<b>POSITION OF DRIVER .</b>	Left side	<b>RADIATOR . . . . .</b>	Cellular
<b>WHEELBASE . . . . .</b>	120 inches	<b>COOLING . . . . .</b>	Water pump
<b>GAUGE . . . . .</b>	56 inches	<b>IGNITION . . . . .</b>	Storage battery
<b>WHEELS . . . . .</b>	Wood	<b>STARTING SYSTEM . . .</b>	Two unit
<b>FRONT TIRES . . . . .</b>	33 x 4 inches, cord, anti-skid	<b>STARTER OPERATED . .</b>	Gear to fly wheel
<b>REAR TIRES . . . . .</b>	33 x 4 inches, cord, anti-skid	<b>LIGHTING SYSTEM . . .</b>	Electric
<b>SERVICE BRAKE . . . .</b>	Contracting on rear wheels	<b>VOLTAGE . . . . .</b>	Six
<b>EMERGENCY BRAKE . .</b>	Expanding on rear wheels	<b>WIRING SYSTEM . . . .</b>	Single
<b>CYLINDERS . . . . .</b>	Six	<b>GASOLINE SYSTEM . . .</b>	Vacuum
<b>HOW ARRANGED . . . .</b>	Vertically	<b>CLUTCH . . . . .</b>	Dry multiple disc
<b>CAST . . . . .</b>	En bloc	<b>TRANSMISSION . . . . .</b>	Selective sliding
<b>HORSEPOWER . . . . .</b>	25.35 (N.A.C.C. Rating)	<b>GEAR CHANGES . . . .</b>	Three forward, one reverse
		<b>DRIVE . . . . .</b>	Spiral bevel
		<b>REAR AXLE . . . . .</b>	Full floating
		<b>STEERING GEAR . . . .</b>	Worm and gear


In addition to above specifications, price includes windshield and cleaner, speedometer, ammeter, tire pump, electric horn, spare tire carrier and demountable rims.

---

# PREMIER MOTOR CORPORATION

INDIANAPOLIS  
INDIANA

Four-Passenger Open Car . . .	} Prices Upon Appli- cation
Two-Passenger Open Car . . .	
Seven-Passenger Closed Car . . .	
Four-Passenger Closed Car . . .	



## PREMIER SEVEN-PASSENGER OPEN CAR—6-D

COLOR . . . . .	Body, blue, ma- roon or gray; running gear, black	BORE AND STROKE . . .	3¼ x 5½ inches
SEATING CAPACITY . .	Seven	LUBRICATION . . . . .	Force feed and splash
POSITION OF DRIVER.	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	126¾ inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . .	Single unit
FRONT TIRES . . . . .	32 x 4½ inches, ribbed cord	STARTER OPERATED .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4½ inches, ribbed cord	LIGHTING SYSTEM . .	Electric
SERVICE BRAKE . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE .	Expanding on rear wheels	WIRING SYSTEM . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . .	Vacuum
HOW ARRANGED . . .	Vertically	CLUTCH . . . . .	Dry disc
CAST . . . . .	En bloc	TRANSMISSION . . . .	Selective sliding
HORSEPOWER . . . . .	27.34 (N.A.C.C. Rating)	GEAR CHANGES . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . .	Worm and gear


In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, clock, tire pump, electric horn, demountable rims, C-H Magnetic Gear Shift, six cord tires, Pyrene Fire Extinguisher, two spot lamps and Perfection Heater.



# PREMIER MOTOR CORPORATION

INDIANAPOLIS  
INDIANA

Seven-Passenger Open Car . . .	} Prices Upon Appli- cation
Four-Passenger Open Car . . .	
Two-Passenger Open Car . . .	
Four-Passenger Closed Car . . .	



## PREMIER SEVEN-PASSENGER CLOSED CAR—6-D


COLOR . . . . .	Body, blue; running gear, black	BORE AND STROKE . . .	3½ x 5½ inches
SEATING CAPACITY . .	Seven	LUBRICATION . . . . .	Force feed and splash
POSITION OF DRIVER .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	126¾ inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . .	Single unit
FRONT TIRES . . . . .	32 x 4½ inches, ribbed cord	STARTER OPERATED .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4½ inches, ribbed cord	LIGHTING SYSTEM . .	Electric
SERVICE BRAKE . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . .	Expanding on rear wheels	WIRING SYSTEM . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . .	Vacuum
HOW ARRANGED . . .	Vertically	CLUTCH . . . . .	Dry disc
CAST . . . . .	En bloc	TRANSMISSION . . .	Selective sliding
HORSEPOWER . . . .	27.34 (N.A.C.C. Rating)	GEAR CHANGES . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . .	Worm and gear

In addition to above specifications, price includes windshield, speedometer, ammeter, clock, tire pump, electric horn, demountable rims, C-H Magnetic Gear Shift, six cord tires, Pyrene Fire Extinguisher, two spot lamps and Perfection Heater.

**M E R C E R  
M O T O R S  
C O M P A N Y**

**T R E N T O N  
N E W J E R S E Y**

**Price, \$4950**




---

**M E R C E R T O U R I N G**

---

COLOR . . . . .	Blue, green, ma- roon, brown or gray	LUBRICATION . . . .	Full force feed
SEATING CAPACITY . .	Six	RADIATOR . . . . .	Cellular
POSITION OF DRIVER .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	132 inches	IGNITION . . . . .	High tension magneto
GAUGE . . . . .	56 inches	STARTING SYSTEM . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . . . .	32 x 4½ inches, cord	LIGHTING SYSTEM . .	Electric
REAR TIRES . . . . .	32 x 4½ inches, cord	VOLTAGE . . . . .	Six
SERVICE BRAKE . . .	Expanding on transmission	WIRING SYSTEM . . .	Single
EMERGENCY BRAKE . .	Expanding on rear wheels	GASOLINE SYSTEM . .	Vacuum
CYLINDERS . . . . .	Four	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . . .	Vertically	TRANSMISSION . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . .	Four forward, one reverse
HORSEPOWER . . . . .	22.5 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . .	3¾ x 6¾ inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . .	Worm and gear


In addition to above specifications, price includes top, top hood, wind-  
shield, speedometer, ammeter, clock, electric horn and demountable rims.

---

# MERCER MOTORS COMPANY

TRENTON  
NEW JERSEY

Price, \$4950



## MERCER SPORTING


COLOR . . . . .	Blue, green, maroon, brown or gray	LUBRICATION . . . .	Full force feed
SEATING CAPACITY .	Four	RADIATOR . . . . .	Cellular
POSITION OF DRIVER	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	132 inches	IGNITION . . . . .	High tension magneto
GAUGE . . . . .	56 inches	STARTING SYSTEM . .	Two unit
WHEELS . . . . .	Wire	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . . .	32x4½ inches, cord	LIGHTING SYSTEM . .	Electric
REAR TIRES . . . .	32x4½ inches, cord	VOLTAGE . . . . .	Six
SERVICE BRAKE . . .	Expanding on transmission	WIRING SYSTEM . . .	Single
EMERGENCY BRAKE .	Expanding on rear wheels	GASOLINE SYSTEM . .	Vacuum
CYLINDERS . . . . .	Four	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . . .	Vertically	TRANSMISSION . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . .	Four forward, one reverse
HORSEPOWER . . . .	22.5 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . .	3¼ x 6¾ inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, clock, electric horn and wire wheels.

# MERCER MOTORS COMPANY

TRENTON  
NEW JERSEY

Price, \$4675



## MERCER RACEABOUT


COLOR . . . . .	Yellow, gray or gunmetal	BORE AND STROKE . .	3¼ x 6¾ inches
SEATING CAPACITY .	Two	LUBRICATION . . . .	Full force feed
POSITION OF DRIVER	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . .	115 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	High tension magneto
WHEELS . . . . .	Wire	STARTING SYSTEM . .	Two unit
FRONT TIRES . . . .	32x4¼ inches, cord	STARTER OPERATED .	Gear to fly wheel
REAR TIRES . . . .	32x4¼ inches, cord	LIGHTING SYSTEM . .	Electric
SERVICE BRAKE . .	Expanding on transmission	VOLTAGE . . . . .	Six
EMERGENCY BRAKE .	Expanding on rear wheels	WIRING SYSTEM . . .	Single
CYLINDERS . . . . .	Four	GASOLINE SYSTEM . .	Vacuum
HOW ARRANGED . .	Vertically	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	En bloc	TRANSMISSION . . .	Selective sliding
HORSEPOWER . . . .	22.5 (N.A.C.C. Rating)	GEAR CHANGES . . .	Four forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Full floating
		STEERING GEAR . . .	Worm and gear

In addition to above specifications, price includes windshield, speedometer, ammeter, clock, electric horn and wire wheels.

# LOCOMOBILE COMPANY OF AMERICA

BRIDGEPORT  
CONNECTICUT

Price . . . . .	\$8100
Sportif . . . . .	8200
Limousine . . . . .	9600
Landaulet . . . . .	9600
Chassis . . . . .	7100



## LOCOMOBILE TOURING 48—SERIES 7


COLOR . . . . .	Optional	LUBRICATION . . . . .	Force feed and splash
SEATING CAPACITY . . . . .	Seven	RADIATOR . . . . .	Cellular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	142 inches	IGNITION . . . . .	High tension magneto
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	35 x 5 inches cord	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	35 x 5 inches cord, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Pressure
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	In pairs	GEAR CHANGES . . . . .	Four forward, one reverse
HORSEPOWER . . . . .	48.6 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	4½ x 5½ inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, voltmeter, clock, tire pump, electric horn and demountable rims.

# OAKLAND MOTOR CAR COMPANY

PONTIAC  
MICHIGAN

Price . . . . .	\$1165
Roadster . . . . .	1165
Four-Door Sedan . . . . .	1825
Coupe . . . . .	1825



## OAKLAND SENSIBLE SIX TOURING—34-C


COLOR . . . . .	Body and wheels, Brewster green; running gear, black	BORE AND STROKE . . . . .	2 1/8 x 4 3/4 inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Force feed and spray
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular and tubular
WHEELBASE . . . . .	115 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	32 x 4 inches	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4 inches, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGES . . . . .	Six-seven
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Cone
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	18.98 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Plain bevel
		REAR AXLE . . . . .	One bearing, full floating
		STEERING GEAR . . . . .	Screw and nut

In addition to above specifications, price includes top, windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.

# OAKLAND MOTOR CAR COMPANY

PONTIAC  
MICHIGAN

Price . . . . .	\$1825
Coupe . . . . .	1825
Touring Car . . . . .	1165
Roadster . . . . .	1165



## OAKLAND SENSIBLE SIX FOUR-DOOR SEDAN—34-C


COLOR . . . . .	Body, blue black; running gear and wheels, black	BORE AND STROKE . . . . .	2 $\frac{1}{8}$ x 4 $\frac{3}{4}$ inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Force feed and spray
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular and tubular
WHEELBASE . . . . .	115 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	32 x 4 inches	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4 inches, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGES . . . . .	Six-seven
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Cone
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	18.98 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Plain bevel
		REAR AXLE . . . . .	One bearing, full floating
		STEERING GEAR . . . . .	Screw and nut

In addition to above specifications, price includes windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.

# NATIONAL MOTOR CAR AND VEHICLE CORPORATION

INDIANAPOLIS  
N D I A N A

Price . . . . .	\$3500
Four-Passenger Phaeton . . . . .	3500
Two-Passenger Roadster . . . . .	3500
Four-Passenger Coupe . . . . .	4650
Seven-Passenger Sedan . . . . .	4700



## NATIONAL SEXTET TOURING

COLOR . . . . .	Blue, gray or green	BORE AND STROKE . . . . .	3 1/2 x 5 1/4 inches
SEATING CAPACITY . . . . .	Seven	LUBRICATION . . . . .	Force feed
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	130 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	32 x 4 1/2 inches, cord	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4 1/2 inches, cord	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear axle	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear axle	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Single dry plate
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	29.4 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and gear


In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, oil gauge, locked electric switch, tire pump, electric horn, motor light, shock absorbers all around, tonneau light, emergency gasoline valve, muffler cut-out, foot pedal pads, motometer, transmission theft lock, demountable rims and complete tool equipment.



# NATIONAL MOTOR CAR AND VEHICLE CORPORATION

INDIANAPOLIS  
I N D I A N A

Price . . . . .	\$4700
Four-Passenger Coupe . . . . .	4650
Seven-Passenger Touring . . . . .	3500
Four-Passenger Phaeton . . . . .	3500
Two-Passenger Roadster . . . . .	3500



## NATIONAL SEXTET SEDAN


COLOR . . . . .	Blue, gray or green	LUBRICATION . . . . .	Force feed
SEATING CAPACITY . . . . .	Seven	RADIATOR . . . . .	Cellular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	130 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	32 x 4 1/2 inches, cord	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	32 x 4 1/2 inches, cord	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear axle	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear axle	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Single dry plate
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	29.4 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3 1/2 x 5 1/4 inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes clock, speedometer, ammeter, oil gauge, locked electric switch, tire pump, electric horn, motor light, shock absorbers all around, smoking and vanity sets, dome, corner and step lights, emergency gasoline valve, muffler cut-out, foot pedal pads, motometer, transmission, theft lock, demountable rims and complete tool equipment.

# KLINE CAR CORPORATION

RICHMOND  
VIRGINIA

Price . . . . .	\$1965
Roadster . . . . .	1965
Sport Touring . . . . .	1965
Touring With Auxilliary Seats . . . . .	1990
Sedan With Auxilliary Seats . . . . .	2790
Coupe . . . . .	2750



## KLINE KAR SPORT TOURING MODEL 6-55


COLOR . . . . .	Body, green; running gear, black	LUBRICATION . . . . .	Full force feed
SEATING CAPACITY . . . . .	Four or five	RADIATOR . . . . .	Cellular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	121 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	33 x 4 inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	33 x 4 inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Plate
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	25.35 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3 3/4 x 4 1/2 inches	REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . . . .	Worm and nut

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, motometer, tire pump, electric horn, spot light and demountable rims.

**MAXWELL  
MOTOR  
COMPANY  
INCORPORATED**

**DETROIT  
MICHIGAN**

<b>Price</b> . . . . .	<b>\$985</b>
<b>Roadster</b> . . . . .	<b>985</b>
<b>Coupe</b> . . . . .	<b>1610</b>
<b>Sedan</b> . . . . .	<b>1655</b>
<b>Chassis with Cowl</b> . . . . .	<b>895</b>




---

**MAXWELL FIVE-PASSENGER TOURING**

---

<b>COLOR</b> . . . . .	Body blue; running gear, black	<b>BORE AND STROKE</b> . . . . .	3 $\frac{3}{4}$ x 4 $\frac{1}{4}$ inches
<b>SEATING CAPACITY</b> . . . . .	Five	<b>LUBRICATION</b> . . . . .	Pump over and splash
<b>POSITION OF DRIVER</b> . . . . .	Left side	<b>RADIATOR</b> . . . . .	Tubular
<b>WHEELBASE</b> . . . . .	108 inches	<b>COOLING</b> . . . . .	Thermo-syphon
<b>GAUGE</b> . . . . .	56 inches	<b>IGNITION</b> . . . . .	Storage battery
<b>WHEELS</b> . . . . .	Wood	<b>STARTING SYSTEM</b> . . . . .	Two unit
<b>FRONT TIRES</b> . . . . .	30 x 3 $\frac{1}{2}$ inches	<b>STARTER OPERATED</b> . . . . .	Gear to fly wheel
<b>REAR TIRES</b> . . . . .	30 x 3 $\frac{1}{2}$ inches, anti-skid	<b>LIGHTING SYSTEM</b> . . . . .	Electric
<b>SERVICE BRAKE</b> . . . . .	Contracting on rear axle	<b>VOLTAGE</b> . . . . .	Six
<b>EMERGENCY BRAKE</b> . . . . .	Contracting on transmission	<b>WIRING SYSTEM</b> . . . . .	Single
<b>CYLINDERS</b> . . . . .	Four	<b>GASOLINE SYSTEM</b> . . . . .	Vacuum
<b>HOW ARRANGED</b> . . . . .	Vertically	<b>CLUTCH</b> . . . . .	Cone, running in oil
<b>CAST</b> . . . . .	En bloc	<b>TRANSMISSION</b> . . . . .	Selective sliding
<b>HORSEPOWER</b> . . . . .	21.03 (N.A.C.C. Rating)	<b>GEAR CHANGES</b> . . . . .	Three forward, one reverse
		<b>DRIVE</b> . . . . .	Plain bevel
		<b>REAR AXLE</b> . . . . .	Three-quarters floating
		<b>STEERING GEAR</b> . . . . .	Worm and gear


In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.

---

# D O R T M O T O R C A R C O M P A N Y

FLINT, MICHIGAN

Price . . . . .	\$1535
Five - Passenger Fourseason Sedan . . . . .	1535
Five-Passenger Touring . . . . .	985
Two-Passenger Roadster . . . . .	985




## DORT THREE-PASSENGER FOURSEASON COUPE—MODEL 10-C

COLOR . . . . .	Sedan green	LUBRICATION . . . . .	Splash with circulating pump
SEATING CAPACITY . . . . .	Five	RADIATOR . . . . .	Cellular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Thermo-syphon
WHEELBASE . . . . .	105 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	31 x 4 inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	31 x 4 inches, non-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Four	CLUTCH . . . . .	Cone
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	19.6 (N.A.C.C. Rating)	DRIVE . . . . .	Plain bevel
BORE AND STROKE . . . . .	3½ x 5 inches	REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . . . .	Screw and nut

In addition to above specifications, price includes windshield, speedometer, ammeter, voltmeter, clock, tire pump, electric horn and demountable rims.

**D O R T  
MOTORCAR  
COMPANY**  
**FLINT, MICHIGAN**

Price . . . . .	\$1535
Three-Passenger Fourseason Coupe . . . . .	1535
Five-Passenger Touring . . . . .	985
Two-Passenger Roadster . . . . .	985




---

**DORT FIVE-PASSENGER FOURSEASON SEDAN—MODEL 15-S**

---


COLOR . . . . .	Sedan green	LUBRICATION . . . .	Splash with circulating pump
SEATING CAPACITY .	Five	RADIATOR . . . . .	Cellular
POSITION OF DRIVER.	Left side	COOLING . . . . .	Thermo-syphon
WHEELBASE . . . .	105 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED.	Gear to fly wheel
FRONT TIRES . . . .	31 x 4 inches	LIGHTING SYSTEM .	Electric
REAR TIRES . . . .	31 x 4 inches, non-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . .	Contracting on rear wheels	WIRING SYSTEM . .	Single
EMERGENCY BRAKE .	Expanding on rear wheels	GASOLINE SYSTEM .	Vacuum
CYLINDERS . . . . .	Four	CLUTCH . . . . .	Cone
HOW ARRANGED . .	Vertically	TRANSMISSION . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . .	Three forward, one reverse
HORSEPOWER . . . .	19.6 (N.A.C.C. Rating)	DRIVE . . . . .	Plain bevel
BORE AND STROKE .	3½ x 5 inches	REAR AXLE . . . .	Three-quarters floating
		STEERING GEAR . . .	Screw and nut

In addition to above specifications, price includes windshield, speedometer, ammeter, voltmeter, clock, tire, pump, electric horn and demountable rims.

# BRISCOE MOTOR CORPORATION

JACKSON  
MICHIGAN

Roadster . . . . .	} Prices Upon Appli- cation
Coupe . . . . .	
Sedan . . . . .	



## 1920 BRISCOE TOURING

COLOR . . . . .	Body and wheels, blue; chassis and fenders, black	BORE AND STROKE . . . . .	3½ x 5 inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Pump over and splash
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Tubular-zig zag
WHEELBASE . . . . .	109 inches	COOLING . . . . .	Thermo-syphon
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood or steel	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	31 x 4 inches non-skid	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	31 x 4 inches non-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Contracting on transmission	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Four	GASOLINE SYSTEM . . . . .	Gravity
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Cone
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	18.23 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear


In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.

**N A S H  
M O T O R S  
C O M P A N Y**  

---

**K E N O S H A  
W I S C O N S I N**

<b>Price . . . . .</b>	<b>\$1490</b>
<b>Two-Passenger Roadster . . . . .</b>	<b>1490</b>
<b>Four-Passenger Sport . . . . .</b>	<b>1595</b>
<b>Seven-Passenger Touring . . . . .</b>	<b>1640</b>
<b>Four-Passenger Coupe . . . . .</b>	<b>2350</b>
<b>Seven-Passenger Sedan . . . . .</b>	<b>2575</b>




---

**NASH SIX FIVE-PASSENGER TOURING**

---


<b>COLOR . . . . .</b>	<b>Nash blue</b>	<b>LUBRICATION . . . . .</b>	<b>Splash with circulating pump</b>
<b>SEATING CAPACITY . . . . .</b>	<b>Five</b>	<b>RADIATOR . . . . .</b>	<b>Vertical tube</b>
<b>POSITION OF DRIVER . . . . .</b>	<b>Left side</b>	<b>COOLING . . . . .</b>	<b>Water pump</b>
<b>WHEELBASE . . . . .</b>	<b>121 inches</b>	<b>IGNITION . . . . .</b>	<b>High tension timer and storage battery</b>
<b>GAUGE . . . . .</b>	<b>56 inches</b>	<b>STARTING SYSTEM . . . . .</b>	<b>Two unit</b>
<b>WHEELS . . . . .</b>	<b>Wood</b>	<b>STARTER OPERATED . . . . .</b>	<b>Gear to fly wheel</b>
<b>FRONT TIRES . . . . .</b>	<b>33 x 4 inches</b>	<b>LIGHTING SYSTEM . . . . .</b>	<b>Electric</b>
<b>REAR TIRES . . . . .</b>	<b>33 x 4 inches, anti-skid</b>	<b>VOLTAGES . . . . .</b>	<b>Six to eight</b>
<b>SERVICE BRAKE . . . . .</b>	<b>Contracting on rear wheels</b>	<b>WIRING SYSTEM . . . . .</b>	<b>Single</b>
<b>EMERGENCY BRAKE . . . . .</b>	<b>Contracting on propeller shaft</b>	<b>GASOLINE SYSTEM . . . . .</b>	<b>Vacuum</b>
<b>CYLINDERS . . . . .</b>	<b>Six</b>	<b>CLUTCH . . . . .</b>	<b>Three plate</b>
<b>HOW ARRANGED . . . . .</b>	<b>Vertically</b>	<b>TRANSMISSION . . . . .</b>	<b>Selective sliding</b>
<b>CAST . . . . .</b>	<b>En bloc</b>	<b>GEAR CHANGES . . . . .</b>	<b>Three forward, one reverse</b>
<b>HORSEPOWER . . . . .</b>	<b>25.35 (N.A.C.C. Rating)</b>	<b>DRIVE . . . . .</b>	<b>Spiral bevel</b>
<b>BORE AND STROKE . . . . .</b>	<b>3 1/4 x 5 inches</b>	<b>REAR AXLE . . . . .</b>	<b>Semi-floating</b>
		<b>STEERING GEAR . . . . .</b>	<b>Worm and gear</b>

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, clock, electric horn and demountable rims.

**THE  
BARTHOLOMEW  
COMPANY**

**PEORIA, ILLINOIS**

**Price . . . . . \$1695**  
**Four-Passenger Roadster . . . . 1695**




---

**GLIDE LIGHT TOURING SIX—40**

---

COLOR . . . . .	Body, meteor blue or maroon; running gear, black with ivory wheels	BORE AND STROKE . . . . .	3¼ x 5 inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Splash with circulating pump
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Tubular
WHEELBASE . . . . .	119 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	34 x 4 inches	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	34 x 4 inches, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	23.44 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . . . .	Worm and gear


In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.



# PACKARD MOTOR CAR COMPANY

DETROIT  
MICHIGAN

Four-Passenger Runabout . . .	} Prices Upon Appli- cation
Four-Passenger Phaeton . . .	
Seven-Passenger Limousine . . .	
Seven-Passenger Duplex Sedan . . .	
Seven-Passenger Coupe . . .	
Chassis only . . . . .	



## PACKARD TWIN-SIX TOURING


COLOR . . . . .	Body and door panels, Packard blue striped with cream yellow; moulding, black; wheels, cream yellow striped with black	HORSEPOWER . . . . . 43.2 (N.A.C.C. Rating)
SEATING CAPACITY . . . . .	Seven	BORE AND STROKE . . . . . 3 x 5 inches
POSITION OF DRIVER . . . . .	Left side	LUBRICATION . . . . . Force feed
WHEELBASE. . . . .	136 inches	RADIATOR . . . . . Cellular
GAUGE . . . . .	56 inches	COOLING . . . . . Water pump
WHEELS . . . . .	Wood	IGNITION . . . . . Storage battery
FRONT TIRES . . . . .	35 x 5 ins., rib cord	STARTING SYSTEM . . . . . Two unit
REAR TIRES . . . . .	35 x 5 ins., cord, non-skid	STARTER OPERATED . . . . . Gear to fly wheel
SERVICE BRAKE . . . . .	Contracting on rear wheels	LIGHTING SYSTEM . . . . . Electric
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	VOLTAGE . . . . . Six
CYLINDERS . . . . .	Twelve	WIRING SYSTEM . . . . . Single
HOW ARRANGED . . . . .	V type, 60 degrees	GASOLINE SYSTEM . . . . . Pressure
CAST . . . . .	In sixes	CLUTCH . . . . . Dry multiple disc
		TRANSMISSION . . . . . Selective sliding
		GEAR CHANGES . . . . . Three forward, one reverse
		DRIVE . . . . . Spiral bevel
		REAR AXLE . . . . . Semi-floating
		STEERING GEAR . . . . . Worm and nut

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, clock, tire pump, electric horn and demountable rims.

**APPERSON  
BROTHERS  
AUTOMOBILE  
COMPANY**

**K O K O M O  
I N D I A N A**

Price . . . . .	\$2950
Four-Passenger Sportster . . . .	2950
Four-Passenger Sedanette . . . .	4000
Seven-Passenger Sedan . . . . .	4000




---

**APPERSON STANDARD TOURING—8-20**

---

COLOR . . . . .	Glidden green	BORE AND STROKE .	3¼ x 5 inches
SEATING CAPACITY .	Seven	LUBRICATION . . . .	Full force feed
POSITION OF DRIVER.	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . .	130 inches	COOLING . . . . .	Thermo-syphon
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . .	Two unit
FRONT TIRES . . . .	34 x 4½ inches, rib cord	STARTER OPERATED .	Gear to fly wheel
REAR TIRES . . . .	34 x 4½ inches, rib cord	LIGHTING SYSTEM .	Electric
SERVICE BRAKE . . .	Contracting on rear wheels	VOLTAGES . . . . .	Six to eight
EMERGENCY BRAKE .	Expanding on rear wheels	WIRING SYSTEM . . .	Single
CYLINDERS . . . . .	Eight	GASOLINE SYSTEM .	Vacuum
HOW ARRANGED . . .	V-type	CLUTCH . . . . .	Dry plate
CAST . . . . .	Four en bloc	TRANSMISSION . . .	Selective sliding
HORSEPOWER . . . .	33.8 (N.A.C.C. Rating)	GEAR CHANGES . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . .	Worm and gear


In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, clock, tire pump, electric horn and demountable rims.

---

# **APPERSON BROTHERS AUTOMOBILE COMPANY**

**K O K O M O  
I N D I A N A**

Price . . . . .	\$4000
Four-Passenger Tourster . . . . .	4000
Four-Passenger Coupe . . . . .	5500
Seven-Passenger Sedan . . . . .	5500



## **APPERSON ANNIVERSARY MODEL—8**


COLOR . . . . .	Deep wine, gun-metal gray or electric blue	BORE AND STROKE . . . . .	3¼ x 5 inches
SEATING CAPACITY . . . . .	Seven	LUBRICATION . . . . .	Full force feed
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	130 inches	COOLING . . . . .	Thermo-syphon
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wire or disteel	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	34 x 4½ inches, rib cord	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	34 x 4½ inches, rib cord	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGES . . . . .	Six to eight
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Eight	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	V-type 90 degrees	CLUTCH . . . . .	Dry plate
CAST . . . . .	Four en bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	33.8	GEAR CHANGES . . . . .	Three forward, one reverse
(N.A.C.C. Rating)		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Three-quarter floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, clock, tire pump, electric horn and demountable rims.

# **REO MOTOR CAR COMPANY**

**LANSING  
MICHIGAN**

Price . . . . .	\$1650
Three-Passenger Roadster . . . . .	1650
Four-Passenger Coupe . . . . .	2400
Five-Passenger Sedan . . . . .	2500



## **REO TOURING—T-6**


COLOR . . . . .	Body, blue; running gear, white	BORE AND STROKE . . . . .	3 $\frac{1}{8}$ x 5 inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Force feed and splash
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Tubular
WHEELBASE . . . . .	120 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	33 x 4 inches, cord	STARTER OPERATED . . . . .	Chain to transmission shaft
REAR TIRES . . . . .	33 x 4 inches, cord, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	24.3 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Pinion and sector

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.

**NORDYKE &  
MARMON  
COMPANY**

**INDIANAPOLIS  
INDIANA**

Price . . . . .	\$4650
Four-Passenger Touring . . . . .	4650
Roadster . . . . .	4650
Four-Passenger Coupe . . . . .	5800
Seven-Passenger Sedan . . . . .	6250
Limousine . . . . .	6450
Town Car . . . . .	6450




---

**MARMON TOURING—34**

---

COLOR . . . . .	Body, blue; running gear, black	BORE AND STROKE . . . . .	3¼ x 5½ inches
SEATING CAPACITY . . . . .	Seven	LUBRICATION . . . . .	Full force feed
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	136 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wire	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	32 x 4½ inches, cord	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4½ inches, cord, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Gravity
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry plate, multiple disc
CAST . . . . .	In threes	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	33.75 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . . . .	Screw and nut


In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, clock, tire pump, electric horn, and extra wire wheel, without extra tire.

---

# H U P P MOTOR CAR CORPORATION

DETROIT  
MICHIGAN

Price, \$1450



## HUPMOBILE TOURING—R


COLOR . . . . .	Body, blue; running gear, black	LUBRICATION . . . .	Force feed and splash
SEATING CAPACITY .	Five	RADIATOR . . . . .	Cellular
POSITION OF DRIVER.	Left side	COOLING . . . . .	Thermo-syphon
WHEELBASE . . . .	112 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . . .	32 x 4 inches	LIGHTING SYSTEM .	Electric
REAR TIRES . . . .	32 x 4 inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . .	Contracting on rear wheel drum	WIRING SYSTEM . .	Single
EMERGENCY BRAKE .	Expanding in rear wheel drum	GASOLINE SYSTEM .	Vacuum
CYLINDERS . . . . .	Four	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . .	Vertically	TRANSMISSION . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . .	Three forward, one reverse
HORSEPOWER . . . .	16.9 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE .	3¼ x 5½ inches	REAR AXLE . . . .	Three-quarters floating
		STEERING GEAR . .	Screw and nut

In addition to above specifications, price includes top, top hood, windshield speedometer, ammeter, tire pump, electric horn and demountable rims.

# H U P P MOTOR CAR CORPORATION

DETROIT  
MICHIGAN

Price, \$1450



## HUPMOBILE ROADSTER—R


COLOR . . . . .	Body, blue; running gear, black	LUBRICATION . . . . .	Force feed and splash
SEATING CAPACITY . .	Two	RADIATOR . . . . .	Cellular
POSITION OF DRIVER .	Left side	COOLING . . . . .	Thermo-syphon
WHEELBASE . . . . .	112 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . . . .	32 x 4 inches	LIGHTING SYSTEM . .	Electric
REAR TIRES . . . . .	32 x 4 inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . .	Contracting on rear wheel drum	WIRING SYSTEM . . .	Single
EMERGENCY BRAKE . .	Expanding in rear wheel drum	GASOLINE SYSTEM . .	Vacuum
CYLINDERS . . . . .	Four	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . . .	Vertically	TRANSMISSION . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . .	Three forward, one reverse
HORSEPOWER . . . . .	16.9 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . .	3¼ x 5½ inches	REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . .	Screw and nut

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.

# H U P P MOTOR CAR CORPORATION

DETROIT  
MICHIGAN

Price, \$1450




## HUPMOBILE TOURING—R

COLOR . . . . .	Body, blue; running gear, black	LUBRICATION . . . . .	Force feed and splash
SEATING CAPACITY . . . . .	Five	RADIATOR . . . . .	Cellular
POSITION OF DRIVER. . . . .	Left side	COOLING . . . . .	Thermo-syphon
WHEELBASE . . . . .	112 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	32 x 4 inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	32 x 4 inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheel drum	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding in rear wheel drum	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Four	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	16.9 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3¼ x 5½ inches	REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . . . .	Screw and nut

In addition to above specifications, price includes top, top hood, windshield speedometer, ammeter, tire pump, electric horn and demountable rims.






---

**HUPMOBILE ROADSTER—R**


---

COLOR . . . . .	Body, blue; running gear, black	LUBRICATION . . . . .	Force feed and splash
SEATING CAPACITY . . . . .	Two	RADIATOR . . . . .	Cellular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Thermo-syphon
WHEELBASE . . . . .	112 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	32 x 4 inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	32 x 4 inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheel drum	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding in rear wheel drum	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Four	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	16.9 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3¼ x 5½ inches	REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . . . .	Screw and nut

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.

**H U P P  
MOTOR CAR  
CORPORATION**  
**D E T R O I T  
M I C H I G A N**

**Price, \$2185**



**HUPMOBILE COUPE—R**


COLOR . . . . .	Lower body, blue; upper body, hood fenders and run- ning gear, black	BORE AND STROKE . . . . .	3 3/4 x 5 1/2 inches
SEATING CAPACITY . . . . .	Four	LUBRICATION . . . . .	Force feed and splash
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	112 inches	COOLING . . . . .	Thermo-syphon
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	32 x 4 inches	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4 inches, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheel drum	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding in rear wheel drum	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Four	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	16.9 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . . . .	Screw and nut

In addition to above specifications, price includes speedometer, ammeter, tire pump, electric horn, windshield wiper and demountable rims.

# H U P P MOTOR CAR CORPORATION

DETROIT  
MICHIGAN

Price, \$2185



## HUPMOBILE SEDAN—R


COLOR . . . . .	Lower body, blue; upper body, hood, fenders and running gear, black	BORE AND STROKE . . . . .	3¼ x 5½ inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Force feed and splash
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	112 inches	COOLING . . . . .	Thermo-syphon
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	32 x 4 inches	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4 inches, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheel drum	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding in rear wheel drum	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Four	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	16.9 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . . . .	Screw and nut

In addition to above specifications, price includes speedometer, ammeter, tire pump, electric horn and demountable rims.

**R O O T &  
VAN DERVOORT  
ENGINEERING  
C O M P A N Y**

**EAST MOLINE  
ILLINOIS**

Price . . . . .	\$3700
Two-Passenger Roadster . . . . .	3150
Four-Passenger Sport . . . . .	3150
Seven-Passenger Touring . . . . .	3150
Seven-Passenger Sedan . . . . .	3800



**R & V-KNIGHT COUPE—J**

COLOR . . . . .	Dark blue	LUBRICATION . . . . .	Force feed and splash
SEATING CAPACITY . . . . .	Four	RADIATOR . . . . .	Tubular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Thermo-syphon
WHEELBASE . . . . .	127 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	32x4½ inches, cord	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	32x4½ inches, cord, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	29.4 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3½ x 4½ inches	REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Screw and nut


In addition to above specifications, price includes windshield, speedometer, ammeter, voltmeter, motometer, tire pump, electric horn and demountable rims.

**J O N E S  
M O T O R C A R  
C O M P A N Y**  

---

**W I C H I T A  
K A N S A S**

Price . . . . .	\$2350
Two-Passenger Roadster . . . . .	2250
Five-Passenger Touring . . . . .	2250
Seven-Passenger Touring . . . . .	2250
Seven-Passenger Victoria . . . . .	2350
Oil Field Special . . . . .	2000




---

**JONES SIX SPEEDSTER TYPE—28-E**


---

COLOR . . . . .	Body, maroon; running gear, black	LUBRICATION . . . . .	Force feed and splash
SEATING CAPACITY . . . . .	Four	RADIATOR . . . . .	Cellular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Centrifugal pump
WHEELBASE . . . . .	126 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wire	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	32 x 4½ inches, rib cord	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	32 x 4½ inches, cord, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry plate disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	29.4 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3½ x 5¼ inches	REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, tire pump, electric horn and demountable rims.

**CHANDLER  
MOTORCAR  
COMPANY**  
CLEVELAND, OHIO

Price . . . . .	\$1895
Four-Passenger Dispatch Car . . . . .	1975
Four-Passenger Roadster . . . . .	1895
Four-Passenger Coupe . . . . .	2795
Seven-Passenger Sedan . . . . .	2895
Seven-Passenger Limousine . . . . .	3395




**CHANDLER TOURING**

COLOR . . . . .	Body, Chandler blue; running gear, black	LUBRICATION . . . . .	Splash with circulating pump
SEATING CAPACITY . . . . .	Seven	RADIATOR . . . . .	Cellular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	123 inches	IGNITION . . . . .	High tension magneto
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	33 x 4 inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	33 x 4 inches, anti-skid	VOLTAGES . . . . .	Six to eight
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry plate
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	In threes	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	29.4 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3½ x 5 inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, hand tire pump, electric horn and demountable rims.

**CHANDLER  
MOTOR CAR  
COMPANY**  
CLEVELAND, OHIO

Price . . . . .	\$2895
Four-Passenger Dispatch Car . . .	1975
Four-Passenger Roadster . . . . .	1895
Seven-Passenger Touring . . . . .	1895
Four-Passenger Coupe . . . . .	2795
Seven-Passenger Limousine . . . .	3395



**CHANDLER SEDAN**


COLOR . . . . .	Body, Chandler blue; running gear, black	BORE AND STROKE . . .	3 3/4 x 5 inches
SEATING CAPACITY . .	Seven	LUBRICATION . . . . .	Splash with circulating pump
POSITION OF DRIVER .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	123 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	High tension magneto
WHEELS . . . . .	Wood	STARTING SYSTEM . . .	Two unit
FRONT TIRES . . . . .	34 x 4 1/2 inches	STARTER OPERATED . .	Gear to fly wheel
REAR TIRES . . . . .	34 x 4 1/2 inches, anti-skid	LIGHTING SYSTEM . . .	Electric
SERVICE BRAKE . . . .	Contracting on rear wheels	VOLTAGES . . . . .	Six to eight
EMERGENCY BRAKE . . .	Expanding on rear wheels	WIRING SYSTEM . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . .	Vacuum
HOW ARRANGED . . . .	Vertically	CLUTCH . . . . .	Dry plate
CAST . . . . .	In threes	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	29.4 (N.A.C.C. Rating)	GEAR CHANGES . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes windshield, speedometer, hand tire pump, electric horn and demountable rims.

**STUTZ MOTOR  
CAR COMPANY  
OF AMERICA,  
INCORPORATED**

**INDIANAPOLIS  
I N D I A N A**

**Four-Passenger Close Coupled } Prices Upon  
Two-Passenger Roadster . . . } Application**




---

**STUTZ SIX-PASSENGER TOURING—SERIES H**

---

COLOR . . . . .	Blue or gray	LUBRICATION . . . .	Force feed and splash
SEATING CAPACITY .	Six	RADIATOR . . . . .	Cellular
POSITION OF DRIVER	Right side	COOLING . . . . .	Water pump
WHEELBASE . . . .	130 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . .	Two unit
WHEELS . . . . .	Wire	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . . .	32 x 4½ inches, cord	LIGHTING SYSTEM . .	Electric
REAR TIRES . . . .	32 x 4½ inches, cord	VOLTAGE . . . . .	Six
SERVICE BRAKE . . .	Expanding on rear wheels	WIRING SYSTEM . . .	Double
EMERGENCY BRAKE .	Expanding on rear wheels	GASOLINE SYSTEM . .	Pressure
CYLINDERS . . . . .	Four—16 valve	CLUTCH . . . . .	Cone
HOW ARRANGED . . .	Vertically	TRANSMISSION . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . .	Three forward, one reverse
HORSEPOWER . . . .	30.63 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE .	4¾ x 6 inches	REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . .	Worm and gear


In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, electric horn, motometer, spotlight and shock absorbers.

---



**STUTZ MOTOR  
CAR COMPANY  
OF AMERICA,  
INCORPORATED**  
**INDIANAPOLIS  
I N D I A N A**

**Price Upon Application**




---

**STUTZ BEARCAT—SERIES H**

---

COLOR . . . . .	Red, gray or yellow	BORE AND STROKE . .	4½ x 6 inches
SEATING CAPACITY .	Two	LUBRICATION . . . .	Force feed and splash
POSITION OF DRIVER	Right side	RADIATOR . . . . .	Cellular
WHEELBASE . . . .	120 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wire	STARTING SYSTEM . .	Two unit
FRONT TIRES . . . .	32 x 4½ inches, cord	STARTER OPERATED .	Gear to fly wheel
REAR TIRES . . . .	32 x 4½ inches, cord	LIGHTING SYSTEM . .	Electric
SERVICE BRAKE . .	Expanding on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE .	Expanding on rear wheels	WIRING SYSTEM . .	Double
CYLINDERS . . . . .	Four—16 valves	GASOLINE SYSTEM . .	Pressure
HOW ARRANGED . .	Vertically	CLUTCH . . . . .	Cone
CAST . . . . .	En bloc	TRANSMISSION . . .	Selective sliding
HORSEPOWER . . . .	30.63 (N.A.C.C. Rating)	GEAR CHANGES . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . .	Three-quarters floating
		STEERING GEAR . .	Worm and gear


In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, electric horn, motometer, spotlight and shock absorbers.

---

**THE LEWIS  
SPRING & AXLE  
COMPANY**

**C H E L S E A  
M I C H I G A N**

**Price, \$1985**




---

**HOLLIER SIX TOURING—206-B**

---

COLOR . . . . .	Body, light blue, running gear, black	BORE AND STROKE . . . . .	3¼ x 4½ inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Force feed and splash
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	120 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	33 x 4 inches, anti-skid	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	33 x 4 inches, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	25.35 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and gear


In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, clock, hand tire pump, electric horn and demountable rims.

---

# SIMPLEX AUTOMOBILE COMPANY

Price, Chassis, \$7000

12th STREET AND  
VERNON AVENUE,  
LONG ISLAND CITY,  
NEW YORK




## SIMPLEX-CRANE LIMOUSINE—5

COLOR . . . . .	Optional	LUBRICATION . . . . .	Force feed
SEATING CAPACITY . . . . .	Seven	RADIATOR . . . . .	Cellular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	143½ inches	IGNITION . . . . .	High tension magneto and storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wire or wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	35 x 5 inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	35 x 5 inches	VOLTAGE . . . . .	Twelve
SERVICE BRAKE . . . . .	Contracting on drive shaft	WIRING SYSTEM . . . . .	Double
EMERGENCY BRAKE . . . . .	Contracting on rear wheels	GASOLINE SYSTEM . . . . .	Pressure
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Single plate in oil
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	In threes	GEAR CHANGES . . . . .	Four forward, one reverse
HORSEPOWER . . . . .	45.94 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	4¾ x 6¼ inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and sector

In addition to above specifications, price includes speedometer, ammeter, voltmeter, clock, tire pump, electric horn and demountable rims.

**SCRIPPS -  
BOOTH  
CORPORATION**  
**DETROIT  
MICHIGAN**

Price . . . . .	\$1425
Three-Passenger Roadster . . . . .	1425
Four-Passenger Sportster . . . . .	1425
Four-Passenger Coupe . . . . .	2095
Five-Passenger Sedan . . . . .	2175




---

**SCRIPPS-BOOTH TOURING—B-39**

---


COLOR . . . . .	Body, blue or maroon; running gear, black	BORE AND STROKE . . . . .	2 $\frac{1}{8}$ x 4 $\frac{3}{4}$ inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Force feed
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	115 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	32 x 4 inches	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4 inches, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGES . . . . .	Six to eight
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Cone
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	18.98 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Plain bevel
		REAR AXLE . . . . .	Floating, single bearing
		STEERING GEAR . . . . .	Screw and nut

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.

---

**SCRIPPS -  
BOOTH  
CORPORATION**  
**DETROIT  
MICHIGAN**

Price . . . . .	\$2095
Five-Passenger Touring Car . .	1425
Three-Passenger Roadster . . .	1425
Four-Passenger Sportster . . .	1425
Five-Passenger Sedan . . . . .	2175




---

**SCRIPPS-BOOTH COUPE—B-42**

---


COLOR . . . . .	Body, blue or maroon; running gear, black	BORE AND STROKE . .	2½ x 4¾ inches
SEATING CAPACITY .	Four	LUBRICATION . . . .	Force feed
POSITION OF DRIVER	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . .	115 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . .	Two unit
FRONT TIRES . . . .	32 x 4 inches	STARTER OPERATED .	Gear to fly wheel
REAR TIRES . . . .	32 x 4 inches, anti-skid	LIGHTING SYSTEM . .	Electric
SERVICE BRAKE . .	Contracting on rear wheels	VOLTAGES . . . . .	Six to eight
EMERGENCY BRAKE .	Expanding on rear wheels	WIRING SYSTEM . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . .	Vacuum
HOW ARRANGED . .	Vertically	CLUTCH . . . . .	Cone
CAST . . . . .	En bloc	TRANSMISSION . . .	Selective sliding
HORSEPOWER . . . .	18.98 (N.A.C.C. Rating)	GEAR CHANGES . . .	Three forward, one reverse
		DRIVE . . . . .	Plain bevel
		REAR AXLE . . . . .	Floating, single bearing
		STEERING GEAR . . .	Screw and nut

In addition to above specifications, price includes windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.

---

**LORRAINE  
MOTORS  
CORPORATION**  
**GRAND RAPIDS  
MICHIGAN**

**Price, \$1425**




---

**LORRAINE TOURING**

---

COLOR . . . . .	Body, light blue; running gear, black	BORE AND STROKE . .	3 1/2 x 5 inches
SEATING CAPACITY .	Five	LUBRICATION . . . .	Full splash
POSITION OF DRIVER	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . .	114 inches	COOLING . . . . .	Thermo-syphon
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . .	Two unit
FRONT TIRES . . . .	32 x 4 inches	STARTER OPERATED .	Gear to fly wheel
REAR TIRES . . . .	32 x 4 inches, anti-skid	LIGHTING SYSTEM . .	Electric
SERVICE BRAKE . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE .	Expanding on rear wheels	WIRING SYSTEM . . .	Single
CYLINDERS . . . . .	Four	GASOLINE SYSTEM . .	Vacuum
HOW ARRANGED . .	Vertically	CLUTCH . . . . .	Dry plate
CAST . . . . .	En bloc	TRANSMISSION . . .	Selective sliding
HORSEPOWER . . . .	19.6 (N.A.C.C. Rating)	GEAR CHANGES . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . .	Worm and gear


In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.

---

# K I N G MOTOR CAR C O M P A N Y

D E T R O I T  
M I C H I G A N

Price . . . . .	\$2585
Foursome . . . .	2585
Road-King . . . .	2600
Limoudan . . . .	3985




## KING "8" TOURING—H

COLOR . . . . .	Body, King blue and Coach Painter's green; running gear, black	HORSEPOWER . . . .	28.8 (N.A.C.C. Rating)
SEATING CAPACITY .	Seven	BORE AND STROKE .	3 x 5 inches
POSITION OF DRIVER	Left side	LUBRICATION . . . .	Force feed
WHEELBASE . . . .	120 inches	RADIATOR . . . . .	Cellular
GAUGE . . . . .	56 inches	COOLING . . . . .	Thermo-syphon
WHEELS . . . . .	Wood	IGNITION . . . . .	Storage battery
FRONT TIRES . . . .	32 x 4½ inches, rib cord	STARTING SYSTEM . .	Two unit
REAR TIRES . . . .	32 x 4½ inches, cord, anti-skid	STARTER OPERATED .	Gear to fly wheel
SERVICE BRAKE . .	Contracting on rear wheels	LIGHTING SYSTEM . .	Electric
EMERGENCY BRAKE .	Expanding on rear wheels	VOLTAGE . . . . .	Six
CYLINDERS . . . .	Eight	WIRING SYSTEM . . .	Single
HOW ARRANGED . .	V type, 90 degrees	GASOLINE SYSTEM . .	Vacuum
CAST . . . . .	Four en bloc	CLUTCH . . . . .	Dry plate
		TRANSMISSION . . .	Selective sliding
		GEAR CHANGES . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . .	Full floating
		STEERING GEAR . . .	Screw and nut

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, clock, motometer, power tire pump, electric horn and demountable rims.

**JORDAN  
MOTOR CAR  
COMPANY  
INCORPORATED**  
CLEVELAND, OHIO

Playboy . . . . .	} Prices Upon Appli- cation
Silhouette Brougham . . . . .	
Silhouette Sedan . . . . .	




---

**JORDAN SILHOUETTE FIVE TOURING**

---


COLOR . . . . .	Body, Brewster green; running gear black	BORE AND STROKE . . . . .	3 1/4 x 4 1/2 inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Force feed and splash
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	120 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Single unit
FRONT TIRES . . . . .	32 x 4 inches	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	32 x 4 inches, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry plate
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	25.35 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, clock, tire pump, electric horn and demountable rims.



**LEXINGTON  
MOTOR  
COMPANY**  
CONNERSVILLE  
INDIANA

Price . . . . .	\$1885
Thorobred . . . .	1885
Lex-Sedan . . . .	2285
Coupe . . . . .	2850
Sedanette . . . .	2850




---

**LEXINGTON TOURING—SERIES "S"**

---

COLOR . . . . .	Body, forest green; running gear, black	LUBRICATION . . . .	Force feed
SEATING CAPACITY .	Five	RADIATOR . . . . .	Cellular
POSITION OF DRIVER	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . .	122 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED	Gear to fly wheel
FRONT TIRES . . . .	32 x 4 inches, cord	LIGHTING SYSTEM . .	Electric
REAR TIRES . . . .	32 x 4 inches, cord	VOLTAGE . . . . .	Six
SERVICE BRAKE . . .	Contracting on rear wheels	WIRING SYSTEM . . .	Single
EMERGENCY BRAKE .	Contracting on propeller shaft	GASOLINE SYSTEM . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry disc
HOW ARRANGED . . .	Vertically	TRANSMISSION . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . .	Three forward, one reverse
HORSEPOWER . . . .	25.4 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . .	3¼ x 4½ inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . .	Worm and gear


In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, motometer, tire pump, electric horn, cord tires and demountable rims.

---

**C R O W -  
E L K H A R T  
M O T O R  
C O R P O R A T I O N**

**E L K H A R T  
I N D I A N A**

**Price . . . . . \$1295**  
**Three-Passenger Roadster—L-53 1295**  
**Four-Passenger Sport Model—**  
**L-54 . . . . . 1445**



**CROW-ELKHART TOURING—L-55**


<b>COLOR . . . . .</b>	Optional	<b>BORE AND STROKE . . . . .</b>	3½ x 5 inches
<b>SEATING CAPACITY . . . . .</b>	Five	<b>LUBRICATION . . . . .</b>	Full splash
<b>POSITION OF DRIVER. . . . .</b>	Left side	<b>RADIATOR . . . . .</b>	Cellular
<b>WHEELBASE . . . . .</b>	117 inches	<b>COOLING . . . . .</b>	Thermo-syphon
<b>GAUGE . . . . .</b>	56 inches	<b>IGNITION . . . . .</b>	Storage battery
<b>WHEELS . . . . .</b>	Wire or wood	<b>STARTING SYSTEM . . . . .</b>	Two unit
<b>FRONT TIRES . . . . .</b>	32 x 3½ inches	<b>STARTER OPERATED . . . . .</b>	Gear to fly wheel
<b>REAR TIRES . . . . .</b>	32 x 3½ inches, anti-skid	<b>LIGHTING SYSTEM . . . . .</b>	Electric
<b>SERVICE BRAKE . . . . .</b>	Contracting on rear wheels	<b>VOLTAGE . . . . .</b>	Six
<b>EMERGENCY BRAKE . . . . .</b>	Expanding on rear wheels	<b>WIRING SYSTEM . . . . .</b>	Single
<b>CYLINDERS . . . . .</b>	Four	<b>GASOLINE SYSTEM . . . . .</b>	Vacuum
<b>HOW ARRANGED . . . . .</b>	Vertically	<b>CLUTCH . . . . .</b>	Dry plate, multiple disc
<b>CAST . . . . .</b>	En bloc	<b>TRANSMISSION . . . . .</b>	Selective sliding
<b>HORSEPOWER . . . . .</b>	19.6 (N.A.C.C. Rating)	<b>GEAR CHANGES . . . . .</b>	Three forward, one reverse
		<b>DRIVE . . . . .</b>	Plain bevel
		<b>REAR AXLE . . . . .</b>	Full floating
		<b>STEERING GEAR . . . . .</b>	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.

**C R O W -  
E L K H A R T  
M O T O R  
C O R P O R A T I O N**

**E L K H A R T  
I N D I A N A**

Price . . . . .	\$2395
Three-Passenger Roadster—H-53	1545
Five-Passenger Touring—H-55	1545
Four-Passenger Sport Model— H-54 . . . . .	1695




---

**CROW-ELKHART SEDAN—H-57**

---

COLOR . . . . .	Black	LUBRICATION . . . . .	Splash with circulating pump
SEATING CAPACITY . . . . .	Seven	RADIATOR . . . . .	Cellular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	117 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wire or wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	33 x 4 inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	33 x 4 inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry plate, multiple disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	23.4 (N.A.C.C. Rating)	DRIVE . . . . .	Plain bevel
BORE AND STROKE . . . . .	3½ x 5 inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and gear


In addition to above specifications, price includes windshield, speedometer, ammeter, clock, tire pump, electric horn and demountable rims.

---

**PAIGE-DETROIT  
MOTOR CAR  
COMPANY**

**DETROIT  
MICHIGAN**

**Price Upon Application**




---

**PAIGE GLENBROOK TOURING**

---


COLOR . . . . .	Dark green	LUBRICATION . . . .	Pressure feed and splash
SEATING CAPACITY .	Five	RADIATOR . . . . .	Cellular
POSITION OF DRIVER	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . .	119 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . . .	32 x 4 inches	LIGHTING SYSTEM . .	Electric
REAR TIRES . . . .	32 x 4 inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . .	Contracting on rear wheels	WIRING SYSTEM . .	Single
EMERGENCY BRAKE .	Expanding on rear wheels	GASOLINE SYSTEM .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Three plate
HOW ARRANGED . .	Vertically	TRANSMISSION . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . .	Three forward, one reverse
HORSEPOWER . . . .	23.44 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE .	3½ x 5 inches	REAR AXLE . . . .	Three-quarters floating
		STEERING GEAR . .	Screw and nut

In addition to above specifications, price includes top, top hood, wind-shield, speedometer, ammeter, electric horn and demountable rims.

**PAIGE-DETROIT  
MOTOR CAR  
COMPANY**

**DETROIT  
MICHIGAN**

**Price Upon Application**




---

**PAIGE LARCHMONT SPORT—6-55**

---


COLOR . . . . .	Bluish green or Quaker brown, optional	LUBRICATION . . . . .	Pressure feed and splash
SEATING CAPACITY . . . . .	Four or five	RADIATOR . . . . .	Cellular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	127 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	33 x 4½ inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	33 x 4½ inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Three plate
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	29.40	DRIVE . . . . .	Spiral bevel
(N.A.C.C. Rating)		REAR AXLE . . . . .	Three-quarters floating
BORE AND STROKE . . . . .	3½ x 5½ inches	STEERING GEAR . . . . .	Screw and nut

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.

---

**F. B. STEARNS  
C O M P A N Y**  
CLEVELAND, OHIO

Price . . . . .	\$3450
Three-Passenger Roadster . . . . .	2350
Five-Passenger Touring . . . . .	2350
Four-Passenger Militaire . . . . .	2375
Seven-Passenger Touring . . . . .	2575
Coupe . . . . .	3150
Limousine . . . . .	4000
Limousine Brougham . . . . .	4150



**STEARNS-KNIGHT SEDAN**


COLOR . . . . .	Body, blue or maroon; running gear, black	BORE AND STROKE . . . . .	3 3/4 x 5 1/2 inches
SEATING CAPACITY . . . . .	Seven	LUBRICATION . . . . .	Full force feed
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	125 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 1/2 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	34 x 4 1/2 inches	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	34 x 4 1/2 inches, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Twelve
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Four	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	22.5 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes windshield, speedometer, ammeter, voltmeter, clock, tire pump, electric horn and demountable rims.

# DORRIS MOTORCAR COMPANY

ST. LOUIS  
MISSOURI

Price . . . . .	\$4350
Four-Passenger Touring . . . . .	4350
Coupe . . . . .	5280
Sedan . . . . .	5720
Chassis Only . . . . .	3430



## DORRIS TOURING—6-80


COLOR . . . . .	Cobalt blue	BORE AND STROKE . . . . .	4 x 5 inches
SEATING CAPACITY . . . . .	Seven	LUBRICATION . . . . .	Full force feed
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Tubular
WHEELBASE . . . . .	132 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	High tension magneto
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	33 x 5 inches, cord	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	33 x 5 inches, cord, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	Three en bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	38.4 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Screw and nut

In addition to above specifications, price includes top, windshield, speedometer, ammeter, voltmeter, clock, tire pump, electric horn, complete set of tools and demountable rims.

# JACKSON MOTORS CORPORATION

JACKSON  
MICHIGAN

Price . . . . . \$1885  
Sport . . . . . 2500  
Sedan . . . . . 2850



## JACKSON TOURING—6-38

COLOR . . . . .	Body, blue; running gear, black	LUBRICATION . . . . .	Force feed and splash
SEATING CAPACITY . . . . .	Five	RADIATOR . . . . .	Tubular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	121 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	33 x 4 inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	33 x 4 inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear axle	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Contracting on transmission	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry plate, multiple disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	25.35 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3 1/4 x 4 1/2 inches	REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.




**W. A. PATERSON  
C O M P A N Y**  

---

**F L I N T  
M I C H I G A N**

Price . . . . .	\$1695
Four-Passenger Roadster . . . . .	1725
Seven-Passenger Touring . . . . .	1725
Seven-Passenger Sedan . . . . .	2600




---

**PATERSON TOURING—6-46**


---

COLOR . . . . .	Body, blue; running gear, black	LUBRICATION . . . . .	Force feed and splash
SEATING CAPACITY . . . . .	Five	RADIATOR . . . . .	Tubular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	120 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	33 x 4 inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	33 x 4 inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Double
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	25.35 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3¼ x 4½ inches	REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and nut

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.

**SAYERS &  
SCOVILL  
COMPANY**  
CINCINNATI, OHIO

Price . . . . .	\$1765
Two- or Three-Passenger Roadster . . . . .	1765
Five-Passenger Sedan . . . . .	2795
Five-Passenger Limousine . . . . .	2795



**SAYERS SIX TOURING—A**


COLOR . . . . .	Body, blue; running gear, black	BORE AND STROKE . . . . .	3¼ x 4¼ inches
SEATING CAPACITY . . . . .	Five	LUBRICATION . . . . .	Force feed and splash
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	118 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	33 x 4 inches	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	33 x 4 inches, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Six	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Three plate
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	25.35 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.

# CADILLAC MOTOR CAR COMPANY

DETROIT  
MICHIGAN

Suburban . . . . .	} Prices Upon Appli- cation
Limousine . . . . .	
Imperial Limousine . . . . .	
Town Brougham . . . . .	



## CADILLAC TOURING—59


COLOR . . . . .	Cadillac blue	LUBRICATION . . . . .	Force feed
SEATING CAPACITY . . . . .	Seven	RADIATOR . . . . .	Tubular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	132 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Single unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	35 x 5 inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	35 x 5 inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Pressure
CYLINDERS . . . . .	Eight	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . . . . .	V type, 90 degrees	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	Four en bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	31.25 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3½ x 5½ inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and sector

In addition to above specifications, price includes top, windshield, speedometer, ammeter, clock, tire pump, electric horn and demountable rims.

# CADILLAC MOTOR CAR COMPANY

DETROIT  
MICHIGAN

Two-Passenger Roadster . . . } Prices  
Two-Passenger Coupe . . . } Upon  
Four-Passenger Sedan . . . } Appli-  
Four-Passenger Phaeton . . . } cation



## CADILLAC VICTORIA—59


COLOR . . . . .	Cadillac blue	LUBRICATION . . . .	Force feed
SEATING CAPACITY .	Four	RADIATOR . . . . .	Tubular
POSITION OF DRIVER	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . .	125 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . .	Single unit
WHEELS . . . . .	Wood	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . . .	34 x 4½ inches	LIGHTING SYSTEM . .	Electric
REAR TIRES . . . .	34 x 4½ inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . .	Contracting on rear wheels	WIRING SYSTEM . . .	Single
EMERGENCY BRAKE .	Expanding on rear wheels	GASOLINE SYSTEM . .	Pressure
CYLINDERS . . . . .	Eight	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . . .	V type, 90 degrees	TRANSMISSION . . . .	Selective sliding
CAST . . . . .	Four en bloc	GEAR CHANGES . . .	Three forward, one reverse
HORSEPOWER . . . .	31.25 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE .	3½ x 5½ inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . .	Worm and sector

In addition to above specifications, price includes speedometer, ammeter, clock, tire pump, electric horn and demountable rims.

# CADILLAC MOTORCAR COMPANY

DETROIT  
MICHIGAN

Suburban . . . . .	} Prices Upon Appli- cation
Imperial Limousine . . . . .	
Town Brougham . . . . .	
Seven-Passenger Touring . . . . .	



## CADILLAC LIMOUSINE—59


COLOR . . . . .	Cadillac blue	LUBRICATION . . . . .	Force feed
SEATING CAPACITY . . . . .	Seven	RADIATOR . . . . .	Tubular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	132 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Single unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	35 x 5 inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	35 x 5 inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Pressure
CYLINDERS . . . . .	Eight	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . . . . .	V type, 90 degrees	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	Four en bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	31.25 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3½ x 5½ inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and sector

In addition to above specifications, price includes speedometer, ammeter, clock, tire pump, electric horn and demountable rims.

**F I A T**

**501 FIFTH AVENUE  
NEW YORK CITY**

**Touring . . . } Prices  
Landaulet . . . } Upon  
Limousine . . . } Appli-  
Brougham . . . } cation  
Sedan . . . }**



### FIAT BROUGHAM—TYPE 505


COLOR . . . . .	Blue, red or gray	BORE AND STROKE . .	3 x 5½ inches
SEATING CAPACITY .	Six	LUBRICATION . . . .	Force feed
POSITION OF DRIVER.	Right side	RADIATOR . . . . .	Cellular
WHEELBASE . . . .	122 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	High tension magneto
WHEELS . . . . .	Pressed steel	STARTING SYSTEM . .	Two unit
FRONT TIRES . . . .	32 x 4½ inches	STARTER OPERATED .	Gear to fly wheel
REAR TIRES . . . .	32 x 4½ inches, anti-skid	LIGHTING SYSTEM . .	Electric
SERVICE BRAKE . .	Contracting on rear wheels	VOLTAGE . . . . .	Twelve
EMERGENCY BRAKE .	Expanding on rear wheels	WIRING SYSTEM . . .	Double
CYLINDERS . . . . .	Four	GASOLINE SYSTEM . .	Pressure
HOW ARRANGED . .	Vertically	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	En bloc	TRANSMISSION . . .	Selective sliding
HORSEPOWER . . . .	14.4 (N.A.C.C. Rating)	GEAR CHANGES . .	Four forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, clock, tire pump, electric horn and spare wheel.

**F I A T**

**501 FIFTH AVENUE  
NEW YORK CITY**

**Touring . . . } Prices  
Roadster . . . } Upon  
Sedan . . . } Appli-  
Coupe . . . } cation**




---

### FIAT TOURING—TYPE 501

---


COLOR . . . . .	Blue, dark red or gray	LUBRICATION . . . . .	Force feed
SEATING CAPACITY . . . . .	Four	RADIATOR . . . . .	Cellular
POSITION OF DRIVER. . . . .	Right side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	106 inches	IGNITION . . . . .	High tension magneto and storage battery
GAUGE . . . . .	50 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Pressed steel	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	30 x 3½ inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	30 x 3½ inches, anti-skid	VOLTAGE . . . . .	Twelve
SERVICE BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Double
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Gravity
CYLINDERS . . . . .	Four	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Four forward, one reverse
HORSEPOWER . . . . .	10.5 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	2⅞ x 4⅞ inches	REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, clock, tire pump, electric horn and spare wheel.

**B A R L E Y  
M O T O R C A R  
C O M P A N Y**

**K A L A M A Z O O  
M I C H I G A N**

Price. . . . .	\$3850
Seven-Passenger Suburban Sedan . . .	4150
Three-Passenger Cabriolet . . .	3550
Four-Passenger Coupe . . . . .	3750
Five-Passenger Limousine . . . . .	3950
Five-Passenger Landaulet . . . . .	4150




---

**ROAMER SEDAN—C-6-54, SERIES E**

---

COLOR . . . . .	Optional	LUBRICATION . . . . .	Force feed and splash
SEATING CAPACITY . . .	Five	RADIATOR . . . . .	Cellular
POSITION OF DRIVER. . .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	128¼ inches	IGNITION . . . . .	High tension magneto and storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wire	STARTER OPERATED . . .	Gear to fly wheel
FRONT TIRES . . . . .	32 x 4½ inches, anti-skid	LIGHTING SYSTEM . . .	Electric
REAR TIRES . . . . .	32 x 4½ inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . .	Expanding on rear wheels	GASOLINE SYSTEM . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . .	Three forward, one reverse
HORSEPOWER . . . . .	29 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . .	3½ x 5½ inches	REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . . . .	Screw and nut


In addition to above specifications, price includes windshield, speedometer, ammeter, voltmeter, clock, tire pump, electric horn and extra wire wheel.



# BARLEY MOTOR CAR COMPANY

KALAMAZOO  
MICHIGAN

Price . . . . .	\$2750
Four-Passenger Sport . . . . .	2875
Two- or Four-Passenger Roadster . . . . .	2875
Two-Passenger Roadster . . . . .	2850
Seven-Passenger Touring . . . . .	2950



## ROAMER TOURING—C-6-54, SERIES E

COLOR . . . . .	Optional	LUBRICATION . . . . .	Force feed and splash
SEATING CAPACITY . . . . .	Four	RADIATOR . . . . .	Cellular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	128¼ inches	IGNITION . . . . .	High tension magneto and storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wire	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	32 x 4½ inches, anti-skid	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	32 x 4½ inches, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Six	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	29 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3½ x 5¼ inches	REAR AXLE . . . . .	Three-quarters floating
		STEERING GEAR . . . . .	Screw and nut

In addition to above specifications, price includes top, top hood, windshield, speedometer, ammeter, voltmeter, clock, tire pump, electric horn and extra wire wheel.



ILLUSTRATIONS AND  
SPECIFICATIONS  
**ELECTRIC**  
**VEHICLES**


---



**DETROIT  
ELECTRIC CAR  
COMPANY**

**DETROIT  
MICHIGAN**

**Price . . . . . \$3300**  
**Four-Passenger Coupe . . . . . 3200**




---

**DETROIT ELECTRIC BROUGHAM—81**

---


<b>COLOR . . . . .</b>	Body, blue or green; running gear, black	<b>BRAKE SYSTEMS . .</b>	Service brakes: Expanding on rear wheels Emergency brake: Contracting on motor
<b>SEATING CAPACITY .</b>	Five		
<b>BODY:</b>			
<b>LENGTH OVER ALL .</b>	144 inches	<b>BATTERY . . . . .</b>	42 cells, 15 plates
<b>WIDTH OVER ALL .</b>	68 inches	<b>SPEED . . . . .</b>	23½ miles per hour
<b>WHEELBASE . . . . .</b>	100 inches	<b>NO. FORWARD SPEEDS</b>	Five
<b>GAUGE . . . . .</b>	56 inches	<b>NO. REVERSE SPEEDS</b>	Five
<b>WHEELS . . . . .</b>	Wire or wood	<b>CONTROL . . . . .</b>	Horizontal lever operated
<b>FRONT TIRES . . . . .</b>	32 x 4½ inches, pneumatic	<b>STEERING . . . . .</b>	Lever
<b>REAR TIRES . . . . .</b>	32 x 4½ inches, pneumatic, anti-skid		

---

# BAKER R & L C O M P A N Y

CLEVELAND, OHIO

Price . . . . . \$4000  
Brougham, Single Rear Drive . . 3700



## RAULANG DOUBLE-DRIVE COACH—C-45


COLOR . . . . .	Optional	BRAKE SYSTEMS. . .	Service brake: Expanding on rear wheels Emergency brake: Mechanical contracting
SEATING CAPACITY .	Five	BATTERY . . . . .	42-15 WTX1 Phil- adelphia or 42-13 MV Special thin Exide
BODY:		SPEED . . . . .	25 miles per hour
LENGTH OVER ALL	142 inches	NO. FORWARD SPEEDS	Six
WIDTH OVER ALL	67 inches	NO. REVERSE SPEEDS	Four
WHEELBASE . . . . .	102 inches	CONTROL . . . . .	Side lever operated
GAUGE . . . . .	56 inches	STEERING . . . . .	Lever only
WHEELS . . . . .	Wood		
FRONT TIRES . . . . .	33 x 4½ inches, pneumatic		
REAR TIRES . . . . .	33 x 4½ inches, pneumatic, anti-skid		

In addition to above specifications, price includes two head lamps, two side lamps, tail lamp, interior dome lamp, autometer, clock, horn and kit of tools.

**MILBURN  
WAGON  
COMPANY**

**TOLEDO, OHIO**

**Price, \$2485**




---

**MILBURN LIGHT ELECTRIC BROUGHAM—27-L**

---

COLOR . . . . .	Body, blue, green, or brown; running gear, black	BRAKE SYSTEMS . .	Service brake: Expanding on rear wheels Emergency brake: Contracting on rear wheels, also electric on motor
SEATING CAPACITY .	Five		
BODY:			
LENGTH OVER ALL	138 inches	BATTERY . . . . .	40 cell, 13 plate (rapid exchange)
WIDTH OVER ALL .	66 inches	SPEED . . . . .	6 to 25 miles per hour
WHEELBASE . . . .	105 inches	NO. FORWARD SPEEDS	Four
GAUGE . . . . .	56 inches	NO. REVERSE SPEEDS	Three
WHEELS . . . . .	Wire or wood	CONTROL . . . . .	Lever operated
FRONT TIRES . . . .	33 x 4 inches, cord	STEERING . . . . .	Lever
REAR TIRES . . . .	33 x 4 inches, cord		

---

**WARD MOTOR  
VEHICLE  
COMPANY**

**MOUNT VERNON  
NEW YORK**

**Price Upon Application**




**WARD SEVEN-HUNDRED-AND-FIFTY-POUND TRUCK—WS**

COLOR . . . . .	Optional	BRAKE SYSTEMS . .	Service brake: Expanding on rear wheels
CARRYING CAPACITY	750 pounds		Emergency brake: Contracting on propeller shaft
BODY:		BATTERY . . . . .	42 cell 7MVV Ironclad Exide, 65 cell G4 Edison, 42 cell 9WTXI Philadelphia lead
LENGTH OVER ALL	122¾ inches	SPEED . . . . .	Ten to twelve miles per hour
WIDTH OVER ALL .	53½ inches	No. FORWARD SPEEDS	Four
WHEELBASE . . . . .	88 inches	No. REVERSE SPEEDS	Two
GAUGE . . . . .	54 inches	CONTROL . . . . .	Lever operated
WHEELS . . . . .	Wood	STEERING . . . . .	Wheel
FRONT TIRES . . . . .	32 x 2½ inches, single solid		
REAR TIRES . . . . .	32 x 3 inches, single solid		



**WARD MOTOR  
VEHICLE  
COMPANY**  
MOUNT VERNON  
NEW YORK

Price Upon Application




**WARD THREE-AND-ONE-HALF-TON TRUCK—WF**

COLOR . . . . .	Optional	BRAKE SYSTEMS . . .	Dual, expanding on rear wheels
CARRYING CAPACITY.	7000 pounds	BATTERY . . . . .	42 cell 19MV Ironclad Exide; 60 cell G14 Edison; 42-27 WTXI Philadelphia lead
BODY:		SPEED . . . . .	Six to seven miles per hour
LENGTH OVER ALL	218 inches	NO. FORWARD SPEEDS	Four
WIDTH OVER ALL	80 inches	NO. REVERSE SPEEDS	Two
WHEELBASE . . . . .	132 inches	CONTROL . . . . .	Lever operated
GAUGE . . . . .	66½ inches	STEERING . . . . .	Wheel
WHEELS . . . . .	Wood		
FRONT TIRES . . . . .	36 x 5 inches, single solid		
REAR TIRES . . . . .	36 x 8 inches, single solid		

**ONEIDA  
MOTOR TRUCK  
COMPANY**  
**GREEN BAY  
WISCONSIN**

**Price, \$2600**



**ONEIDA TWO-TON UNIT DRIVE ELECTRIC TRUCK—2-E**

COLOR . . . . .	Lead	BRAKE SYSTEMS . .	Two independent sets, expanding on rear wheels
CARRYING CAPACITY.	4000 pounds		
BODY:			
LENGTH OVER ALL.	184 inches	BATTERY . . . . .	At extra charge
WIDTH OVER ALL .	77 inches	SPEED . . . . .	15 miles per hour
WHEELBASE . . . . .	111 inches	NO. FORWARD SPEEDS	Five
GAUGE . . . . .	56½ inches	NO. REVERSE SPEEDS	Five
WHEELS . . . . .	Wood	CONTROL . . . . .	Lever, reverse, pedal
FRONT TIRES . . . . .	36 x 4 inches, single solid	Steering . . . . .	Lever or wheel
REAR TIRES . . . . .	36 x 6 inches, single solid		

**ILLUSTRATIONS AND  
SPECIFICATIONS  
GASOLINE  
COMMERCIAL  
VEHICLES**

---

## **N. A. C. C. DEFINITION OF STANDARD CHASSIS FOR GASOLINE COMMERCIAL VEHICLES**

**A** STANDARD chassis of a commercial vehicle to be propelled by an internal combustion engine shall consist of an assembly of all essential parts of a truck chassis with protective housings, ready for operation on the road, including, as minimum equipment, a set of tires attached to wheels; driver's seat with padding or cushion on all chassis rated at one-ton capacity or more; front wheel fenders; running board or mounting step; tool compartment; priming coat of lead on all parts to be painted; pair of front lights and one tail lamp; license brackets; warning signal; jack and a set of tools commonly used for making adjustments and minor repairs on the road.


---

## **N. A. C. C. DEFINITION OF STANDARD CHASSIS FOR ELECTRIC COMMERCIAL VEHICLES**

**A** STANDARD chassis of a commercial vehicle to be propelled by electricity shall consist of a running gear, motor, battery cradle or box, driving and control mechanism and wiring, with all essential parts, fittings and protective housings thereof, assembled complete ready for operation on the road with the exception of a battery; a priming coat of lead on all parts to be painted; and, as minimum equipment, a set of tires attached to wheels; pair of front lights and one tail lamp, with necessary wiring installed; license brackets, charging plug and cable; odometer; warning signal, and set of tools commonly used for making adjustments and minor repairs on the road.

**STANDARD  
MOTOR TRUCK  
COMPANY**  
**DETROIT  
MICHIGAN**

Price, Chassis . . . . .	\$4200
One-Ton Chassis—56 . . . . .	2250
Two-Ton Chassis—76 . . . . .	3200
Five-Ton Chassis—86 . . . . .	5000




---

**STANDARD THREE-AND-ONE-HALF-TON TRUCK—66**

---


COLOR . . . . .	Gray	HORSEPOWER . . . . .	32.4 (N.A.C.C. Rating)
CARRYING CAPACITY. . . . .	7000 pounds	BORE AND STROKE . . . . .	4½ x 5½ inches
POSITION OF DRIVER. . . . .	Left side	LUBRICATION . . . . .	Splash with circulating pump
WHEELBASE . . . . .	160 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	Front, 67 inches; rear, 65¾ inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Wood	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 5 inches, single solid	LIGHTING SYSTEM . . . . .	Oil
REAR TIRES . . . . .	36 x 5 inches, dual solid	GASOLINE SYSTEM . . . . .	Vacuum
SERVICE BRAKE . . . . .	Expanding on rear wheels	CLUTCH . . . . .	Dry plate
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective sliding
CYLINDERS . . . . .	Four	GEAR CHANGES . . . . .	Four forward, one reverse
HOW ARRANGED . . . . .	Vertically	DRIVE . . . . .	Worm
CAST . . . . .	In pairs	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and gear

---

**DIAMOND T  
MOTOR CAR  
COMPANY**

**CHICAGO  
ILLINOIS**

Price, Chassis . . . . .	\$4390
One-and-One-Half-Ton—T . . .	2675
Two-Ton—J3 . . . . .	3185
Five-Ton Special—S . . . . .	5785
One-and-One-Half-Ton Farm Special with Cab and Body Complete . . . . .	2930




---

**DIAMOND T THREE-AND-ONE-HALF-TON TRUCK—LB**


---

COLOR . . . . .	Gray	HORSEPOWER . . . . .	32.4 (N.A.C.C. Rating)
CARRYING CAPACITY. . . . .	7000 pounds	BORE AND STROKE . . . . .	4½ x 5½ inches
POSITION OF DRIVER. . . . .	Right side	LUBRICATION . . . . .	Force feed and splash
WHEELBASE . . . . .	170 and 180 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	Front, 66¾ inches; rear, 66¾ inches	COOLING . . . . .	Centrifugal pump
WHEELS . . . . .	Wood	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 5 inches, single solid	GASOLINE SYSTEM . . . . .	Gravity
REAR TIRES . . . . .	36 x 5 inches, dual solid	CLUTCH . . . . .	Dry multiple disc
SERVICE BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective sliding
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GEAR CHANGES . . . . .	Four forward, one reverse
CYLINDERS . . . . .	Four	DRIVE . . . . .	Worm
HOW ARRANGED . . . . .	Vertically	REAR AXLE . . . . .	Full floating
CAST . . . . .	In pairs	STEERING GEAR . . . . .	Worm and gear

---

**A C M E  
MOTOR TRUCK  
COMPANY  
C A D I L L A C  
M I C H I G A N**

One-Ton . . . . .	} Prices Upon Appli- cation
One-and-Half-Ton . . . . .	
Two-Ton . . . . .	
Three-and-One-Half-Ton . . . . .	
Five-Ton . . . . .	




---

**ACME TWO-TON TRUCK—A**

---

COLOR . . . . .	Gray prime	HORSEPOWER . . . . .	27.23 (N.A.C.C. Rating)
CARRYING CAPACITY. . . . .	4000 pounds	BORE AND STROKE . . . . .	4½ x 5¼ inches
POSITION OF DRIVER. . . . .	Left side	LUBRICATION . . . . .	Force feed and splash
WHEELBASE . . . . .	148 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	58½ inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Wood	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 4 inches, single solid	GASOLINE SYSTEM . . . . .	Vacuum
REAR TIRES . . . . .	36 x 7 inches, single solid	CLUTCH . . . . .	Single dry plate
SERVICE BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective dog clutch type
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GEAR CHANGES . . . . .	Four forward, one reverse
CYLINDERS . . . . .	Four	DRIVE . . . . .	Worm
HOW ARRANGED . . . . .	Vertically	REAR AXLE . . . . .	Full floating
CAST . . . . .	En bloc	STEERING GEAR . . . . .	Screw and nut


In addition to above specifications, price includes seat, lamps, mechanical horn, jack, tools and tool box.

---

# NASH MOTORS COMPANY

KENOSHA  
WISCONSIN

Price, Chassis . . \$2250  
One-Ton, Chassis. 1650



## NASH TWO-TON TRUCK


COLOR . . . . .	Battleship gray	LUBRICATION . . . .	Force feed and splash
CARRYING CAPACITY .	4000 pounds	RADIATOR . . . . .	Vertical tube
POSITION OF DRIVER	Left side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	144 inches	IGNITION . . . . .	High tension magneto
GAUGE . . . . .	Front, 56½ inches; rear, 59½ inches	STARTING SYSTEM . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED .	Gear to fly wheel
FRONT TIRES . . . . .	34 x 4 inches, single solid	LIGHTING SYSTEM . .	Electric
REAR TIRES . . . . .	34 x 6 inches, single solid	VOLTAGES . . . . .	Six to eight
SERVICE BRAKE . . .	Contracting on rear wheels	WIRING SYSTEM . . .	Single
EMERGENCY BRAKE .	Contracting on drive shaft	GASOLINE SYSTEM . .	Gravity
CYLINDERS . . . . .	Four	CLUTCH . . . . .	Three dry plate
HOW ARRANGED . . .	Vertically	TRANSMISSION . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . .	Four forward, one reverse
HORSEPOWER . . . .	22.5 (N.A.C.C. Rating)	DRIVE . . . . .	Internal gear
BORE AND STROKE . .	3¾ x 5¼ inches	REAR AXLE . . . . .	Dead
		STEERING GEAR . . .	Screw and nut



# NASH MOTORS COMPANY

KENOSHA  
WISCONSIN

Price, Chassis . . . \$3250  
One-Ton, Chassis . 1650




## NASH TWO-TON QUAD

COLOR . . . . .	Battleship gray	HORSEPOWER . . . . .	28.90 (N.A.C.C. Rating)
CARRYING CAPACITY.	4000 pounds	BORE AND STROKE . .	4¼ x 5½ inches
POSITION OF DRIVER	Left side	LUBRICATION . . . . .	Full force feed
WHEELBASE . . . . .	124 inches	RADIATOR . . . . .	Vertical tube
GAUGE . . . . .	60½ inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Steel castings	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 5 inches, single solid	LIGHTING SYSTEM . .	Gas
REAR TIRES . . . . .	36 x 5 inches, single solid	GASOLINE SYSTEM . .	Gravity
SERVICE BRAKE . . .	Contracting on all four wheels	CLUTCH . . . . .	Three dry plate
EMERGENCY BRAKE .	Contracting on propeller shaft	TRANSMISSION . . . .	Selective sliding
CYLINDERS . . . . .	Four	GEAR CHANGES . . .	Four forward, one reverse
HOW ARRANGED . . .	Vertically	DRIVE . . . . .	Internal gear
CAST . . . . .	En bloc	REAR AXLE . . . . .	Dead
		STEERING GEAR . . .	Screw and nut

**AMERICAN-  
LA FRANCE  
FIRE ENGINE  
COMPANY  
INCORPORATED**

**E L M I R A  
N E W Y O R K**

85-Foot-6-C . . .	} Prices Upon Appli- cation
75-Foot-6-C . . .	
65-Foot-6-C . . .	
55-Foot-6-C . . .	
85-Foot-4-C . . .	
75-Foot-4-C . . .	
65-Foot-4-C . . .	
55-Foot-4-C . . .	



**AMERICAN-LA FRANCE AERIAL HOOK AND LADDER TRUCK**


COLOR . . . . .	Optional	LUBRICATION . . . .	Force feed and splash
POSITION OF DRIVER .	Right side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	19 feet, 9 inches to 31 feet, 9 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	Front, 76¾ inches; rear, 62 inches	IGNITION . . . . .	High tension magneto and storage battery
WHEELS . . . . .	Front, solid cast steel; rear, wood	STARTING SYSTEM .	Two unit
FRONT TIRES . . . .	38 x 4 inches, dual solid	STARTER OPERATED .	Gear to fly wheel
REAR TIRES . . . . .	42 x 4 inches, single solid	LIGHTING SYSTEM .	Electric
SERVICE BRAKE . . .	Contracting on jack shaft	VOLTAGE . . . . .	Six
EMERGENCY BRAKE .	Expanding on front wheels	WIRING SYSTEM . .	Single
CYLINDERS . . . . .	Four or six	GASOLINE SYSTEM .	Gravity
HOW ARRANGED . . .	Vertically	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	In pairs	TRANSMISSION . . .	Selective sliding
HORSEPOWER . . . .	48.4 or 72.6 (N.A.C.C. Rating)	GEAR CHANGES . .	Three forward, one reverse
BORE AND STROKE .	5½ x 6 inches	DRIVE . . . . .	To front wheels
		REAR AXLE . . . . .	Dead
		STEERING GEAR . . .	Planetary

In addition to above specifications, price includes speedometer, voltmeter, siren horn and locomotive bell.

**AMERICAN-  
LA FRANCE  
FIRE ENGINE  
COMPANY  
INCORPORATED**

**E L M I R A  
N E W Y O R K**

1000-Gallon—6-C.	} Prices Upon Appli- cation
750-Gallon—6-C.	
600-Gallon—6-C.	
350-Gallon—6-C.	
600-Gallon—4-C.	
300-Gallon—4-C.	



**AMERICAN-LA FRANCE TRIPLE COMBINATION PUMPING CAR**


COLOR . . . . .	Optional	LUBRICATION . . . .	Force feed and splash
POSITION OF DRIVER . . . . .	Right side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	140½, 156¾, or 161¾ inches	COOLING . . . . .	Water pump
GAUGE . . . . .	Front 62 inches; rear 71¾ inches	IGNITION . . . . .	High tension magneto and storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . .	Two unit
FRONT TIRES . . . . .	36 x 4 inches, single solid	STARTER OPERATED .	Gear to fly wheel
REAR TIRES . . . . .	36 x 4 inches, dual solid	LIGHTING SYSTEM . .	Electric
SERVICE BRAKE . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . .	Expanding on rear wheels	WIRING SYSTEM . . .	Single
CYLINDERS . . . . .	Four or six	GASOLINE SYSTEM . .	Gravity
HOW ARRANGED . . . .	Vertically	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	In pairs	TRANSMISSION . . . .	Selective sliding
HORSEPOWER . . . . .	48.4, 72.6, or 48.6 (N.A.C.C. Rating)	GEAR CHANGES . . .	Three forward, one reverse
BORE AND STROKE . . .	5½ x 6 inches, 4 and 6 cylinders; 4¾ x 6 inches, 4 cylinders	DRIVE . . . . .	Plain bevel
		REAR AXLE . . . . .	Dead
		STEERING GEAR . . . .	Worm and gear

In addition to above specifications, price includes speedometer, voltmeter, siren horn and locomotive bell.

**PIERCE-ARROW  
MOTOR CAR  
COMPANY**

**B U F F A L O  
N E W Y O R K**

**Price, Chassis, \$4300**




---

**PIERCE-ARROW TWO-TON TRUCK**

---

COLOR . . . . .	Optional	HORSEPOWER . . . . .	25.6 (N.A.C.C. Rating)
CARRYING CAPACITY.	4000 pounds	BORE AND STROKE . . . . .	4 x 5½ inches
POSITION OF DRIVER.	Right side	LUBRICATION . . . . .	Force feed
WHEELBASE . . . . .	150 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	Front, 59 <sup>11</sup> / <sub>16</sub> inches; rear, 56½ inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Wood	IGNITION . . . . .	Dual high tension magneto with coil and battery
FRONT TIRES . . . . .	36 x 4 inches, single solid	GASOLINE SYSTEM . . . . .	Gravity
REAR TIRES . . . . .	36 x 4 inches, dual solid	CLUTCH . . . . .	Enclosed cone
SERVICE BRAKE . . . . .	Contracting on transmission	TRANSMISSION . . . . .	Selective sliding
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GEAR CHANGES . . . . .	Four forward, one reverse
CYLINDERS . . . . .	Four	DRIVE . . . . .	Worm
CAST . . . . .	In pairs	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Screw and nut


In addition to above specifications, price includes cab, windshield, side curtains, hubodometer, anti-skid chains and hooks on rear wheels, towing hooks front and rear, wood body sills clipped to frame, horn, tool box and full set of tools.

---

**PIERCE-ARROW  
MOTOR CAR  
COMPANY**

**B U F F A L O  
N E W Y O R K**

**Price, Chassis, \$5500**




---

**PIERCE-ARROW FIVE-TON TRUCK**

---


<b>COLOR . . . . .</b>	Optional	<b>BORE AND STROKE . .</b>	4 $\frac{7}{8}$ x 6 inches
<b>CARRYING CAPACITY.</b>	10,000 pounds	<b>LUBRICATION . . . .</b>	Force feed
<b>POSITION OF DRIVER.</b>	Right side	<b>RADIATOR . . . . .</b>	Tubular
<b>WHEELBASE . . . .</b>	168 inches	<b>COOLING . . . . .</b>	Water pump
<b>GAUGE . . . . .</b>	Front, 68 inches; rear, 64 inches	<b>IGNITION . . . . .</b>	High tension magneto with automatic impulse starter coupling
<b>WHEELS . . . . .</b>	Wood, artillery	<b>GASOLINE SYSTEM .</b>	Gravity
<b>FRONT TIRES . . .</b>	36 x 5 inches, single solid	<b>CLUTCH . . . . .</b>	Enclosed cone
<b>REAR TIRES . . . .</b>	40 x 6 inches, dual solid	<b>TRANSMISSION . . .</b>	Selective sliding
<b>SERVICE BRAKE . .</b>	Contracting on transmission	<b>GEAR CHANGES . .</b>	Three forward, one reverse
<b>EMERGENCY BRAKE .</b>	Expanding on rear wheels	<b>DRIVE . . . . .</b>	Worm
<b>CYLINDERS . . . . .</b>	Four	<b>REAR AXLE . . . . .</b>	Full floating
<b>CAST . . . . .</b>	In pairs	<b>STEERING GEAR . . .</b>	Screw and nut
<b>HORSEPOWER . . .</b>	38.03 (N.A.C.C. Rating)		

In addition to above specifications, price includes cab, windshield, side curtains, hubodometer, anti-skid chains and hooks on rear wheels, towing hooks front and rear, wood body sills clipped to frame, horn, tool box and full set of tools.

**BROCKWAY  
MOTOR TRUCK  
COMPANY**

**CORTLAND  
NEW YORK**

Price, Chassis . . . . .	\$5000
One-and-One-Half-Ton Chassis—S2 . . . . .	2100
Two-and-One-Half-Ton Chassis—K4 . . . . .	3000
Three-and-One-Half-Ton Chassis—R2 . . . . .	3900




**BROCKWAY FIVE-TON TRUCK—"T"**

COLOR . . . . .	Brockway brown	CAST . . . . .	In pairs
CARRYING CAPACITY. . . . .	10,000 pounds	HORSEPOWER . . . . .	36.1 (N.A.C.C. Rating)
POSITION OF DRIVER. . . . .	Left side	BORE AND STROKE . . . . .	4 $\frac{3}{4}$ x 6 inches
WHEELBASE . . . . .	174 inches	LUBRICATION . . . . .	Full force feed
GAUGE . . . . .	Front, 68 $\frac{3}{4}$ inches; rear, 60 $\frac{1}{2}$ inches	RADIATOR . . . . .	Tubular
WHEELS . . . . .	Metal	COOLING . . . . .	Water pump
FRONT TIRES . . . . .	36 x 6 inches, single solid	IGNITION . . . . .	High tension magneto
REAR TIRES . . . . .	40 x 6 inches, dual solid	GASOLINE SYSTEM . . . . .	Vacuum
SERVICE BRAKE . . . . .	Expanding rear wheel brake drums	CLUTCH . . . . .	Dry multiple disc
EMERGENCY BRAKE . . . . .	Expanding rear wheel brake drums	TRANSMISSION . . . . .	Selective sliding
CYLINDERS . . . . .	Four	GEAR CHANGES . . . . .	Four forward, one reverse
HOW ARRANGED . . . . .	Vertically	DRIVE . . . . .	Worm
		REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and gear

**OLDS MOTOR  
WORKS  
LANSING  
MICHIGAN**

**Price . . . . . \$1350**  
**Chassis . . . . . 1250**  
**Chassis with Cab . 1295**




---

**OLDSMOBILE ECONOMY TRUCK, EXPRESS MODEL**

---

COLOR . . . . .	Maroon	BORE AND STROKE . . . . .	3½ x 5¼ inches
CARRYING CAPACITY.	1500 pounds	LUBRICATION . . . . .	Force feed and splash
POSITION OF DRIVER	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	128 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	35 x 5 inches, ribbed cord	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	35 x 5 inches, cord, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Four	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Cone
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER. . . . .	21.7 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Internal gear
		REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Screw and nut


In addition to above specifications, price includes top, windshield, speedometer, ammeter, electric horn and demountable rims.

---

# THE AUTOCAR COMPANY

ARDMORE  
PENNSYLVANIA

Price, Chassis . . . . . \$2300  
XXI-G Chassis, 120-inch  
Wheelbase . . . . . 2400




## AUTOCAR TWO-TON TRUCK—XXI-F

COLOR . . . . .	Gear, red; seat structure, green	HORSEPOWER . . . . .	18 (N.A.C.C. Rating)
CARRYING CAPACITY.	4000 pounds	BORE AND STROKE . . . . .	4¾ x 4½ inches
POSITION OF DRIVER.	Right side	LUBRICATION . . . . .	Full splash with mechanical oiler
WHEELBASE . . . . .	97 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	58 inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Wood	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	34 x 4 inches, single solid or 36 x 5 inches, pneumatic	LIGHTING SYSTEM . . . . .	Gas and oil
REAR TIRES . . . . .	34 x 5 inches, single solid or 36 x 5 inches, pneumatic	GASOLINE SYSTEM . . . . .	Gravity
SERVICE BRAKE . . . . .	Contracting on rear wheels	CLUTCH . . . . .	Plate
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Progressive sliding
CYLINDERS . . . . .	Two	GEAR CHANGES . . . . .	Three forward, one reverse
HOW ARRANGED . . . . .	Horizontally	DRIVE . . . . .	Double reduction bevel and spur
CAST . . . . .	Separate	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Bevel pinion and sector



**MAXWELL  
MOTOR  
COMPANY  
INCORPORATED**  
**DETROIT  
MICHIGAN**

Price, Chassis . . . . .	\$1185.00
Chassis—Cape Top and Wind- shield . . . . .	1225.00
“ Box Side Body . . . . .	1320.00
“ Box Side Grain Body, End Gate. . . . .	1333.00
“ Double Panel Box Side Grain Body, End Gate . . . . .	1345.00
“ Stake Side Body . . . . .	1312.50
“ Stock Rack Body . . . . .	1325.00
“ Box Side Body and Canopy . . . . .	1355.00





---

**MAXWELL ONE-AND-ONE-HALF-TON TRUCK**

---

COLOR . . . . .	Body, black; running gear, red	BORE AND STROKE . . . . .	3½ x 4½ inches
CARRYING CAPACITY. . . . .	3000 pounds	LUBRICATION . . . . .	Pump over and splash
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Tubular
WHEELBASE . . . . .	124 inches	COOLING . . . . .	Thermo-syphon
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	LIGHTING SYSTEM . . . . .	Electric
FRONT TIRES . . . . .	32 x 3 inches, single solid	VOLTAGE . . . . .	Six
REAR TIRES . . . . .	32 x 4 inches, single solid	WIRING SYSTEM . . . . .	Single
SERVICE BRAKE . . . . .	Expanding on rear axle	GASOLINE SYSTEM . . . . .	Gravity
EMERGENCY BRAKE . . . . .	Expanding on rear axle	CLUTCH . . . . .	Cone, running in oil
CYLINDERS . . . . .	Four	TRANSMISSION . . . . .	Selective sliding
HOW ARRANGED . . . . .	Vertically	GEAR CHANGES . . . . .	Three forward, one reverse
CAST . . . . .	En bloc	DRIVE . . . . .	Worm
HORSEPOWER . . . . .	21.03 (N.A.C.C. Rating)	REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes electric horn.




---

**WILSON TWO-AND-ONE-HALF-TON TRUCK—EA**

---

COLOR . . . . .	Wilson gray	BORE AND STROKE .	4¼ x 5¼ inches
CARRYING CAPACITY.	5000 pounds	LUBRICATION . . . .	Splash with circulating pump
POSITION OF DRIVER.	Left side	RADIATOR . . . . .	Tubular
WHEELBASE . . . . .	152 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	58½ inches	IGNITION . . . . .	High tension magneto
WHEELS . . . . .	Wood	LIGHTING SYSTEM .	Oil
FRONT TIRES . . . .	36 x 4 inches, single solid	WIRING SYSTEM . .	Single
REAR TIRES . . . . .	36 x 7 inches, single solid	GASOLINE SYSTEM .	Gravity
SERVICE BRAKE . . .	Expanding on rear wheels	CLUTCH . . . . .	Dry disc
EMERGENCY BRAKE .	Expanding on rear wheels	TRANSMISSION . . .	Selective sliding
CYLINDERS . . . . .	Four	GEAR CHANGES . .	Four forward, one reverse
HOW ARRANGED . . .	Vertically	DRIVE . . . . .	Worm
CAST . . . . .	En bloc	REAR AXLE . . . . .	Full floating
HORSEPOWER . . . .	27.2 (N.A.C.C. Rating)	STEERING GEAR . . .	Worm and gear


In addition to above specifications, price includes diaphragm horn, oil head and tail lights, jack, seat, tools, cushions, front fenders and bumper.

---

**LOCOMOBILE  
COMPANY  
OF AMERICA**

**BRIDGEPORT  
CONNECTICUT**

**Price, \$4700**




---

**RIKER FOUR-TON TRUCK—BB**

---


COLOR . . . . .	Optional	LUBRICATION . . . . .	Force feed and splash
SEATING CAPACITY . . . . .	8000 pounds	RADIATOR . . . . .	Tubular
POSITION OF DRIVER . . . . .	Right side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	150 inches	IGNITION . . . . .	High tension magneto
GAUGE . . . . .	Front, 60 inches; rear, 66 inches	STARTING SYSTEM . . . . .	Two unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	36 x 5 inches, single solid	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	36 x 6 inches, dual solid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on propeller shaft	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Gravity
CYLINDERS . . . . .	Four	CLUTCH . . . . .	Cone
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	In pairs	GEAR CHANGES . . . . .	Four forward, one reverse
HORSEPOWER . . . . .	28.9 (N.A.C.C. Rating)	DRIVE . . . . .	Worm
BORE AND STROKE . . . . .	4¼ x 6 inches	REAR AXLE . . . . .	Live axle
		STEERING GEAR . . . . .	Screw and nut

---

**MORELAND  
MOTOR TRUCK  
COMPANY**

**LOS ANGELES  
CALIFORNIA**

Price, Chassis . . . . .	\$3775
One-and-One-Half-Ton—19B . . .	2930
Four-Ton—19G . . . . .	4875
Five-Ton—19J . . . . .	5350




---

**MORELAND TWO-AND-ONE-HALF-TON TRUCK—19C**


---

COLOR . . . . .	Chassis, red with black striping	HORSEPOWER . . . . .	32.4 (N.A.C.C. Rating)
CARRYING CAPACITY.	5000 pounds	BORE AND STROKE . . .	4½ x 5½ inches
POSITION OF DRIVER.	Left side	LUBRICATION . . . . .	Splash with circulating pump
WHEELBASE . . . . .	144 or 168 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	Front, 58¾ inches; rear, 58¼ inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Metal	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 4 inches, single solid	LIGHTING SYSTEM . . .	Oil
REAR TIRES . . . . .	36 x 7 inches, single solid	GASOLINE SYSTEM . . .	Gravity
SERVICE BRAKE . . . .	Expanding on rear wheels	CLUTCH . . . . .	Dry multiple disc
EMERGENCY BRAKE . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective sliding
CYLINDERS . . . . .	Four	GEAR CHANGES . . . .	Four forward, one reverse
HOW ARRANGED . . . .	Vertically	DRIVE . . . . .	Worm
CAST . . . . .	In pairs	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Screw and nut

---

**VIM MOTOR  
TRUCK  
COMPANY**  
**PHILADELPHIA  
PENNSYLVANIA**

Price (Standard)	\$1095
Model D Closed Panel Body	1235
" F Open Express	1195
" B Wire Door Tail Gate	1235
" G Closed Cab Panel Body	1315
" H Cab Top Express	1195
" M U. S. Mail Wagon.	1345
" S Stake Body	1275
" SC Special—Chassis	1350
" SF Special—Express Body	1480
One-Ton Chassis	2195
One-Ton B Closed Panel Body	2450
One-Ton F Open Express Body	2395
Two-Ton Chassis (Standard)	3150
Three-Ton Chassis (Standard)	3950



**VIM ONE-HALF-TON TRUCK—27**


COLOR . . . . .	Body, blue; running gear, black	BORE AND STROKE . . . . .	3 x 4½ inches
CARRYING CAPACITY.	1000 pounds	LUBRICATION . . . . .	Force feed and splash
POSITION OF DRIVER.	Left side	RADIATOR . . . . .	Tubular
WHEELBASE . . . . .	108 inches	COOLING . . . . .	Thermo-syphon
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	LIGHTING SYSTEM . . . . .	Electric
FRONT TIRES . . . . .	31 x 4 inches, pneumatic	VOLTAGE . . . . .	Six
REAR TIRES . . . . .	31 x 4 inches, pneumatic, anti-skid	WIRING SYSTEM . . . . .	Single
SERVICE BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Gravity
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	CLUTCH . . . . .	Cone
CYLINDERS . . . . .	Four	TRANSMISSION . . . . .	Selective sliding
HOW ARRANGED . . . . .	Vertically	GEAR CHANGES . . . . .	Three forward, one reverse
CAST . . . . .	En bloc	DRIVE . . . . .	Worm
HORSEPOWER . . . . .	14.4 (N.A.C.C. Rating)	REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes top, top hood,  
windshield, tire pump, electric horn and demountable rims.

# MACCAR TRUCK COMPANY

SCRANTON  
PENNSYLVANIA

Price, Chassis, \$3500




## MACCAR TWO-AND-ONE-HALF-TON TRUCK

COLOR . . . . .	Lead	HORSEPOWER . . . . .	32.4 (N.A.C.C. Rating)
CARRYING CAPACITY.	5000 pounds	BORE AND STROKE . . . . .	4 1/4 x 5 1/2 inches
POSITION OF DRIVER.	Left side	LUBRICATION . . . . .	Force feed and splash
WHEELBASE . . . . .	162 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	58 1/2 inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Steel or wood	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 4 inches, single solid	GASOLINE SYSTEM . . . . .	Gravity
REAR TIRES . . . . .	36 x 4 inches, dual solid	CLUTCH . . . . .	Dry multiple disc
SERVICE BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective sliding
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GEAR CHANGES . . . . .	Three forward, one reverse
CYLINDERS . . . . .	Four	DRIVE . . . . .	Worm
HOW ARRANGED . . . . .	Vertically	REAR AXLE . . . . .	Full floating
CAST . . . . .	In pairs	STEERING GEAR . . . . .	Worm and nut

In addition to above specifications price includes driver's low seat,  
two side and one rear oil lamp, horn, jack, tool box and set of tools.

**REO MOTOR  
CAR COMPANY**  
**LANSING  
MICHIGAN**

Price, Chassis . . . . .	\$1285
Cab and Sills . . . . .	1385
Cab and Express . . . . .	1435
Canopy Top Express . . . . .	1455
Cab and Stake Body . . . . .	1460
Cab and Grain Body . . . . .	1465
Carryall . . . . .	1490




---

**REO SPEED WAGON**

---


COLOR . . . . .	Body, olive drab; running gear, black	BORE AND STROKE . . . . .	4 $\frac{1}{8}$ x 4 $\frac{1}{2}$ inches
CARRYING CAPACITY . . . . .	1500 pounds	LUBRICATION . . . . .	Pump over and splash
POSITION OF DRIVER . . . . .	Left side	RADIATOR . . . . .	Tubular
WHEELBASE . . . . .	128 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	56 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	34 x 4 $\frac{1}{2}$ inches, pneumatic	STARTER OPERATED . . . . .	Chain to trans- mission shaft
REAR TIRES . . . . .	34x4 $\frac{1}{2}$ inches, pneu- matic, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Contracting on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Double
CYLINDERS . . . . .	Four	GASOLINE SYSTEM . . . . .	Gravity
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	In pairs	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	27.23 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Spiral bevel
		REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Pinion and sector

In addition to above specifications, price includes speed-ometer, ammeter, tire pump and demountable rims.

---

**THE KELLY-  
SPRINGFIELD  
MOTOR TRUCK  
C O M P A N Y**  
SPRINGFIELD  
O H I O

Price, Chassis—K-32 . . . . .	\$3000
One-and-One-Half-Ton Chassis, Chain-Drive—K-31 . . . . .	3000
Two-and-One-Half-Ton Chassis, Worm-Drive—K-36 . . . . .	3500
Two-and-One-Half-Ton Chassis, Chain-Drive—K-35 . . . . .	3500



**KELLY-SPRINGFIELD ONE-AND-ONE-HALF-TON TRUCK—K-32**

COLOR . . . . .	Gray lead	HORSEPOWER . . . . .	22.5 (N.A.C.C. Rating)
CARRYING CAPACITY. . . . .	3000 pounds	BORE AND STROKE . . . . .	3¼ x 5¼ inches
POSITION OF DRIVER. . . . .	Left side	LUBRICATION . . . . .	Force feed
WHEELBASE . . . . .	144 inches	RADIATOR . . . . .	Cellular
GAUGE . . . . .	Front, 57 inches; rear, 59½ inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Wood	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 3½ inches, single solid	GASOLINE SYSTEM . . . . .	Gravity
REAR TIRES . . . . .	36 x 6 inches, single solid	CLUTCH . . . . .	Cone
SERVICE BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective sliding
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GEAR CHANGES . . . . .	Three forward, one reverse
CYLINDERS . . . . .	Four	DRIVE . . . . .	Worm
HOW ARRANGED . . . . .	Vertically	REAR AXLE . . . . .	Semi-floating
CAST . . . . .	En bloc	STEERING GEAR . . . . .	Worm and gear


In addition to above specifications, price includes driver's seat, two oil dash side lamps and tail lamp, full set of small tools in kit roll, two-ton jack and special wrenches, warning signal and hubodometer.



**THE KELLY-  
SPRINGFIELD  
MOTOR TRUCK  
COMPANY**

**SPRINGFIELD  
O H I O**

Price, Chassis—K-40 . . . . .	\$4400
Four-Ton Chassis, Chain-Drive —K-45 . . . . .	4550
Five-Ton Chassis, Chain-Drive —K-50 . . . . .	5150
Six-Ton Chassis, Chain-Drive —K-60 . . . . .	5500



**KELLY-SPRINGFIELD THREE-AND-ONE-HALF-TON TRUCK—K-40**


COLOR . . . . .	Gray lead	HORSEPOWER . . . . .	32.4 (N.A.C.C. Rating)
CARRYING CAPACITY. . . . .	7000 pounds	BORE AND STROKE . . . . .	4½ x 6½ inch
POSITION OF DRIVER. . . . .	Left side	LUBRICATION . . . . .	Force feed
WHEELBASE . . . . .	150 inches	RADIATOR . . . . .	Cellular
GAUGE . . . . .	Front, 70 inches; rear, 73¾ inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Wood	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 5 inches, single solid	GASOLINE SYSTEM . . . . .	Gravity
REAR TIRES . . . . .	40 x 5 inches, dual solid	CLUTCH . . . . .	Cone
SERVICE BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective sliding
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GEAR CHANGES . . . . .	Three forward, one reverse
CYLINDERS . . . . .	Four	DRIVE . . . . .	Double chain
HOW ARRANGED . . . . .	Vertically	REAR AXLE . . . . .	Dead; semi- floating jack shaft
CAST . . . . .	In pairs	STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes driver's seat, two oil dash side lamps and tail lamp, full set of small tools in kit roll, five-ton jack and special wrenches, warning signal and hubodometer.

# SERVICE MOTOR TRUCK COMPANY

W A B A S H  
I N D I A N A

Price, \$3215




## SERVICE ONE-AND-ONE-HALF-TON TRUCK—36

COLOR . . . . .	Lead	HORSEPOWER . . . . .	28.0 (N.A.C.C. Rating)
CARRYING CAPACITY.	3000 pounds	BORE AND STROKE . . . . .	4¼ x 5½ inches
POSITION OF DRIVER.	Left side	LUBRICATION . . . . .	Full force feed
WHEELBASE . . . . .	150 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	58½ inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Wood	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	35 x 5 inches, pneumatic anti-skid	LIGHTING SYSTEM . . . . .	Oil
REAR TIRES . . . . .	38 x 7 inches, pneumatic anti-skid	GASOLINE SYSTEM . . . . .	Gravity
SERVICE BRAKE . . . . .	Expanding on rear wheels	CLUTCH . . . . .	Dry plate
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective sliding
CYLINDERS . . . . .	Four	GEAR CHANGES . . . . .	Four forward, one reverse
HOW ARRANGED . . . . .	Vertically	DRIVE . . . . .	Worm
CAST . . . . .	En bloc	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Screw and nut

# SERVICE MOTOR TRUCK COMPANY

W A B A S H  
I N D I A N A

Price, \$3245



## SERVICE TWO-AND-ONE-HALF-TON TRUCK—51

COLOR . . . . .	Lead	HORSEPOWER . . . . .	28.9 (N.A.C.C. Rating)
CARRYING CAPACITY.	5000 pounds	BORE AND STROKE . . . . .	4¼ x 5½ inches
POSITION OF DRIVER.	Left side	LUBRICATION . . . . .	Full force feed
WHEELBASE . . . . .	160 and 180 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	58½ inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Wood	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 4 inches single solid	LIGHTING SYSTEM . . . . .	Oil
REAR TIRES . . . . .	36 x 7 inches, single solid	GASOLINE SYSTEM . . . . .	Gravity
SERVICE BRAKE . . . . .	Expanding on rear wheels	CLUTCH . . . . .	Dry plate
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective sliding
CYLINDERS . . . . .	Four	GEAR CHANGES . . . . .	Four forward, one reverse
HOW ARRANGED . . . . .	Vertically	DRIVE . . . . .	Worm
CAST . . . . .	En bloc	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Screw and nut


**G. A. SCHACHT  
MOTOR TRUCK  
C O M P A N Y**

**CINCINNATI, OHIO**

**Price, Chassis . . . . . \$3350**

**Two-and-One-Half-Ton Chassis 3650**

**Three-and-One-Half-Ton Chassis 4150**




---


**SCHACHT TWO-TON TRUCK**

---

<b>COLOR . . . . .</b>	Chassis, lead	<b>HORSEPOWER . . . . .</b>	28.9 (N.A.C.C. Rating)
<b>CARRYING CAPACITY. 4000 pounds</b>		<b>BORE AND STROKE . . . . .</b>	4 3/4 x 5 1/2 inches
<b>POSITION OF DRIVER. Left side</b>		<b>LUBRICATION . . . . .</b>	Force feed
<b>WHEELBASE . . . . .</b>	144 or 156 inches	<b>RADIATOR . . . . .</b>	Tubular
<b>GAUGE . . . . .</b>	Front, 62 inches; rear, 64 inches	<b>COOLING . . . . .</b>	Water pump
<b>WHEELS . . . . .</b>	Wood	<b>IGNITION . . . . .</b>	High tension magneto
<b>FRONT TIRES . . . . .</b>	36 x 4 inches, single solid	<b>LIGHTING SYSTEM . . . . .</b>	Oil
<b>REAR TIRES . . . . .</b>	36 x 7 inches, single solid	<b>GASOLINE SYSTEM . . . . .</b>	Gravity
<b>SERVICE BRAKE . . . . .</b>	Contracting on propeller shaft	<b>CLUTCH . . . . .</b>	Cone
<b>EMERGENCY BRAKE . . . . .</b>	Expanding on rear wheels	<b>TRANSMISSION . . . . .</b>	Selective sliding
<b>CYLINDERS . . . . .</b>	Four	<b>GEAR CHANGES . . . . .</b>	Three forward, one reverse
<b>HOW ARRANGED . . . . .</b>	Vertically	<b>DRIVE . . . . .</b>	Worm
<b>CAST . . . . .</b>	En bloc	<b>REAR AXLE . . . . .</b>	Full floating
		<b>STEERING GEAR . . . . .</b>	Worm and gear

In addition to above specifications, price includes hubodometer, two side lights, tail light, horn, jack and necessary tools.

---



## SCHACHT FIVE-TON TRUCK


COLOR . . . . .	Chassis lead	CAST . . . . .	En bloc
CARRYING CAPACITY. . . . .	10,000 pounds	HORSEPOWER . . . . .	32.4 (N.A.C.C. Rating)
POSITION OF DRIVER . . . . .	Left side	BORE AND STROKE . . . . .	4½ x 6 inches
WHEELBASE . . . . .	168, 180 or 156 inches	LUBRICATION . . . . .	Force feed
GAUGE . . . . .	Front, 64 inches; rear, 66 inches	RADIATOR . . . . .	Tubular
WHEELS . . . . .	Wood	COOLING . . . . .	Water pump
FRONT TIRES . . . . .	36 x 5 inches, single solid	IGNITION . . . . .	High tension magneto
REAR TIRES . . . . .	40 x 6 inches, dual solid	GASOLINE SYSTEM . . . . .	Gravity
SERVICE BRAKE . . . . .	Contracting on propeller shaft	CLUTCH . . . . .	Cone
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective sliding
CYLINDERS . . . . .	Four	GEAR CHANGES . . . . .	Eight forward, two reverse
HOW ARRANGED . . . . .	Vertically	DRIVE . . . . .	Worm
		REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes hubodometer, two side lights, tail light, horn, jack and necessary tools.

**GENERAL  
MOTORS  
TRUCK  
COMPANY**

**PONTIAC  
MICHIGAN**

**Price, Chassis, \$1595**




---

**G M C THREE-QUARTERS-TO-ONE-TON TRUCK—16**

---

<b>COLOR</b> . . . . .	Chassis, lead primer	<b>CAST</b> . . . . .	En bloc
<b>CARRYING CAPACITY.</b>	1500 to 2000 pounds	<b>HORSEPOWER</b> . . . . .	22.5 (N.A.C.C. Rating)
<b>POSITION OF DRIVER.</b>	Left side	<b>BORE AND STROKE</b> . . . . .	3¼ x 5 inches
<b>WHEELBASE</b> . . . . .	132 inches	<b>LUBRICATION</b> . . . . .	Pump over and splash
<b>GAUGE</b> . . . . .	56 inches	<b>RADIATOR</b> . . . . .	Tubular
<b>WHEELS</b> . . . . .	Wood	<b>COOLING</b> . . . . .	Water pump
<b>FRONT TIRES</b> . . . . .	35 x 5 inches, pneumatic, anti-skid	<b>IGNITION</b> . . . . .	High tension magneto
<b>REAR TIRES</b> . . . . .	35 x 5 inches, pneumatic, anti-skid	<b>GASOLINE SYSTEM</b> . . . . .	Gravity
<b>SERVICE BRAKE</b> . . . . .	Contracting on rear wheels	<b>CLUTCH</b> . . . . .	Dry multiple disc
<b>EMERGENCY BRAKE</b> . . . . .	Expanding on rear wheels	<b>TRANSMISSION</b> . . . . .	Selective sliding
<b>CYLINDERS</b> . . . . .	Four	<b>GEAR CHANGES</b> . . . . .	Three forward, one reverse
<b>HOW ARRANGED</b> . . . . .	Vertically	<b>DRIVE</b> . . . . .	Plain bevel
		<b>REAR AXLE</b> . . . . .	Three-quarters floating
		<b>STEERING GEAR</b> . . . . .	Screw and nut

In addition to above specifications, price includes tire pump, horn and demountable rim.


---

**D O D G E**  
**B R O T H E R S**  


---

**D E T R O I T**  
**M I C H I G A N**

Price . . . . . \$1160  
 Screen Side Business Car . . 1085




---

**DODGE BROTHERS PANEL BUSINESS CAR**

---

COLOR . . . . .	Black	LUBRICATION . . . . .	Splash with circulating pump
CARRYING CAPACITY. . . . .	1000 pounds	RADIATOR . . . . .	Tubular
POSITION OF DRIVER . . . . .	Left side	COOLING . . . . .	Centrifugal pump
WHEELBASE . . . . .	114 inches	IGNITION . . . . .	Storage battery
GAUGE . . . . .	56 inches	STARTING SYSTEM . . . . .	Single unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Chain to crank shaft
FRONT TIRES . . . . .	33 x 4 inches	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	33 x 4 inches, pneumatic, anti-skid	VOLTAGE . . . . .	Twelve
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Four	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	24.03 (N.A.C.C. Rating)	DRIVE . . . . .	Spiral bevel
BORE AND STROKE . . . . .	3 $\frac{7}{8}$ x 4 $\frac{1}{2}$ inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and worm wheel

In addition to above specifications, price includes top, windshield, speedometer, ammeter, tire pump, electric horn and demountable rims.


---

**J O N E S  
M O T O R C A R  
C O M P A N Y**  

---

**W I C H I T A  
K A N S A S**

**Price, Chassis, \$1495**




---

**JONES ONE-TON TRUCK—31-A**

---

COLOR . . . . .	Red	HORSEPOWER . . . . .	22.5 (N.A.C.C. Rating)
CARRYING CAPACITY.	2000 pounds	BORE AND STROKE . . . . .	3¼ x 5 inches
POSITION OF DRIVER.	Left side	LUBRICATION . . . . .	Force feed and splash
WHEELBASE . . . . .	130 inches	RADIATOR . . . . .	Cellular
GAUGE . . . . .	56 inches	COOLING . . . . .	Centrifugal pump
WHEELS . . . . .	Wood	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	34 x 3½ inches, single solid	GASOLINE SYSTEM . . . . .	Gravity
REAR TIRES . . . . .	34½ x 4 inches, single solid	CLUTCH . . . . .	Dry plate disc
SERVICE BRAKE . . . . .	Contracting on rear wheel drum	TRANSMISSION . . . . .	Selective sliding
EMERGENCY BRAKE . . . . .	Expanding on rear wheel drum	GEAR CHANGES . . . . .	Three forward, one reverse
CYLINDERS . . . . .	Four	DRIVE . . . . .	Spiral bevel
HOW ARRANGED . . . . .	Vertically	REAR AXLE . . . . .	Semi-floating
CAST . . . . .	En bloc	STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes cab.




**D E N B Y  
MOTOR TRUCK  
C O M P A N Y**  

---

**D E T R O I T  
M I C H I G A N**

Price . . . . .	\$3250
One-Ton—12 . . . . .	1950
Two-Ton—13 . . . . .	2450
Four-Ton—27 . . . . .	4250
Five-Ton—210 . . . . .	4900
Contractor—214 . . . . .	6000




---

**DENBY TWO-AND-ONE-HALF-TON TRUCK**


---

COLOR . . . . .	Lead	HORSEPOWER . . . . .	27.23 (N.A.C.C. Rating)
CARRYING CAPACITY. . . . .	5000-6000 pounds	BORE AND STROKE . . . . .	4½ x 5¼ inches
POSITION OF DRIVER. . . . .	Left side	LUBRICATION . . . . .	Splash with circulating pump
WHEELBASE . . . . .	149½ inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	Front, 60 inches rear, 62 inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Steel	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 4 inches, single solid	GASOLINE SYSTEM . . . . .	Gravity
REAR TIRES . . . . .	36 x 7 inches, single solid	CLUTCH . . . . .	Dry multiple disc
SERVICE BRAKE . . . . .	Contracting on rear wheels	TRANSMISSION . . . . .	Selective sliding
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GEAR CHANGES . . . . .	Four forward, one reverse
CYLINDERS . . . . .	Four	DRIVE . . . . .	Internal gear
HOW ARRANGED . . . . .	Vertically	REAR AXLE . . . . .	Dead axle and internal gear
CAST . . . . .	En bloc	STEERING GEAR . . . . .	Worm and wheel

**THE WHITE  
MOTOR  
COMPANY**

**CLEVELAND, OHIO**

**Price, Chassis . . \$2400  
Standard Express . 2675**




---

**WHITE THREE-QUARTER-TON TRUCK—15**

---

COLOR . . . . .	Body, dark green; running gear, red	HORSEPOWER . . . . .	22.5 (N.A.C.C. Rating)
CARRYING CAPACITY.	1500 pounds	BORE AND STROKE . . . . .	3¼ x 5½ inches
POSITION OF DRIVER.	Left side	LUBRICATION . . . . .	Pump over and splash
WHEELBASE . . . . .	133½ inches	RADIATOR . . . . .	Cellular
GAUGE . . . . .	56 inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Wood	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	34 x 4¼ inches, pneumatic	LIGHTING SYSTEM . . . . .	Gas
REAR TIRES . . . . .	34 x 4¼ inches, pneumatic	GASOLINE SYSTEM . . . . .	Gravity
SERVICE BRAKE . . . . .	Contracting on rear wheels	CLUTCH . . . . .	Plate in oil
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective sliding
CYLINDERS . . . . .	Four	GEAR CHANGES . . . . .	Four forward, one reverse
HOW ARRANGED . . . . .	Vertically	DRIVE . . . . .	Spiral bevel
CAST . . . . .	En bloc	REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and sector


In addition to above specifications, price includes front fenders, two acetylene headlights and prest-o-lite tank, two oil side lamps and oil tail lamp, signal horn, extra demountable rim, full set of tools including tire pump, tire repair outfit and jack.

---

# THE WHITE MOTOR COMPANY

CLEVELAND, OHIO

Price, Chassis . . . \$3300  
Standard Platform . 3550  
Standard Express . . 3600



## WHITE TWO-TON TRUCK—20


COLOR . . . . .	Red	CAST . . . . .	En bloc
CARRYING CAPACITY.	4000 pounds	HORSEPOWER . . . .	22.5
POSITION OF DRIVER.	Left side	(N.A.C.C. Rating)	
WHEELBASE . . . . .	157½ inches	BORE AND STROKE . .	3¼ x 5½ inches
GAUGE . . . . .	Front, 58½ inches; rear, 61 inches	LUBRICATION . . . .	Pump over and splash
WHEELS . . . . .	Wood	RADIATOR . . . . .	Cellular
FRONT TIRES . . . . .	36 x 4 inches, single solid or 37 x 5 inches, pneumatic	COOLING . . . . .	Water pump
REAR TIRES . . . . .	36 x 7 inches, single solid or 36 x 4 inches, dual solid	IGNITION . . . . .	High tension magneto
SERVICE BRAKE . . .	Contracting on rear wheels	LIGHTING SYSTEM . .	Gas
EMERGENCY BRAKE .	Expanding on rear wheels	GASOLINE SYSTEM . .	Gravity
CYLINDERS . . . . .	Four	CLUTCH . . . . .	Plate in oil
HOW ARRANGED . . .	Vertically	TRANSMISSION . . . .	Selective sliding
		GEAR CHANGES . . .	Four forward, one reverse
		DRIVE . . . . .	Plain bevel, double reduction
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . .	Worm and sector

In addition to above specifications, price includes seat and cushion, front fenders, two acetylene head lights and prest-o-lite tank, two oil side lamps and oil tail lamp, signal horn, full set of tools including jack.

# THE WHITE MOTOR COMPANY

CLEVELAND, OHIO

Price, Chassis . . . \$4300  
Standard Platform . 4575



## WHITE THREE—THREE-AND-ONE-HALF-TON TRUCK—40

COLOR . . . . .	Lead	GASOLINE SYSTEM . . .	Vacuum
CARRYING CAPACITY. . .	6000-7000 pounds	CLUTCH . . . . .	Plate in oil
POSITION OF DRIVER. . .	Left side	TRANSMISSION . . . .	Selective sliding
WHEELBASE . . . . .	174 inches	GEAR CHANGES . . .	Four forward, one reverse
GAUGE . . . . .	Front, 64½ inches; rear, 62 inches	DRIVE . . . . .	Double reduction gear drive. By shaft to floating type of rear axle. Power is applied to wheels by means of gears enclosed in hub case and running in oil. Each axle shaft carries on its outer end a center driving gear, which through an inter- mediate gear ap- plies power to a ring gear in the wheel hub case.
WHEELS . . . . .	Metal		
FRONT TIRES . . . . .	36 x 5 inches, single solid		
REAR TIRES . . . . .	40 x 5 inches, dual solid		
SERVICE BRAKE . . . .	Contracting on drive shaft		
EMERGENCY BRAKE . . .	Expanding on rear wheels		
CYLINDERS . . . . .	Four		
HOW ARRANGED . . . .	Vertically		
CAST . . . . .	En bloc		
HORSEPOWER . . . . .	22.5 (N.A.C.C. Rating)		
BORE AND STROKE . . .	3¼ x 5¼ inches		
LUBRICATION . . . . .	Force feed		
RADIATOR . . . . .	Tubular		
COOLING . . . . .	Water pump		
IGNITION . . . . .	High tension magneto	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . .	Worm and sector


In addition to above specifications, price includes seat and cushion, front fenders, oil dash lamps and tail lamp, signal horn and complete set of tools, including jack.

**THE WHITE  
MOTOR  
COMPANY**

**CLEVELAND, OHIO**

**Price . . . . . \$5000**

**Standard Platform . 5275**




---

**WHITE FIVE-TON TRUCK—45**

---


COLOR . . . . .	Lead	GASOLINE SYSTEM . .	Vacuum
CARRYING CAPACITY.	10,000 pounds	CLUTCH . . . . .	Plate in oil
POSITION OF DRIVER.	Left side	TRANSMISSION . . .	Selective sliding
WHEELBASE . . . . .	174 inches	GEAR CHANGES . .	Four forward, one reverse
GAUGE . . . . .	Front, 64½ inches; rear, 65½ inches	DRIVE . . . . .	Double reduction gear drive. By shaft to floating type of rear axle. Power is applied to wheels by means of gears enclosed in hub case and run- ning in oil. Each axle shaft carries on its outer end a cen- ter driving gear which, through an intermediate gear, applies power to a ring gear in the wheel hub case.
WHEELS . . . . .	Metal	REAR AXLE . . . .	Full floating
FRONT TIRES . . . .	36 x 6 in. single solid	STEERING GEAR . .	Worm and sector
REAR TIRES . . . .	40 x 6 in. dual solid		
SERVICE BRAKE . . .	Contracting on drive shaft		
EMERGENCY BRAKE .	Expanding on rear wheels		
CYLINDERS . . . . .	Four		
HOW ARRANGED . . .	Vertically		
CAST . . . . .	En bloc		
HORSEPOWER . . . .	28.9 (N.A.C.C. Rating)		
BORE AND STROKE . .	4¼ x 5¾ inches		
LUBRICATION . . . .	Force feed		
RADIATOR . . . . .	Tubular		
COOLING . . . . .	Water pump		
IGNITION . . . . .	High tension magneto		

In addition to above specifications, price includes seat and cushion, front fenders, oil dash lamps and tail lamp, signal horn, complete set of tools including jack.

# THE WHITE MOTOR COMPANY

CLEVELAND, OHIO

Price, \$5600



## WHITE FIVE-TON POWER-DUMPING TRUCK—45-D


COLOR . . . . .	Priming or lead	GASOLINE SYSTEM . .	Vacuum
CARRYING CAPACITY. .	10,000 pounds	CLUTCH . . . . .	Plate in oil
POSITION OF DRIVER. .	Left side	TRANSMISSION . . .	Selective sliding
WHEELBASE . . . . .	156 inches	GEAR CHANGES . .	Four forward, one reverse
GAUGE . . . . .	Front, 64½ inches; rear, 65½ inches	DRIVE . . . . .	Double reduction gear drive. By shaft to floating type of rear axle. Power is applied to wheels by means of gears enclosed in hub case and run- ning in oil. Each axle shaft carries on its outer end a center driving gear, which, through an intermediate gear, applies power to a ring gear in the wheel hub case.
WHEELS . . . . .	Metal		
FRONT TIRES . . . .	40 x 6 in. single solid		
REAR TIRES . . . .	40 x 6 in. dual solid		
SERVICE BRAKE . . .	Contracting on drive shaft		
EMERGENCY BRAKE .	Expanding on rear wheels		
CYLINDERS . . . . .	Four		
HOW ARRANGED . . .	Vertically		
CAST . . . . .	En bloc		
HORSEPOWER . . . .	28.9 (N.A.C.C. Rating)		
BORE AND STROKE . .	4¼ x 5¼ inches		
LUBRICATION . . . .	Force feed		
RADIATOR . . . . .	Tubular		
COOLING . . . . .	Water pump		
IGNITION . . . . .	High tension magneto	REAR AXLE . . . .	Full floating
		STEERING GEAR . .	Worm and sector

In addition to above specifications, price includes seat and cushion, front fenders, oil dash lamps and tail lamp, signal horn and complete set of tools including jack.

**INTERNATIONAL  
MOTOR  
COMPANY**  
**MACK BROS.  
MOTOR CAR  
COMPANY**

WEST END AVENUE  
AND 64th STREET  
NEW YORK, N. Y.

Price . . . . .	\$6000
One-and-One-Half-Ton . . . . .	3000
Two-Ton . . . . .	3300
Three-and-One-Half-Ton . . . . .	4950
Five-and-One-Half-Ton . . . . .	5500



**MACK SEVEN-AND-ONE-HALF-TON TRUCK—AC**


COLOR . . . . .	Lead
CARRYING CAPACITY. . . . .	15,000 pounds
POSITION OF DRIVER. . . . .	Left side
WHEELBASE . . . . .	156, 168 or 180 inches
GAUGE . . . . .	Front, 68 inches; rear, 74½ inches
WHEELS . . . . .	Wood
FRONT TIRES . . . . .	36 x 7 inches, single solid
REAR TIRES . . . . .	40 x 7 inches, dual solid
SERVICE BRAKE . . . . .	Contracting on jack shaft
EMERGENCY BRAKE . . . . .	Expanding on rear wheels
CYLINDERS . . . . .	Four
HOW ARRANGED . . . . .	Vertically
CAST . . . . .	In pairs

HORSEPOWER . . . . .	40 (N.A.C.C. Rating)
BORE AND STROKE . . . . .	5 x 6 inches
LUBRICATION . . . . .	Splash with circulating pump
RADIATOR . . . . .	Tubular
COOLING . . . . .	Water pump
IGNITION . . . . .	High tension magneto and impulse starter
GASOLINE SYSTEM . . . . .	Gravity
CLUTCH . . . . .	Dry plate
TRANSMISSION . . . . .	Selective sliding
GEAR CHANGES . . . . .	Three forward, one reverse
DRIVE . . . . .	Double chain
REAR AXLE . . . . .	Dead
STEERING GEAR . . . . .	Worm and gear

# SELDEN TRUCK CORPORATION

ROCHESTER  
NEW YORK

Open or Flare Board Express	} Prices Upon Appli- cation
Standard Platform Stake . . .	
Stake and Rack . . . . .	
Covered Express with Canopy Top and Curtains . . . . .	
Two-and-One-Half-Ton . . . . .	
Three-and-One-Half-Ton . . . . .	
Five-Ton . . . . .	



## SELDEN ONE-AND-ONE-HALF-TON TRUCK

COLOR . . . . .	Body, green; running gear, red	HORSEPOWER . . . . .	22.5 (N.A.C.C. Rating)
CARRYING CAPACITY.	3000 pounds	BORE AND STROKE . . . . .	3 3/4 x 5 inches
POSITION OF DRIVER.	Right side	LUBRICATION . . . . .	Force feed and splash
WHEELBASE . . . . .	140 inches	RADIATOR . . . . .	Cellular
GAUGE . . . . .	Front, 55 inches; rear, 58 inches	COOLING . . . . .	Thermo-syphon
WHEELS . . . . .	Wood	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	35 x 5 inches	GASOLINE SYSTEM . . . . .	Gravity
REAR TIRES . . . . .	36 x 6 inches, anti-skid	CLUTCH . . . . .	Dry plate, multiple disc
SERVICE BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective sliding
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GEAR CHANGES . . . . .	Three forward, one reverse
CYLINDERS . . . . .	Four	DRIVE . . . . .	Worm
HOW ARRANGED . . . . .	Vertically	REAR AXLE . . . . .	Semi-floating
CAST. . . . .	En bloc	STEERING GEAR . . . . .	Worm and nut


In addition to the above specifications, price in-  
cludes horn, oil lamps and complete set of tools.



**S E L D E N  
T R U C K  
C O R P O R A T I O N**  
**R O C H E S T E R  
N E W Y O R K**

Standard Platform Stake . . .  
Steel Dump with Hydraulic  
Hoist . . . . .  
One-and-One-Half-Ton . . . . .  
Two-and-One-Half-Ton . . . . .  
Five-Ton . . . . .

} Prices  
Upon  
Appli-  
cation




**SELDEN THREE-AND-ONE-HALF-TON TRUCK**

COLOR . . . . .	Lead	HORSEPOWER . . . . .	32.4 (N.A.C.C. Rating)
CARRYING CAPACITY. . . . .	7000 pounds	BORE AND STROKE . . . . .	4½ x 5½ inches
POSITION OF DRIVER. . . . .	Right side	LUBRICATION . . . . .	Force feed and splash
WHEELBASE . . . . .	162 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	Front, 66½ inches; rear, 68 inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Wood	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 5 inches, single solid	GASOLINE SYSTEM . . . . .	Gravity
REAR TIRES . . . . .	36 x 10 inches, single solid or 36 x 5 dual solid	CLUTCH . . . . .	Dry plate, multiple disc
SERVICE BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective sliding
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GEAR CHANGES . . . . .	Four forward, one reverse
CYLINDERS . . . . .	Four	DRIVE . . . . .	Worm
HOW ARRANGED . . . . .	Vertically	REAR AXLE . . . . .	Full floating
CAST . . . . .	In pairs	STEERING GEAR . . . . .	Worm and sector

In addition to above specifications, price includes hubodometer, motometer, radiator guard, nickel steel bumper, horn, oil lamp and complete set of tools.

**K I S S E L  
M O T O R C A R  
C O M P A N Y**  
**H A R T F O R D  
W I S C O N S I N**

**General Delivery Truck . . . . .**  
**Freighter Truck . . . . .**  
**Heavy-Duty Truck . . . . .**  
**Goliath Truck . . . . .** } **Prices  
Upon  
Appli-  
cation**




---

**KISSEL GENERAL UTILITY TRUCK**

---

<b>COLOR . . . . .</b>	Gray lead	<b>HORSEPOWER . . . . .</b>	24.03 (N.A.C.C. Rating)
<b>CARRYING CAPACITY. . . . .</b>	3000 pounds	<b>BORE AND STROKE . . . . .</b>	3 $\frac{1}{4}$ x 5 $\frac{1}{4}$ inches
<b>POSITION OF DRIVER. . . . .</b>	Left side	<b>LUBRICATION . . . . .</b>	Splash with circulating pump
<b>WHEELBASE . . . . .</b>	152 inches	<b>RADIATOR . . . . .</b>	Tubular
<b>GAUGE . . . . .</b>	57 $\frac{1}{2}$ inches, rear	<b>COOLING . . . . .</b>	Water pump
<b>WHEELS . . . . .</b>	Wood	<b>IGNITION . . . . .</b>	High tension magneto
<b>FRONT TIRES . . . . .</b>	36 x 3 $\frac{1}{4}$ inches, single solid	<b>GASOLINE SYSTEM . . . . .</b>	Vacuum
<b>REAR TIRES . . . . .</b>	36 x 5 inches, single solid	<b>CLUTCH . . . . .</b>	Dry multiple disc
<b>SERVICE BRAKE . . . . .</b>	Expanding on rear wheels	<b>TRANSMISSION . . . . .</b>	Selective sliding
<b>EMERGENCY BRAKE . . . . .</b>	Expanding on rear wheels	<b>GEAR CHANGES . . . . .</b>	Three forward, one reverse
<b>CYLINDERS . . . . .</b>	Four	<b>DRIVE . . . . .</b>	Worm
<b>HOW ARRANGED . . . . .</b>	Vertically	<b>REAR AXLE . . . . .</b>	Semi-floating
<b>CAST . . . . .</b>	Four, en bloc	<b>STEERING GEAR . . . . .</b>	Screw and split nut


In addition to above specifications, price includes  
all year open cab, horn, lamps, jack and tools.

**K I S S E L  
M O T O R C A R  
C O M P A N Y**  

---

**H A R T F O R D  
W I S C O N S I N**

**General Delivery Truck . . . . .**  
**General Utility Truck . . . . .**  
**Heavy-Duty Truck . . . . .**  
**Goliath Truck . . . . .** } **Prices  
Upon  
Appli-  
cation**




---

**K I S S E L F R E I G H T E R T R U C K**


---

<b>COLOR . . . . .</b>	Gray lead	<b>HORSEPOWER . . . . .</b>	28.9 (N.A.C.C. Rating)
<b>CARRYING CAPACITY. . . . .</b>	5000 pounds	<b>BORE AND STROKE . . . . .</b>	4¼ x 5½ inches
<b>POSITION OF DRIVER. . . . .</b>	Left side	<b>LUBRICATION . . . . .</b>	Splash with circulating pump
<b>WHEELBASE . . . . .</b>	168 inches	<b>RADIATOR . . . . .</b>	Tubular
<b>GAUGE . . . . .</b>	57¼ inches, rear	<b>COOLING . . . . .</b>	Water pump
<b>WHEELS . . . . .</b>	Wood	<b>IGNITION . . . . .</b>	High tension magneto
<b>FRONT TIRES . . . . .</b>	36 x 4 inches, single solid	<b>GASOLINE SYSTEM . . . . .</b>	Vacuum
<b>REAR TIRES . . . . .</b>	36 x 7 inches, single solid	<b>CLUTCH . . . . .</b>	Dry multiple disc
<b>SERVICE BRAKE . . . . .</b>	Expanding on rear wheels	<b>TRANSMISSION . . . . .</b>	Selective sliding
<b>EMERGENCY BRAKE . . . . .</b>	Expanding on rear wheels	<b>GEAR CHANGES . . . . .</b>	Four forward, one reverse
<b>CYLINDERS . . . . .</b>	Four	<b>DRIVE . . . . .</b>	Worm
<b>HOW ARRANGED . . . . .</b>	Vertically	<b>REAR AXLE . . . . .</b>	Full floating
<b>CAST . . . . .</b>	Four, en bloc	<b>STEERING GEAR . . . . .</b>	Screw and split nut

In addition to above specifications, price includes all-year open cab, top, horn, lamps, bumper, jack and tools

**K I S S E L  
M O T O R C A R  
C O M P A N Y**  
H A R T F O R D  
W I S C O N S I N

General Delivery Truck . . . } Prices  
General Utility Truck . . . } Upon  
Freighter Truck . . . } Appli-  
Goliath Truck . . . } cation



### KISSEL HEAVY-DUTY TRUCK


COLOR . . . . .	Gray lead	HORSEPOWER . . . . .	28.9 (N.A.C.C. Rating)
CARRYING CAPACITY. . . . .	7000 pounds	BORE AND STROKE . . . . .	4 3/4 x 5 1/2 inches
POSITION OF DRIVER. . . . .	Left side	LUBRICATION . . . . .	Splash with circulating pump
WHEELBASE . . . . .	168 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	66 inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Wood	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 5 inches, single solid	GASOLINE SYSTEM . . . . .	Vacuum
REAR TIRES . . . . .	36 x 5 inches, dual solid	CLUTCH . . . . .	Dry multiple disc
SERVICE BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective sliding
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GEAR CHANGES . . . . .	Four forward, one reverse
CYLINDERS . . . . .	Four	DRIVE . . . . .	Worm
HOW ARRANGED . . . . .	Vertically	REAR AXLE . . . . .	Semi-floating
CAST . . . . .	Four, en bloc	STEERING GEAR . . . . .	Worm and nut

In addition to above specifications, price includes all-year open cab, horn, bumper, lamps, jack and tools.

# VELIE MOTORS CORPORATION

M O L I N E  
I L L I N O I S


Price, Chassis . . . . . \$3900  
One-and-One-Half-Ton Chassis. 1925



## VELIE THREE-AND-ONE-HALF-TON TRUCK—26-B

COLOR . . . . .	Body, optional; running gear, lead	CAST . . . . .	In pairs
CARRYING CAPACITY. . . . .	7000 pounds	HORSEPOWER . . . . .	32.4 (N.A.C.C. Rating)
POSITION OF DRIVER. . . . .	Left side	BORE AND STROKE . . . . .	4½ x 5½ inches
WHEELBASE . . . . .	148 or 172 inches	LUBRICATION . . . . .	Pump over and splash
GAUGE . . . . .	Front, 62 inches; rear, 64 inches	RADIATOR . . . . .	Tubular
WHEELS . . . . .	Wood	COOLING . . . . .	Water pump
FRONT TIRES . . . . .	36 x 5 inches, single solid	IGNITION . . . . .	High tension magneto
REAR TIRES . . . . .	36 x 5 inches, dual solid	GASOLINE SYSTEM . . . . .	Vacuum
SERVICE BRAKE . . . . .	Expanding on rear wheels	CLUTCH . . . . .	Dry disc
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective sliding
CYLINDERS . . . . .	Four	GEAR CHANGES . . . . .	Four forward, one reverse
HOW ARRANGED . . . . .	Vertically	DRIVE . . . . .	Worm
		REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes  
cab, top, bumper, odometer, lamps, tools and horn.




---

**GARFORD ONE-AND-ONE-QUARTER-TON TRUCK—25**


---

<b>COLOR</b> . . . . .	Lead or Garford brown	<b>HORSEPOWER</b> . . . . .	22.5 (N.A.C.C. Rating)
<b>CARRYING CAPACITY.</b>	2500 pounds	<b>BORE AND STROKE</b> . . . . .	3 $\frac{3}{4}$ x 5 $\frac{1}{4}$ inches
<b>POSITION OF DRIVER.</b>	Left side	<b>LUBRICATION</b> . . . . .	Splash with circulating pump
<b>WHEELBASE</b> . . . . .	135 inches	<b>RADIATOR</b> . . . . .	Tubular
<b>GAUGE</b> . . . . .	Front, 56 inches; rear, 58 inches	<b>COOLING</b> . . . . .	Water pump
<b>WHEELS</b> . . . . .	Wood	<b>IGNITION</b> . . . . .	High tension magneto
<b>FRONT TIRES</b> . . . . .	36 x 3 $\frac{3}{4}$ inches, single solid	<b>LIGHTING SYSTEM</b> . . . . .	Oil
<b>REAR TIRES</b> . . . . .	36 x 4 inches, single solid	<b>WIRING SYSTEM</b> . . . . .	Single
<b>SERVICE BRAKE</b> . . . . .	Expanding in rear wheels	<b>GASOLINE SYSTEM</b> . . . . .	Gravity
<b>EMERGENCY BRAKE</b> . . . . .	Expanding in rear wheels	<b>CLUTCH</b> . . . . .	Dry multiple disc
<b>CYLINDERS</b> . . . . .	Four	<b>TRANSMISSION</b> . . . . .	Selective sliding
<b>HOW ARRANGED</b> . . . . .	Vertically	<b>GEAR CHANGES</b> . . . . .	Three forward, one reverse
<b>CAST</b> . . . . .	En bloc	<b>DRIVE</b> . . . . .	Worm
		<b>REAR AXLE</b> . . . . .	Semi-floating
		<b>STEERING GEAR</b> . . . . .	Screw and nut

---

**GARFORD  
MOTOR TRUCK  
COMPANY**  
**LIMA, OHIO**

**Price, Chassis, \$3190**




---

**GARFORD TWO-TON TRUCK—70-H**

---

COLOR . . . . .	Lead or Garford brown	HORSEPOWER . . . . .	28.9 (N.A.C.C. Rating)
CARRYING CAPACITY.	4000 pounds	BORE AND STROKE . . . . .	4¼ x 5½ inches
POSITION OF DRIVER.	Left side	LUBRICATION . . . . .	Force feed
WHEELBASE . . . . .	144 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	Front, 58½ inches; rear, 59¾ inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Wood	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 4 inches, single solid	GASOLINE SYSTEM . . . . .	Gravity
REAR TIRES . . . . .	36 x 7 inches, single solid	CLUTCH . . . . .	Dry multiple disc
SERVICE BRAKE . . . . .	Expanding in rear wheels	TRANSMISSION . . . . .	Selective sliding
EMERGENCY BRAKE . . . . .	Expanding in rear wheels	GEAR CHANGES . . . . .	Four forward, one reverse
CYLINDERS . . . . .	Four	DRIVE . . . . .	Worm
HOW ARRANGED . . . . .	Vertically	REAR AXLE . . . . .	Full floating
CAST . . . . .	En bloc	STEERING GEAR . . . . .	Screw and nut


---

**G A R F O R D**  
**M O T O R T R U C K**  
**C O M P A N Y**  


---

**L I M A , O H I O**

**Price, Chassis, \$4190**




---


**G A R F O R D T H R E E - A N D - O N E - H A L F - T O N T R U C K — 7 7 - D**

---

COLOR . . . . .	Lead or Garford brown	HORSEPOWER . . . . .	32.4 (N.A.C.C. Rating)
CARRYING CAPACITY.	7000 pounds	BORE AND STROKE . . . .	4½ x 6 inches
POSITION OF DRIVER.	Left side	LUBRICATION . . . . .	Force feed
WHEELBASE . . . . .	162 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	Front, 67 inches; rear, 65¾ inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Steel	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 5 inches, single solid	LIGHTING SYSTEM . . . .	Oil
REAR TIRES . . . . .	36 x 5 inches, dual solid	GASOLINE SYSTEM . . . .	Gravity
SERVICE BRAKE . . . .	Expanding in rear wheels	CLUTCH . . . . .	Dry multiple disc
EMERGENCY BRAKE . .	Expanding in rear wheels	TRANSMISSION . . . . .	Selective sliding
CYLINDERS . . . . .	Four	GEAR CHANGES . . . .	Four forward, one reverse
HOW ARRANGED . . . .	Vertically	DRIVE . . . . .	Worm
CAST . . . . .	En bloc	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . .	Screw and nut

---






---

**GARFORD FIVE-TON TRUCK—68**

---


COLOR . . . . .	Lead or Garford brown	HORSEPOWER . . . . .	36.1 (N.A.C.C. Rating)
CARRYING CAPACITY.	10,000 pounds	BORE AND STROKE . . . . .	4¾ x 5½ inches
POSITION OF DRIVER.	Right side	LUBRICATION . . . . .	Force feed
WHEELBASE . . . . .	128 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	Front, 67½ inches; rear, 71 inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Steel	IGNITION . . . . .	High tension magneto and dry cells
FRONT TIRES . . . . .	36 x 6 inches, single solid	LIGHTING SYSTEM . . . . .	Oil
REAR TIRES . . . . .	40 x 6 inches, dual solid	GASOLINE SYSTEM . . . . .	Gravity
SERVICE BRAKE . . . . .	Contracting on transmission	CLUTCH . . . . .	Dry multiple disc
EMERGENCY BRAKE . . . . .	Expanding in rear wheels	TRANSMISSION . . . . .	Selective sliding
CYLINDERS . . . . .	Four	GEAR CHANGES . . . . .	Four forward, one reverse
HOW ARRANGED . . . . .	Vertically	DRIVE . . . . .	Chain drive
CAST . . . . .	In pairs	REAR AXLE . . . . .	Rectangular solid
		STEERING GEAR . . . . .	Screw and nut

---

**KLEIBER &  
COMPANY  
INCORPORATED**

**SAN FRANCISCO  
CALIFORNIA**

<b>Price, Chassis</b> . . . . .	<b>\$3800</b>
<b>One-Ton</b> . . . . .	<b>2400</b>
<b>One-and-One-Half-Ton</b> . . . . .	<b>2800</b>
<b>Two-Ton</b> . . . . .	<b>3200</b>
<b>Three-and-One-Half-Ton</b> . . . . .	<b>4400</b>
<b>Five-Ton</b> . . . . .	<b>5300</b>



**KLEIBER TWO-AND-ONE-HALF-TON TRUCK—B**


<b>COLOR</b> . . . . .	Body, Brewster green; running gear, vermillion	<b>HORSEPOWER</b> . . . . .	32.4 (N.A.C.C. Rating)
<b>CARRYING CAPACITY.</b>	5000 pounds	<b>BORE AND STROKE</b> . . . . .	4½ x 5½ inches
<b>POSITION OF DRIVER.</b>	Right side	<b>LUBRICATION</b> . . . . .	Splash with circulating pump
<b>WHEELBASE</b> . . . . .	160 inches	<b>RADIATOR</b> . . . . .	Tubular
<b>GAUGE</b> . . . . .	60 inches	<b>COOLING</b> . . . . .	Water pump
<b>WHEELS</b> . . . . .	Wood	<b>IGNITION</b> . . . . .	High tension magneto
<b>FRONT TIRES</b> . . . . .	36 x 5 inches, single solid	<b>LIGHTING SYSTEM</b> . . . . .	Oi
<b>REAR TIRES</b> . . . . .	36 x 8 inches, single solid	<b>WIRING SYSTEM</b> . . . . .	Single
<b>SERVICE BRAKE</b> . . . . .	Expanding on rear wheel drum	<b>GASOLINE SYSTEM</b> . . . . .	Gravity
<b>EMERGENCY BRAKE</b> . . . . .	Expanding on rear wheel drum	<b>CLUTCH</b> . . . . .	Multiple disc in oil
<b>CYLINDERS</b> . . . . .	Four	<b>TRANSMISSION</b> . . . . .	Selective sliding
<b>HOW ARRANGED</b> . . . . .	Vertically	<b>GEAR CHANGES</b> . . . . .	Four forward, one reverse
<b>CAST</b> . . . . .	In pairs	<b>DRIVE</b> . . . . .	Worm
		<b>REAR AXLE</b> . . . . .	Full floating
		<b>STEERING GEAR</b> . . . . .	Screw and nut

In addition to above specifications, price includes hubodometer.

**CORBITT  
MOTOR TRUCK  
COMPANY**

**HENDERSON  
NORTH CAROLINA**

**Price, Chassis . . . . \$3500**  
**Cab . . . . . 3560**  
**Cab and Windshield . 3575**




---

**CORBITT TWO-AND-ONE-HALF-TON TRUCK—B**

---


<b>COLOR . . . . .</b>	Battleship gray or red	<b>BORE AND STROKE . .</b>	4¼ x 5¼ inches
<b>CARRYING CAPACITY</b>	5000 pounds	<b>LUBRICATION . . . .</b>	Force feed and splash
<b>POSITION OF DRIVER</b>	Left side	<b>RADIATOR . . . . .</b>	Tubular
<b>WHEELBASE . . . .</b>	148 inches	<b>COOLING . . . . .</b>	Water pump
<b>GAUGE . . . . .</b>	62 inches	<b>IGNITION . . . . .</b>	High tension magneto
<b>WHEELS . . . . .</b>	Wood	<b>LIGHTING SYSTEM . .</b>	Gas
<b>FRONT TIRES . . . .</b>	36 x 4 inches, single solid	<b>WIRING SYSTEM . . .</b>	Single
<b>REAR TIRES . . . .</b>	36 x 4 inches, dual solid	<b>GASOLINE SYSTEM . .</b>	Vacuum
<b>SERVICE BRAKE . .</b>	Expanding on rear wheels	<b>CLUTCH . . . . .</b>	Dry multiple disc
<b>EMERGENCY BRAKE .</b>	Expanding on rear wheels	<b>TRANSMISSION . . .</b>	Selective sliding
<b>CYLINDERS . . . . .</b>	Four	<b>GEAR CHANGES . . .</b>	Four forward, one reverse
<b>HOW ARRANGED . .</b>	Vertically	<b>DRIVE . . . . .</b>	Worm
<b>CAST . . . . .</b>	En bloc	<b>REAR AXLE . . . . .</b>	Semi-floating
<b>HORSEPOWER . . . .</b>	27.23 (N.A.C.C. Rating)	<b>STEERING GEAR . . .</b>	Worm and nut

---

# DUPLEX TRUCK COMPANY

LANSING  
MICHIGAN

Price, Chassis, \$2575




## DUPLEX LIMITED—MODEL A

COLOR . . . . .	Body, Duplex lake red; running gear, black	BORE AND STROKE . . . . .	4 x 5 1/4 inches
CARRYING CAPACITY.	3000 pounds	LUBRICATION . . . . .	Force feed and splash
POSITION OF DRIVER.	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	145 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	Front, 55 3/4 inches; rear, 57 inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	35 x 5 inches, pneumatic cord, anti-skid	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	38 x 7 inches, pneumatic cord, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Expanding on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Four	GASOLINE SYSTEM . . . . .	Gravity
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry multiple disc
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	25.6	GEAR CHANGES . . . . .	Three forward, one reverse
(N.A.C.C. Rating)		DRIVE . . . . .	Worm
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and nut

In addition to above specifications, price includes windshield, speedometer, ammeter, electric horn and seat.

**D U P L E X  
T R U C K  
C O M P A N Y**  
L A N S I N G  
M I C H I G A N

**Price, Chassis, \$4000**



**DUPLEX 4-WHEEL DRIVE THREE-AND-ONE-HALF-TON TRUCK—E**


COLOR . . . . .	Chassis, gray; wheels, red	BORE AND STROKE .	4¼ x 5½ inches
CARRYING CAPACITY.	7000 pounds	LUBRICATION . . . .	Force feed and splash
POSITION OF DRIVER.	Left side	RADIATOR . . . . .	Tubular
WHEELBASE . . . . .	130 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	60 inches	IGNITION . . . . .	High tension magneto
WHEELS . . . . .	Wood	LIGHTING SYSTEM .	Gas
FRONT TIRES . . . .	36 x 6 inches, single solid	GASOLINE SYSTEM .	Vacuum
REAR TIRES . . . . .	36 x 6 inches, single solid	CLUTCH . . . . .	Dry multiple disc
SERVICE BRAKE . . .	Contracting on chain case drum	TRANSMISSION . . .	Selective sliding
EMERGENCY BRAKE .	Contracting on rear wheels	GEAR CHANGES . .	Four forward, one reverse
CYLINDERS . . . . .	Four	DRIVE . . . . .	Plain bevel and spur gear
HOW ARRANGED . . .	Vertically	REAR AXLE . . . . .	Dead axle with live shaft removable
CAST . . . . .	En bloc	STEERING GEAR . . .	Worm and block
HORSEPOWER . . . .	28.9 (N.A.C.C. Rating)		

In addition to above specifications, price includes cab and seat, speedometer and horn

**ATTERBURY  
MOTOR CAR  
COMPANY**

**B U F F A L O  
N E W Y O R K**

Price . . . . .	\$3975
One-and-One-Half-Ton—7R . . . . .	2575
Two-and-One-Half-Ton—7CX . . . . .	3175
Two-and-One-Half-Ton—7CX, Long Wheelbase . . . . .	3275
Three-and-One-Half-Ton—7D Long Wheelbase . . . . .	4075
Five-Ton—8E . . . . .	5475



**ATTERBURY THREE-AND-ONE-HALF-TON TRUCK—7-D**

COLOR . . . . .	Battleship gray	HORSEPOWER . . . . .	32.4 (N.A.C.C. Rating)
CARRYING CAPACITY. . . . .	7000 pounds	BORE AND STROKE . . . . .	4½ x 5½ inches
POSITION OF DRIVER. . . . .	Right side	LUBRICATION . . . . .	Splash with circulating pump
WHEELBASE . . . . .	167½ inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	Front, 66 inches; rear, 67¼ inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Wood	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 5 inches, single solid	GASOLINE SYSTEM . . . . .	Gravity
REAR TIRES . . . . .	40 x 5 inches, dual solid	CLUTCH . . . . .	Dry plate, multiple disc
SERVICE BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective sliding
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GEAR CHANGES . . . . .	Four forward, one reverse
CYLINDERS . . . . .	Four	DRIVE . . . . .	Worm
HOW ARRANGED . . . . .	Vertically	REAR AXLE . . . . .	Full floating
CAST . . . . .	In pairs	STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes cab, full set of curtains, two side and one tail oil lamp, horn, jack, set of tools and tool box.

# INTERNATIONAL HARVESTER COMPANY

CHICAGO  
ILLINOIS

Three-Quarter-Ton . . . . .	} Prices Upon Application
One-Ton . . . . .	
One and One-Half-Ton . . . . .	
Three and One-Half-Ton . . . . .	



## INTERNATIONAL TWO-TON TRUCK—G

COLOR . . . . .	Body, dark green; running gear, red	LUBRICATION . . . . .	Splash with circulating pump
CARRYING CAPACITY.	4000 pounds	RADIATOR . . . . .	Tubular
POSITION OF DRIVER.	Left side	COOLING . . . . .	Thermo-syphon
WHEELBASE . . . . .	138 inches	IGNITION . . . . .	High tension magneto
GAUGE . . . . .	61 inches	LIGHTING SYSTEM . .	Gas
WHEELS . . . . .	Wood	WIRING SYSTEM . . .	Single
FRONT TIRES . . . .	36 x 4 inches, single solid	GASOLINE SYSTEM . .	Vacuum
REAR TIRES . . . . .	36 x 6 inches, single solid	CLUTCH . . . . .	Dry multiple disc
SERVICE BRAKE . . .	Expanding on rear wheels	TRANSMISSION . . . .	Selective sliding
EMERGENCY BRAKE . .	Expanding on rear wheels	GEAR CHANGES . . .	Three forward, one reverse
CYLINDERS . . . . .	Four	DRIVE . . . . .	Internal gear and plain bevel
HOW ARRANGED . . .	Vertically	REAR AXLE . . . . .	Live axle for transmitting power; dead axle for carrying load
CAST . . . . .	En bloc	STEERING GEAR . . .	Worm and gear
HORSEPOWER . . . .	25.6 (N.A.C.C. Rating)		
BORE AND STROKE . .	4 x 5 inches		

**ROWE MOTOR  
MANUFACTURING  
COMPANY**  

---

**LANCASTER  
PENNSYLVANIA**

**Price, Chassis . . . . . \$4500**  
**With Cab . . . . . 4600**  
**With 30-Passenger Bus Body . . 5500**



**ROWE THREE-TON HIGH-SPEED PNEUMATIC-TIRED TRUCK—GW**

COLOR . . . . .	Chassis, red; cab, seat box hood and fenders, green	BORE AND STROKE . . . . .	3¼ x 5 inches
CARRYING CAPACITY.	6000 pounds	LUBRICATION . . . . .	Force feed
POSITION OF DRIVER.	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	170 inches	COOLING . . . . .	Water pump
GAUGE . . . . .	60½ inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Front, wood; rear, steel	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	38 x 7 inches, pneumatic, anti-skid	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	42 x 9 inches, pneumatic, anti-skid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	Expanding on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Eight	GASOLINE SYSTEM . . . . .	Vacuum
HOW ARRANGED . . . . .	V type, 90 degrees	CLUTCH . . . . .	Dry plate, multiple disc
CAST . . . . .	Four en bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	33.8 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Four forward, one reverse
		DRIVE . . . . .	Worm
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and nut


In addition to above specifications, price includes ammeter, tire pump, electric horn and demountable rims.



# UNITED MOTORS COMPANY

GRAND RAPIDS  
MICHIGAN

Price Upon Application




## UNITED FIVE-TON TRUCK—V

COLOR . . . . .	Red	HORSEPOWER . . . . .	28.9 (N.A.C.C. Rating)
CARRYING CAPACITY.	10,000 pounds	BORE AND STROKE . . . . .	4½ x 6 inches
POSITION OF DRIVER.	Optional	LUBRICATION . . . . .	Full force feed
WHEELBASE . . . . .	166 or 185 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	66 inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Cast steel	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 5 inches, single solid	LIGHTING SYSTEM . . . . .	Oil
REAR TIRES . . . . .	40 x 6 inches, dual solid	GASOLINE SYSTEM . . . . .	Gravity
SERVICE BRAKE . . . . .	Expanding on rear axle	CLUTCH . . . . .	Dry multiple disc
EMERGENCY BRAKE . . . . .	Contracting on rear axle	TRANSMISSION . . . . .	Selective sliding
CYLINDERS . . . . .	Four	GEAR CHANGES . . . . .	Four forward, one reverse
HOW ARRANGED . . . . .	Vertically	DRIVE . . . . .	Internal gear
CAST . . . . .	En bloc	REAR AXLE . . . . .	Dead
		STEERING GEAR . . . . .	Worm and nut

In addition to above specifications, price includes ammeter and horn.

**COMMERCE  
MOTOR CAR  
COMPANY**  
DETROIT  
MICHIGAN

Price . . . . .	\$2030
With Covered Express—EPH . . . . .	2095
With Stake Body—EPS . . . . .	2120
With Everyway Body—EPF . . . . .	2190
With Dump Body—EPD . . . . .	2390
Chassis—EP . . . . .	1965



**COMMERCE ONE-AND-ONE-HALF—TWO-TON TRUCK—EPA**


COLOR . . . . .	Orange and black	BORE AND STROKE . . . . .	3¼ x 5 inches
CARRYING CAPACITY. . . . .	3000-4000 pounds	LUBRICATION . . . . .	Splash with circulating pump
POSITION OF DRIVER. . . . .	Left side	RADIATOR . . . . .	Tubular cast tanks
WHEELBASE . . . . .	134 inches	COOLING . . . . .	Thermo-syphon
GAUGE . . . . .	56 inches	IGNITION . . . . .	High tension magneto
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Impulse starter
FRONT TIRES . . . . .	36 x 6 inches, pneumatic, non-skid	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	36 x 6 inches, pneumatic, non-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Contracting on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Four	CLUTCH . . . . .	Cone
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
HORSEPOWER . . . . .	22.5 (N.A.C.C. Rating)	DRIVE . . . . .	Internal gear
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and nut

In addition to above specifications, price includes windshield, ammeter, voltmeter, horn, electric lights, bumper and spotlight

**STEWART  
MOTOR  
CORPORATION**

**BUFFALO  
NEW YORK**

Price, Chassis . . . . .	\$3500
With Stake Platform Body . . .	3990
With Steel Coal Dump with Hydraulic Hoist . . . . .	4225
1500-Pound . . . . .	1195
2000-Pound . . . . .	1650
3000-Pound . . . . .	1975
4000-Pound . . . . .	2575




**STEWART THREE-AND-ONE-HALF-TON TRUCK—10**

COLOR . . . . .	Stewart red	CAST . . . . .	In pairs
CARRYING CAPACITY. . . . .	7000 pounds	HORSEPOWER . . . . .	32.4 (N.A.C.C. Rating)
POSITION OF DRIVER. . . . .	Left side	BORE AND STROKE . . . . .	4½ x 5½ inches
WHEELBASE . . . . .	165 or 185 inches	LUBRICATION . . . . .	Force feed and splash
GAUGE . . . . .	Front, 58 inches; rear, 70 inches	RADIATOR . . . . .	Tubular
WHEELS . . . . .	Steel	COOLING . . . . .	Water pump
FRONT TIRES . . . . .	36 x 5 inches, single solid	IGNITION . . . . .	High tension magneto
REAR TIRES . . . . .	36 x 5 inches, dual solid	GASOLINE SYSTEM . . . . .	Gravity
SERVICE BRAKE . . . . .	Contracting on rear wheels	CLUTCH . . . . .	Dry multiple disc
EMERGENCY BRAKE . . . . .	Contracting on drive shaft at rear of transmission	TRANSMISSION . . . . .	Selective sliding
CYLINDERS . . . . .	Four	GEAR CHANGES . . . . .	Four forward, one reverse
HOW ARRANGED . . . . .	Vertically	DRIVE . . . . .	Internal gear
		REAR AXLE . . . . .	Internal gear
		STEERING GEAR . . . . .	Worm and nut

In addition to above specifications, price includes seat, seat box and cowl complete, horn, side and tail lights, jack, tool box and tool kit.

**PAIGE-DETROIT  
MOTOR CAR  
COMPANY**  
**DETROIT  
MICHIGAN**


Price Upon Application



**PAIGE TWO-AND-ONE-HALF-TON TRUCK—50-18**

COLOR . . . . .	Chassis, red	HORSEPOWER . . . . .	27.23 (N.A.C.C. Rating)
CARRYING CAPACITY. . . . .	5000 pounds	BORE AND STROKE . . . . .	4½ x 5¼ inches
POSITION OF DRIVER. . . . .	Left side	LUBRICATION . . . . .	Splash with circulating pump
WHEELBASE . . . . .	150 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	58½ inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Wood or steel	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 4 inches, single solid	LIGHTING SYSTEM . . . . .	Oil
REAR TIRES . . . . .	36 x 7 inches, single solid	GASOLINE SYSTEM . . . . .	Gravity
SERVICE BRAKE . . . . .	Expanding on rear wheels	CLUTCH . . . . .	Dry multiple disc
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective sliding
CYLINDERS . . . . .	Four	GEAR CHANGES . . . . .	Four forward, one reverse
HOW ARRANGED . . . . .	Vertically	DRIVE . . . . .	Worm
CAST . . . . .	En bloc	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Screw and nut

In addition to above specifications, price includes cab, windshield, odometer and horn.



### **PAIGE THREE-AND-ONE-HALF-TON TRUCK—51-18**


<b>COLOR</b> . . . . .	Chassis, red	<b>HORSEPOWER</b> . . . . .	32.4 (N.A.C.C. Rating)
<b>CARRYING CAPACITY.</b>	7000 pounds	<b>BORE AND STROKE</b> . . . . .	4½ x 5½ inches
<b>POSITION OF DRIVER.</b>	Left side	<b>LUBRICATION</b> . . . . .	Splash with circulating pump
<b>WHEELBASE</b> . . . . .	160 inches	<b>RADIATOR</b> . . . . .	Tubular
<b>GAUGE</b> . . . . .	Front, 66½ inches; rear, 65¼ inches	<b>COOLING</b> . . . . .	Water pump
<b>WHEELS</b> . . . . .	Steel	<b>IGNITION</b> . . . . .	High tension magneto
<b>FRONT TIRES</b> . . . . .	36 x 5 inches, single solid	<b>LIGHTING SYSTEM</b> . . . . .	Oil
<b>REAR TIRES</b> . . . . .	36 x 5 inches, dual solid	<b>GASOLINE SYSTEM</b> . . . . .	Gravity
<b>SERVICE BRAKE</b> . . . . .	Expanding on rear wheels	<b>CLUTCH</b> . . . . .	Dry multiple disc
<b>EMERGENCY BRAKE</b> . . . . .	Expanding on rear wheels	<b>TRANSMISSION</b> . . . . .	Selective sliding
<b>CYLINDERS</b> . . . . .	Four	<b>GEAR CHANGES</b> . . . . .	Four forward, one reverse
<b>HOW ARRANGED</b> . . . . .	Vertically	<b>DRIVE</b> . . . . .	Worm
<b>CAST</b> . . . . .	In pairs	<b>REAR AXLE</b> . . . . .	Full floating
		<b>STEERING GEAR</b> . . . . .	Screw and nut

In addition to above specifications, price includes  
cab, top hood, windshield, odometer and horn

# JACKSON MOTORS CORPORATION

JACKSON  
MICHIGAN

Price, \$4250



## JACKSON THREE-AND-ONE-HALF-TON TRUCK—B


COLOR . . . . .	Chassis, gray	LUBRICATION . . . . .	Force feed and splash
CARRYING CAPACITY. . . . .	7000 pounds	RADIATOR . . . . .	Tubular
POSITION OF DRIVER. . . . .	Right side	COOLING . . . . .	Water pump
WHEELBASE . . . . .	150 inches	IGNITION . . . . .	High tension magneto
GAUGE . . . . .	58 inches	STARTING SYSTEM . . . . .	Single unit
WHEELS . . . . .	Wood	STARTER OPERATED . . . . .	Gear to fly wheel
FRONT TIRES . . . . .	36 x 7 inches, single solid	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	36 x 7 inches, single solid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Contracting on transmission	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Four	CLUTCH . . . . .	Dry multiple disc
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	In pairs	GEAR CHANGES . . . . .	Four forward, one reverse
HORSEPOWER . . . . .	32.4 (N.A.C.C. Rating)	DRIVE . . . . .	Plain bevel
BORE AND STROKE . . . . .	4½ x 5½ inches	REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Screw and nut

In addition to above specifications, price includes cab, speedometer, ammeter and electric horn.

# DORRIS MOTOR CAR COMPANY

ST. LOUIS  
MISSOURI

Price, Chassis, \$3285




## DORRIS TWO—TWO-AND-ONE-HALF-TON TRUCK—K-4

COLOR . . . . .	Lead	HORSEPOWER . . . . .	28.90 (N.A.C.C. Rating)
CARRYING CAPACITY.	4000-5000 pounds	BORE AND STROKE . . . . .	4¼ x 5½ inches
POSITION OF DRIVER.	Left side	LUBRICATION . . . . .	Full force feed
WHEELBASE . . . . .	144 or 162 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	58½ inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Steel	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 4 inches, single solid	GASOLINE SYSTEM . . . . .	Gravity
REAR TIRES . . . . .	36 x 7 inches, single solid	CLUTCH . . . . .	Dry multiple disc
SERVICE BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective sliding
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GEAR CHANGES . . . . .	Four forward, one reverse
CYLINDERS . . . . .	Four	DRIVE . . . . .	Worm
HOW ARRANGED . . . . .	Vertically	REAR AXLE . . . . .	Full floating
CAST . . . . .	En bloc	STEERING GEAR . . . . .	Screw and nut

In addition to above specifications, price includes oil side and tail lights, horn, speedometer, complete set of tools and jack, tool box and driver's seat with spring cushion.

**FEDERAL  
MOTOR TRUCK  
COMPANY**  
DETROIT  
MICHIGAN

Price, Chassis . . . . .	\$2300
One-and-One-Half-Ton Chassis . . . . .	2500
Two-Ton Chassis . . . . .	2800
Three-and-One-Half-Ton Chassis . . . . .	3650
Five-Ton Chassis . . . . .	4500




---

**FEDERAL ONE-TON TRUCK—SD**

---


COLOR . . . . .	Lead	HORSEPOWER . . . . .	22.5 (N.A.C.C. Rating)
CARRYING CAPACITY. . . . .	2000 pounds	BORE AND STROKE . . . . .	3 $\frac{3}{4}$ x 5 inches
POSITION OF DRIVER. . . . .	Left side	LUBRICATION . . . . .	Force feed
WHEELBASE . . . . .	132 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	56 inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Steel disc	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	35 x 5 inches, pneumatic, anti-skid	LIGHTING SYSTEM . . . . .	Electric
REAR TIRES . . . . .	36 x 6 inches, pneumatic, anti-skid	VOLTAGE . . . . .	Six
SERVICE BRAKE . . . . .	Expanding on rear wheels	WIRING SYSTEM . . . . .	Single
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
CYLINDERS . . . . .	Four	CLUTCH . . . . .	Dry plate
HOW ARRANGED . . . . .	Vertically	TRANSMISSION . . . . .	Selective sliding
CAST . . . . .	En bloc	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Worm
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and gear

In addition to above specifications, price includes tire pump, horn, electric side and tail lights, jack, tool box and complete set of tools.



**FEDERAL  
MOTOR TRUCK  
COMPANY**  
DETROIT  
MICHIGAN

Stake, Express, Farm, Dump,  
Combination Dump and Plat-  
form, Tank, Flushing, Sprink-  
ling, Fire, Van and others special  
bodies . . . . . } Prices  
Upon Appli-  
cation



**FEDERAL THREE-AND-ONE-HALF-TON TRUCK—WD**


COLOR . . . . .	Lead	HORSEPOWER . . . . .	32.4 (N.A.C.C. Rating)
CARRYING CAPACITY.	7000 pounds	BORE AND STROKE . . . . .	4½ x 5½ inches
POSITION OF DRIVER.	Left side	LUBRICATION . . . . .	Splash with circulating pump
WHEELBASE . . . . .	156 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	Front, 66½ inches; rear, 67¾ inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Hollow steel spoke type	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 5 inches, single solid	GASOLINE SYSTEM . . . . .	Gravity
REAR TIRES . . . . .	36 x 5 inches, dual solid	CLUTCH . . . . .	Dry plate
SERVICE BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective sliding
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GEAR CHANGES . . . . .	Four forward, one reverse
CYLINDERS . . . . .	Four	DRIVE . . . . .	Worm
HOW ARRANGED . . . . .	Vertically	REAR AXLE . . . . .	Full floating
CAST . . . . .	In pairs	STEERING GEAR . . . . .	Worm and gear

In addition to above specifications price includes horn, three  
oil lamps, grease gun, tool box and complete set of tools.

**O N E I D A  
MOTOR TRUCK  
C O M P A N Y**

**GREEN BAY  
WISCONSIN**

Price, Chassis . . . . .	\$2385
One-and-One-Quarter-Ton . . . . .	1985
Two-and-One-Quarter-Ton . . . . .	2900
Three-and-One-Half-Ton . . . . .	3800
Five-Ton . . . . .	4850




**ONEIDA ONE-AND-THREE-QUARTER-TON TRUCK—MODEL B-9**

COLOR . . . . .	Lead	CAST . . . . .	En bloc
CARRYING CAPACITY. . . . .	4550 pounds	HORSEPOWER . . . . .	25.6 (N.A.C.C. Rating)
POSITION OF DRIVER. . . . .	Left or right side	BORE AND STROKE . . . . .	4 x 5 1/4 inches
WHEELBASE . . . . .	144 inches	LUBRICATION . . . . .	Full force feed
GAUGE . . . . .	Front, 55 3/4 inches; rear, 57 1/2 inches	RADIATOR . . . . .	Cellular
WHEELS . . . . .	Wood	COOLING . . . . .	Water pump
FRONT TIRES . . . . .	36 x 3 1/2 inches, single solid	IGNITION . . . . .	High tension magneto
REAR TIRES . . . . .	36 x 6 inches, single solid	GASOLINE SYSTEM . . . . .	Vacuum
SERVICE BRAKE . . . . .	Expanding on rear wheels	CLUTCH . . . . .	Dry multiple disc
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective sliding
CYLINDERS . . . . .	Four	GEAR CHANGES . . . . .	Three forward, one reverse
HOW ARRANGED . . . . .	Vertically	DRIVE . . . . .	Worm
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and nut

**ONEIDA  
MOTOR TRUCK  
COMPANY**

**GREEN BAY  
WISCONSIN**

Price, Chassis . . . . .	\$3800
One-and-One-Quarter-Ton . . .	1985
One-and-Three-Quarter-Ton . .	2385
Two-and-One-Quarter-Ton . . .	2900
Five-Ton . . . . .	4850




**ONEIDA THREE-AND-ONE-HALF-TON TRUCK—MODEL D-9**

COLOR . . . . .	Lead	CAST . . . . .	En bloc
CARRYING CAPACITY. . . . .	8400 pounds	HORSEPOWER . . . . .	32.4
POSITION OF DRIVER. . . . .	Left or right side	(N.A.C.C. Rating)	
WHEELBASE . . . . .	170 inches, standard; 144 inches, dump bodies	BORE AND STROKE . . . . .	4½ x 5½ inches
GAUGE . . . . .	67 inches	LUBRICATION . . . . .	Full force feed
WHEELS . . . . .	Steel, spoke type	RADIATOR . . . . .	Cellular
FRONT TIRES . . . . .	36 x 5 inches, single solid	COOLING . . . . .	Water pump
REAR TIRES . . . . .	36 x 10 inches, dual solid	IGNITION . . . . .	High tension magneto, impulse starter
SERVICE BRAKE . . . . .	Expanding on rear wheels	GASOLINE SYSTEM . . . . .	Vacuum
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	CLUTCH . . . . .	Dry multiple disc
CYLINDERS . . . . .	Four	TRANSMISSION . . . . .	Selective sliding
HOW ARRANGED . . . . .	Vertically	GEAR CHANGES . . . . .	Four forward, one reverse
		DRIVE . . . . .	Worm
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and nut

**ONEIDA  
MOTOR TRUCK  
COMPANY**

**GREEN BAY  
WISCONSIN**

Price, Chassis . . . . .	\$4850
One-and-One-Quarter-Ton . . .	1985
One-and-Three Quarter-Ton . .	2385
Two-and-One-Quarter-Ton . . .	2900
Three-and-One-Half-Ton . . . .	3800




**ONEIDA FIVE-TON TRUCK—MODEL E-9**

COLOR . . . . .	Lead	CAST . . . . .	En bloc
CARRYING CAPACITY. . . . .	11,800 pounds	HORSEPOWER . . . . .	32.4 (N.A.C.C. Rating)
POSITION OF DRIVER. . . . .	Left or right side	BORE AND STROKE . . . . .	4½ x 5½ inches
WHEELBASE . . . . .	180 inches	LUBRICATION . . . . .	Full force feed
GAUGE . . . . .	Front, 68 inches; rear, 69 inches	RADIATOR . . . . .	Cellular
WHEELS . . . . .	Steel, spoke type	COOLING . . . . .	Water pump
FRONT TIRES . . . . .	36 x 6 inches, single solid	IGNITION . . . . .	High tension magneto, impulse coupling
REAR TIRES . . . . .	40 x 12 inches, single solid	GASOLINE SYSTEM . . . . .	Vacuum
SERVICE BRAKE . . . . .	Expanding on rear wheels	CLUTCH . . . . .	Dry multiple disc
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective, constant mesh
CYLINDERS . . . . .	Four	GEAR CHANGES . . . . .	Four forward, one reverse
HOW ARRANGED . . . . .	Vertically	DRIVE . . . . .	Worm
		REAR AXLE . . . . .	Semi-floating
		STEERING GEAR . . . . .	Worm and nut

**STERLING  
MOTOR TRUCK  
COMPANY**  
MILWAUKEE  
WISCONSIN

Price, Chassis . . . . .	\$3475
With Holst and Coal Dump Body . . . . .	4190
With Holst and Gravel Dump Body . . . . .	4115
With Flare Board Body . . . . .	3665
With Stake Body . . . . .	3665




### STERLING TWO-AND-ONE-HALF-TON TRUCK

COLOR . . . . .	Battleship gray	HORSEPOWER . . . . .	30.6 (N.A.C.C. Rating)
CARRYING CAPACITY. . . . .	5000 pounds	BORE AND STROKE . . . . .	4 $\frac{3}{8}$ x 5 $\frac{3}{4}$ inches
POSITION OF DRIVER. . . . .	Left side	LUBRICATION . . . . .	Force feed
WHEELBASE . . . . .	156 inches	RADIATOR . . . . .	Cellular
GAUGE . . . . .	58 $\frac{1}{2}$ inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Wood	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 4 inches, single solid	LIGHTING SYSTEM . . . . .	Oil
REAR TIRES . . . . .	36 x 4 inches, dual solid	WIRING SYSTEM . . . . .	Single
SERVICE BRAKE . . . . .	Expanding on rear axle	GASOLINE SYSTEM . . . . .	Vacuum tank
EMERGENCY BRAKE . . . . .	Expanding on rear axle	CLUTCH . . . . .	Dry plate multiple disc
CYLINDERS . . . . .	Four	TRANSMISSION . . . . .	Selective sliding
HOW ARRANGED . . . . .	Vertically	GEAR CHANGES . . . . .	Four forward, one reverse
CAST . . . . .	In pairs	DRIVE . . . . .	Worm
		REAR AXLE . . . . .	Full-floating
		STEERING GEAR . . . . .	Worm and nut

In addition to above specifications, price includes cab, curtains, windshield, horn, etc.

**THE  
CLYDESDALE  
MOTOR TRUCK  
COMPANY**  
CLYDE OHIO

Price Upon Application




---

**CLYDESDALE FIVE-TON TRUCK—120B**


---

COLOR . . . . .	Gray lead	HORSEPOWER . . . . .	36.1 (N.A.C.C. Rating)
CARRYING CAPACITY.	10,000 pounds	BORE AND STROKE . . .	4¼ x 6 inches
POSITION OF DRIVER.	Left side	LUBRICATION . . . . .	Full force feed
WHEELBASE . . . . .	204 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	Front, 68¾ inches; rear, 69½ inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Steel	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 6 inches, single solid	STARTING SYSTEM . . .	Two unit
REAR TIRES . . . . .	40 x 12 inches, solid	STARTER OPERATED . .	Gear to fly wheel
SERVICE BRAKE . . .	Expanding on rear wheels	GASOLINE SYSTEM . . .	Vacuum
EMERGENCY BRAKE .	Expanding on rear wheels	CLUTCH . . . . .	Dry multiple disc
CYLINDERS . . . . .	Four	TRANSMISSION . . . .	Selective sliding
HOW ARRANGED . . .	Vertically	GEAR CHANGES . . .	Four forward, one reverse
CAST . . . . .	In pairs	DRIVE . . . . .	Worm
		REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . .	Screw and nut

---

THE  
CLYDESDALE  
MOTOR TRUCK  
COMPANY  
CLYDE, OHIO

Price Upon Application




CLYDESDALE THREE-AND-ONE-HALF-TON TRUCK—90

COLOR . . . . .	Gray lead	HORSEPOWER . . . . .	32.4 (N.A.C.C. Rating)
CARRYING CAPACITY.	7000 pounds	BORE AND STROKE . .	4½ x 5½ inches
POSITION OF DRIVER.	Left side	LUBRICATION . . . . .	Splash with circulating pump
WHEELBASE . . . . .	190 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	Front, 66½ inches; rear, 65¾ inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Steel	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . .	36 x 5 inches, single solid	GASOLINE SYSTEM . .	Gravity
REAR TIRES . . . . .	40 x 10 inches, single solid	CLUTCH . . . . .	Dry multiple disc
SERVICE BRAKE . . .	Expanding on rear wheels	TRANSMISSION . . . .	Selective sliding
EMERGENCY BRAKE .	Expanding on rear wheels	GEAR CHANGES . . .	Four forward, one reverse
CYLINDERS . . . . .	Four	DRIVE . . . . .	Worm
HOW ARRANGED . . .	Vertically	REAR AXLE . . . . .	Full floating
CAST . . . . .	In pairs	STEERING GEAR . . . .	Screw and nut

# WALTER MOTOR TRUCK COMPANY

227-243 W. 61st ST.  
NEW YORK CITY

Price, Chassis . . . . . \$5500



## WALTER FIVE-TON TRUCK—MODEL "S"

COLOR . . . . .	Chrome green	HORSEPOWER . . . . .	32.4 (N.A.C.C. Rating)
CARRYING CAPACITY. . . . .	10,000 pounds	BORE AND STROKE . . . . .	4½ x 6¼ inches
POSITION OF DRIVER. . . . .	Left side	LUBRICATION . . . . .	Pressure feed
WHEELBASE . . . . .	168 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	Front, 66 inches; rear, 66 inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Cast steel	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 6 inches, single solid	GASOLINE SYSTEM . . . . .	Gravity
REAR TIRES . . . . .	40 x 6 inches, dual solid	CLUTCH . . . . .	Dry plate multiple disc
SERVICE BRAKE . . . . .	Contracting on differential	TRANSMISSION . . . . .	Selective sliding
EMERGENCY BRAKE . . . . .	Contracting on rear wheels	GEAR CHANGES . . . . .	Four forward, one reverse
CYLINDERS . . . . .	Four	DRIVE . . . . .	Suspended differential
HOW ARRANGED . . . . .	Vertically	REAR AXLE . . . . .	Solid forging
CAST . . . . .	In pairs	STEERING GEAR . . . . .	Worm and gear


In addition to above specifications, price includes cab, self-starter and electric lighting



**REPUBLIC  
MOTOR TRUCK  
COMPANY  
INCORPORATED**

**ALMA, MICHIGAN**

Standard Stake Body with Seat	} Prices Upon Appli- cation
Standard Stake Body with Cab and Curtains . . . . .	
Standard Stake Body with Ves- tibule Cab . . . . .	
Standard Three-Yard Dump Truck with Cab and Cur- tains . . . . .	
All Other Types of Bodies to Order . . . . .	




**REPUBLIC THREE-AND-ONE-HALF-TON TRUCK—MODEL 20**

COLOR . . . . .	Chassis, Republic yellow; seat, royal blue	CAST . . . . .	In pairs
CARRYING CAPACITY.	7000 pounds	HORSEPOWER . . . .	32.4 (N.A.C.C. Rating)
POSITION OF DRIVER.	Left side	BORE AND STROKE . .	4½ x 5½ inches
WHEELBASE . . . .	165 or 185 inches	LUBRICATION . . . .	Force feed and splash
GAUGE . . . . .	Front, 65 inches; rear, 66 inches	RADIATOR . . . . .	Tubular
WHEELS . . . . .	Steel, spoke type	COOLING . . . . .	Centrifugal pump
FRONT TIRES . . . .	36 x 5 inches, solid	IGNITION . . . . .	High tension magneto and impulse starter
REAR TIRES . . . .	36 x 10 inches, solid	GASOLINE SYSTEM . .	Gravity
SERVICE BRAKE . .	Double internal expanding on rear wheels	CLUTCH . . . . .	Dry multiple disc
EMERGENCY BRAKE .	External contract- ing type on rear axle pinion shaft	TRANSMISSION . . .	Selective sliding
CYLINDERS . . . .	Four	GEAR CHANGES . .	Four forward, one reverse
HOW ARRANGED . .	Vertically	DRIVE . . . . .	Internal gear
		REAR AXLE . . . .	Full floating
		STEERING GEAR . .	Worm and split nut

In addition to above specifications, price includes tools, side and rear oil lamps.

**BETHLEHEM  
MOTORS  
CORPORATION**  
**ALLENTOWN  
PENNSYLVANIA**

**Price, Chassis, \$3595**




---

**BETHLEHEM THREE-AND-ONE-HALF-TON TRUCK—FJ**


---

COLOR . . . . .	Body, green; running gear, red	BORE AND STROKE . . . . .	4½ x 5½ inches
CARRYING CAPACITY.	7000 pounds	LUBRICATION . . . . .	Force feed, gear pump
POSITION OF DRIVER.	Left side	RADIATOR . . . . .	Cellular
WHEELBASE . . . . .	162 inches	COOLING . . . . .	Thermo-syphon
GAUGE . . . . .	Front, 56 inches; rear, 65½ inches	IGNITION . . . . .	Storage battery
WHEELS . . . . .	Wood	STARTING SYSTEM . . . . .	Two unit
FRONT TIRES . . . . .	34 x 4 inches, single solid	STARTER OPERATED . . . . .	Gear to fly wheel
REAR TIRES . . . . .	34 x 5 inches, dual solid	LIGHTING SYSTEM . . . . .	Electric
SERVICE BRAKE . . . . .	External contract- ing on rear wheels	VOLTAGE . . . . .	Six
EMERGENCY BRAKE . . . . .	Internal expanding on rear wheels	WIRING SYSTEM . . . . .	Single
CYLINDERS . . . . .	Four	GASOLINE SYSTEM . . . . .	Gravity
HOW ARRANGED . . . . .	Vertically	CLUTCH . . . . .	Dry disc
CAST . . . . .	En bloc	TRANSMISSION . . . . .	Selective sliding
HORSEPOWER . . . . .	32.4 (N.A.C.C. Rating)	GEAR CHANGES . . . . .	Three forward, one reverse
		DRIVE . . . . .	Internal gear
		REAR AXLE . . . . .	Full floating
		STEERING GEAR . . . . .	Screw and nut

---

**SANFORD  
MOTOR TRUCK  
COMPANY**  
SYRACUSE  
NEW YORK

Price . . . . . \$5225  
Two-and-One-Half-Ton Chassis 3000  
Three-and-One-Half-Ton Chassis 3975  
Five-Ton Chassis . . . . . 4750




---

**SANFORD FIVE-TON TRUCK—W-50**


---

COLOR . . . . .	Body, green; running gear, red	HORSEPOWER . . . . .	32.4 (N.A.C.C. Rating)
CARRYING CAPACITY.	10,000 pounds	BORE AND STROKE . . . . .	4½ x 5½ inches
POSITION OF DRIVER.	Left side	LUBRICATION . . . . .	Force feed and splash
WHEELBASE . . . . .	174 inches	RADIATOR . . . . .	Tubular
GAUGE . . . . .	74½ inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Steel	IGNITION . . . . .	High tension magneto
FRONT TIRES . . . . .	36 x 5 inches, single solid	GASOLINE SYSTEM . . . . .	Gravity
REAR TIRES . . . . .	40 x 6 inches, dual solid	CLUTCH . . . . .	Dry disc
SERVICE BRAKE . . . . .	Expanding on rear wheels	TRANSMISSION . . . . .	Selective sliding
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GEAR CHANGES . . . . .	Four forward, one reverse
CYLINDERS . . . . .	Four	DRIVE . . . . .	Worm
HOW ARRANGED . . . . .	Vertically	REAR AXLE . . . . .	Semi-floating
CAST . . . . .	In pairs	STEERING GEAR . . . . .	Worm and nut

In addition to above specifications, price includes top, top hood, horn and bumper.

**PACKARD  
MOTOR CAR  
COMPANY**  
DETROIT  
MICHIGAN

One-and-One-Half-Ton—E	} Prices Upon Appli- cation
Two—Two-and-One-Half Ton—E . . . . .	
Three—Three-and-One-Half Ton—E . . . . .	
Four—Four-and-One-Half Ton—E . . . . .	
Five—Five-and-One-Half Ton—E . . . . .	
Six—Six-and-One-Half Ton—E . . . . .	



**PACKARD FIVE-TON TRUCK—5-E**

COLOR . . . . .	Gray	HORSEPOWER . . . . .	40 (N.A.C.C. Rating)
CARRYING CAPACITY.	12,500 pounds	BORE AND STROKE . . . . .	5 x 5½ inches
POSITION OF DRIVER.	Left side	LUBRICATION . . . . .	Force feed
WHEELBASE . . . . .	156 or 186 inches	RADIATOR . . . . .	Cellular
GAUGE . . . . .	Front, 69½ inches; rear, 69½ inches	COOLING . . . . .	Water pump
WHEELS . . . . .	Steel disc	IGNITION . . . . .	High tension magneto and storage battery
FRONT TIRES . . . . .	36 x 6 inches, single solid	GASOLINE SYSTEM . . . . .	Pressure
REAR TIRES . . . . .	40 x 6 inches, dual solid	CLUTCH . . . . .	Dry multiple disc
SERVICE BRAKE . . . . .	Contracting on drive shaft	TRANSMISSION . . . . .	Selective sliding
EMERGENCY BRAKE . . . . .	Expanding on rear wheels	GEAR CHANGES . . . . .	Four forward, one reverse
CYLINDERS . . . . .	Four	DRIVE . . . . .	Worm
HOW ARRANGED . . . . .	Vertically	REAR AXLE . . . . .	Full floating
CAST . . . . .	In fours	STEERING GEAR . . . . .	Worm and gear

## CATALOGUE REQUEST BLANK

(To be sent direct to manufacturer.  
For address see pages on which models are shown)

\_\_\_\_\_19

\_\_\_\_\_

GENTLEMEN:—Please send me catalogue describing your automobiles shown in the **HAND BOOK OF AUTOMOBILES** published by the National Automobile Chamber of Commerce, Inc., and oblige,

Name\_\_\_\_\_

Street\_\_\_\_\_City\_\_\_\_\_

## CATALOGUE REQUEST BLANK

(To be sent direct to manufacturer.  
For address see pages on which models are shown)

\_\_\_\_\_19

\_\_\_\_\_

GENTLEMEN:—Please send me catalogue describing your automobiles shown in the **HAND BOOK OF AUTOMOBILES** published by the National Automobile Chamber of Commerce, Inc., and oblige,

Name\_\_\_\_\_

Street\_\_\_\_\_City\_\_\_\_\_

## CATALOGUE REQUEST BLANK

(To be sent direct to manufacturer.  
For address see pages on which models are shown)

\_\_\_\_\_19

\_\_\_\_\_

GENTLEMEN:—Please send me catalogue describing your automobiles shown in the **HAND BOOK OF AUTOMOBILES** published by the National Automobile Chamber of Commerce, Inc., and oblige,

Name\_\_\_\_\_

Street\_\_\_\_\_City\_\_\_\_\_



## CATALOGUE REQUEST BLANK

(To be sent direct to manufacturer.  
For address see pages on which models are shown)

\_\_\_\_\_19

\_\_\_\_\_

GENTLEMEN:—Please send me catalogue describing your automobiles shown in the **HAND BOOK OF AUTOMOBILES** published by the National Automobile Chamber of Commerce, Inc., and oblige,

Name\_\_\_\_\_

Street\_\_\_\_\_City\_\_\_\_\_

## CATALOGUE REQUEST BLANK

(To be sent direct to manufacturer.  
For address see pages on which models are shown)

\_\_\_\_\_19

\_\_\_\_\_

GENTLEMEN:—Please send me catalogue describing your automobiles shown in the **HAND BOOK OF AUTOMOBILES** published by the National Automobile Chamber of Commerce, Inc., and oblige,

Name\_\_\_\_\_

Street\_\_\_\_\_City\_\_\_\_\_

## CATALOGUE REQUEST BLANK

(To be sent direct to manufacturer.  
For address see pages on which models are shown)

\_\_\_\_\_19

\_\_\_\_\_

GENTLEMEN:—Please send me catalogue describing your automobiles shown in the **HAND BOOK OF AUTOMOBILES** published by the National Automobile Chamber of Commerce, Inc., and oblige,

Name\_\_\_\_\_

Street\_\_\_\_\_City\_\_\_\_\_

BENTLEY HISTORICAL LIBRARY




3 9015 07120 9715











5007  
F-400

